



AUDIT ST-1 MPI SHOT TIMER

To maintain product quality it is important that every aspect of an inspection system is monitored regularly. In particular the performance of an MPI system is dependent on a number of parameters, each of which must be within acceptable procedural limits.

Where magnetizing equipment is fitted with a timer to control shot duration, it must be calibrated on a regular basis, usually to an accuracy within ± 0.1 sec.

ADVANTAGES

- A precision hand-held electronic timer that is specifically designed to check timer controls fitted to MPI benches.
- The AUDIT ST-1 has a resolution of 0.02 sec and is able to make accurate measurement of the duration of a magnetizing shot in respect of AC, HWDC and FWDC waveforms.
- Operates equally for current flow, coil and flux flow magnetizing methods.
- Can accommodate dual shots, recording both the first and second shot times and the duration of the rest interval.
- Fully calibrated using equipment traceable to National Standards.

KEY BENEFITS

SHOT DISPLAY

Audit ST-1 displays the shot duration for current flow, coil and flux flow with selectable resolutions of either 0.1s or 0.02s. Additionally the magnetizing waveforms are indicated, "A"=AC, "H"=HWDC, "F"=FWDC.

EASY TO USE

Simply press the ON button and the instrument operates at the 0.1s resolution. Press and hold the ON button and it operates at the 0.02s resolution.

Audit ST-1 is held in-line with the magnetizing coil or a current flow component and the shot performed and displays the shot duration and the waveform code as described.

Then briefly press the ON button to reset the instrument.

VERSATILE

Audit ST-1 can also measure two successive shot times and the rest interval (up to a maximum of 4 seconds), on dual-shot equipment.

SPECIFICATION	
General	Audit ST-1 is a microprocessor controlled precision instrument housed in a rigid injection moulded plastic case, with front panel membrane ensuring excellent environmental protection. A magnetic field with a strength of 20mT (200 Gauss) or more.
Trigger	0.02 seconds to 9.98 seconds.
Range	0.1 seconds or 0.02 seconds.
Resolution	0.1 seconds or 0.02 seconds
Accuracy	dependent upon resolution selected.
Battery Type	1xPP3
Low Battery Threshold	6.5V approx.
Auto-shutdown	after 60 seconds.
Display	4 Segment LCD
Dimensions	3.2" (w) x 6" (h) x 1.4" (d)
Weight	0.52 lbs (including battery).

Audit ST-1 is supplied complete with:

- Carrying case.
- Operating instructions.
- Baugh & Weedon Ltd's comprehensive two year guarantee.



Document number BR1004: Issue 1

