



## Sound Absorbing Panel Specifications

ACOUSTIC PANEL TYPES	FIBERGLASS CORE CONSTRUCTION	TOTAL THICKNESS W/O MFG	ACOUSTIC PANEL EDGE DETAIL	NRC
<b>TRENDSETTER II BAFFLE</b>	1" OR 2" CORE 6-7 lb. density	2"	Routed edge to conceal seam	2" = 1.00
<b>PS-80AL BAFFLE</b>	1" or 2" CORE 4-7 lb. density	1-5/16" 2-5/16"	Square edge only	1-5/16" = 0.80 2-5/16" = 1.00

## Sound Absorbing TRIMLINE Panel Specifications

TYPE	DENSITY	THICKNESS	COVER	126Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	NRC
<b>TRIMLINE</b>	10lb	½"	FR701	0.04	0.11	0.38	0.80	0.98	1.04	0.55
<b>TRIMLINE</b>	10lb	½"	Vinyl	0.00	0.15	0.56	0.93	0.94	0.78	0.65
<b>TRIMLINE</b>	10lb	½"	Polyolefin	0.14	0.44	1.09	0.91	0.80	0.89	0.80
<b>TRIMLINE</b>	8lb	½"	Vinyl	0.09	0.10	0.36	0.81	1.09	1.21	0.60

Panel Solutions, Inc. 100 East Diamond Ave. Hazleton, PA 18201

570-459-3490

[www.panelsolutions.com](http://www.panelsolutions.com)