

PRO MAX SERIES SPECIFICATIONS

Display	Model	JFP65AV14	JFP75AV14	JFP86AV14
	Size	65"	75"	86"
	Backlight	D-LED		
	Glue Type	Zero Bonding (0.5mm)		
	OD	35		
	Visible Screen Area	1428 x 803 mm	1650 x 928 mm	1895 x 1066mm
	Aspect Ratio	16:9		
	Resolution	3840 x 2160 (4K)		
	Color Spectrum	72% NTSC		
	Number of Color	1.07 Billion		
	Glass Thickness	Level 7 MoHS 3.2mm Tempered Glass		
	Brightness	≥400 cd/m²		
	Contrast	1200:1		
	Response Time	8ms (typ.)		
	Viewing Angle	H = 178, V = 178 typ.		
	Life Time	≥50000 hours		
Touch Solutions	Touch Solutions	IR		
	Surface Treatment	Anti-glare & Anti-Sratch		
	Transparency	88%±3		
	Haze	4-8%		
	Hardness	> 7H		
	Touch Diameter	Φ 0.5mm		
	Response Time	≤6ms		
	Number of touches	40-touch points		
	Palm rejection	Support		
	Support OS	Windows, Mac, Android, Linux, Chrome		
	Tools	Pen & Finger		
Electrical Performance	Operating Voltage	AC100-240V		
	Power Consumption	≤250W	≤350W	≤450W
	Standby Mode	<0.5W		
Android System	Mainboard	A311D2		
	CPU	Octa-Core A73*4 (2.2GHZ) +A53*4 (2.20GHZ)		
	GPU		Mali-G52	
	RAM	8G		
	ROM	128G		
	Android Version	Android 14		
Interface	Rear	RJ 45 10/100/1000M*2, LINE OUT 3.5mm*1, VGA*1, AUDIO IN 3.5mm*1, USB 2.0*1, COAX/SPDIF Optical, RS232 DP9*1, TOUCH USB 3.0*2, TYPE-C IN USB*1, HDMI IN 2.0*2, DP IN 1.2*1, HDMI OUT 2.0*1, USB 3.0*2		
	Front	USB-A 3.0*2, TOUCH USB-B 3.0*1, HDMI IN 2.0*1, TYPE-C DP1.2*1+USB 2.0+Lan+TOUCH+PD15W		
Physic button	Button	Seven		
Others	WIFI	WiFi 6		
	BT	BT 5.0		
	Screen Casting Software	Eshare		
	Built-in Camera	48MP AI Auto-Framing & Voice Tracking		
	Built-in Microphone	8-Arrays		
	Speaker	15W*2		
	Sub-Woofer	20W		
Transportation/Storage Conditions	Storage Temperature/Humidity	-10~55°C 20~90%RH		
	Operating Temperature/Humidity	0~55°C 20~80%RH		
	Installation	Wall mount/Portable Stand		
	Panel Size	1490.6*887.5*116.5mm	1712.9*1012.8*116.5mm	1958.92*1151.7*116.5mm
	Packing Size	1576*980*230mm	1785*1125*200mm	2040*1260*200mm
	Net Weight	43±1 kg	55KG±1	70KG±1
	Gross Weight	57.5±1 kg	70KG±1	84KG±1