

Introduce young learners to a world of interactive learning with the new Javiya Pro Max. Designed with teachers and little learners in mind, it runs on the latest Android 14 OS for a smooth, safe, and easy classroom experience.

With a built-in whiteboard, touch-friendly interface, and wireless screen sharing, Javiya Pro Max makes lessons more engaging and fun. Kids can draw, play educational games, and learn together—all on a big, bright 4K display with anti-glare glass for safe viewing.

Teachers can easily connect to the panel using any device—Windows, Android, or iPad. Simple, colourful, and powerful, Javiya Pro Max is the perfect tool for active, joyful learning in every classroom.

PRO MAX SERIES SPECIFICATIONS

	Model	JFP65AV14	JFP75AV14	JFP86AV14
Display	Size	65"	75"	86"
	Backlight	D-LED		
	Glue Type	Zero Bonding (0.5mm)		
	OD OD	35		
	Visible Screen Area	1428 x 803 mm	1650 x 928 mm	1895 x 1066mm
	Aspect Ratio	1120 X 000 11111	16:9	1000 X 1000
	Resolution	3840 x 2160 (4K)		
	Color Spectrum	72% NTSC		
	Number of Color	1.07 Billion		
	Glass Thickness	Level 7 MoHS 3.2mm Tempered Glass		
	Brightness	≥400 cd/m²		
	Contrast	1200:1		
	Response Time	8ms (typ.)		
	Viewing Angle	H = 178, V = 178 typ.		
	Life Time	≥50000 hours		
	Touch Solutions	IR		
Touch Solutions	Surface Treatment	Anti-glare & Anti-Sratch		
	Transparency	88%±3		
	Haze	4-8%		
	Hardness	>7H		
	Touch Diameter	Ф 0.5mm		
	Response Time	≤6ms		
	Number of touches	40-touch points		
	Palm rejection	Support		
	Support OS	Windows, Mac, Android, Linux, Chrome		
	Tools	Pen & Finger		
Electrical Performance	Operating Voltage	AC100-240V		
	Power Consumption	≤250W	≤350W	≤450W
	Standby Mode		<0.5W	
Android System	Mainboard	A311D2		
	CPU	Octa-Core A73*4 (2.2GHZ) +A53*4 (2.20GHZ)		
	GPU	Mali-G52		
	RAM	86		
	ROM	128G		
	Android Version	Android 14		
Interface		RJ 45 10/100/1000M*2, LINE OUT 3.5mm*1, VGA*1, AUDIO IN 3.5mm*1, USB 2.0*1,		
	Rear	COAX/SPDIF Optical, RS232 DP9*1, TOUCH USB 3.0*2, TYPE-C IN USB*1, HDMI IN 2.0*2,		
		DP IN 1.2*1, HDMI OUT 2.0*1, USB 3.0*2		
	Front	USB-A 3.0*2, TOUCH USB-B 3.0*1, HDMI IN 2.0*1, TYPE-C DP1.2*1+USB		
		2.0+Lan+TOUCH+PD15W		
Physic button	Button	Seven		
Others	WIFI	WiFi 6		
	ВТ	BT 5.0		
	Screen Casting Software	Eshare		
	Built-in Camera	48MP AI Auto-Framing & Voice Tracking		
	Built-in Microphone	8-Arrays		
	Speaker	15W*2		
	Sub-Woofer	20W		
Transportation/Storage Conditions	Storage	-10~55°C		
	Temperature/Humidity	20~90%RH		
	Operating Temperature/Humidity	0~55°C 20~90% PH		
	Installation	20~80%RH Wall mount/Portable Stand		
	mstallation	waii iiiouiit, roi table Staliu		
	Panel Size	1490.6*887.5*116.5mm	1712.9.2*1012.8*116.5mm	1958.92*1151.7*116.5mm
	Packing Size	1576*980*230mm	1785*1125*200mm	2040*1260*200mm
	Net Weight	43±1 kg	55KG±1	70KG±1
	Gross Weight	57.5±1 kg	70KG±1	84KG±1



4K Display



Multi Touch



Wi-Fi 6



Powered USB Type-C



Optional OPS Slot Ready



Zero Bonding



Broad Compatibility

The content of this document are subject to change without notice

Authorised Dealer:



*Microsoft and Windows are trademarks of the Microsoft group of companies
*MAC is trademark of the Apple Inc.





