

USS-DESTROYER™ | 350-750 TON WIRELINE FRAME

- API 8C Specifications for Drilling and Production Hoisting Equipment
- Articulating Lift Sub
- Off-Center Main Hoist for centering wire
- Turret Manipulator Arms (21K Capacity)
- Link Pins on Frame to Eliminate Risk
- DNV Certified Main Hoist (40K Capacity)
- Wide Work Window between Links
- CID2 Electric Power Pack
- Traditional Bail | Elevator Option Available



UNITEDSUBSEA.COM



UNITED SUBSEA
SPECIALIST

USS BATTLESHIP™ | 15M SURFACE TEST TREE

- 8 ft OAL | 13,000 lb. (With War-Lift Device)
- 7-1/16" API Flange Top Connection
- 6.5" Internal Diameter
- 750T Capacity (1.5 Million Lb. Swivel)
- 3-1/16" Flanged Wing Outlets
- API 17-G 2nd Edition Design
- API 6A 20th Edition | PSL3
- Dual actuators on Swab & Master (Faster close time & more powerful)
- ESD System
- CID2 Power Pack
- Integral Swab Valve within Body
- Fail Safe Close Gate Valves (Choke & Kill Valves)
- Metal to Metal Seal w/ Insert Backup (Swab & Master Valve)
- Additional Backup Seat on Master Valve
- Chemical Injection access below Master Valve



CONFIDENTIAL

UNITEDSUBSEA.COM



UNITED SUBSEA
SPECIALIST