



# APPLICATION GUIDE FOR DUSTRX HYDRO

**DustRX Hydro is formulated for use in both hydroseeders and water trucks.  
Hydroseeder applications can be completed using tower or hose.**

**Additional applications may be necessary depending on project needs, climates, soil types, or on higher traffic areas for best performance.**

## Hydroseeder Application/Loading Procedures

- A.** Strictly comply with equipment manufacturer's instructions and recommendations. Use approved hydro-spraying machines with the appropriate nozzle whenever possible to achieve best soil coverage.
- B.** To ensure proper application rates, measure and stake area.
- C.** Consult loading chart below to determine number of bags to be added for the desired area and application rate.
- D.** Add DustRX Hydro to tank slowly at the predetermined amount of DustRX Hydro during continual agitation allowing suitable time for material to activate. Increased concentration rates can be utilized with equipment capable of mixing and pumping higher viscosity solutions.
- E.** Apply evenly over substrate and visually monitor to ensure uniform coverage.
- F.** Upon completion of application, return immediately to water source to repeat mixing and application sequence or to flush equipment. Be sure to thoroughly purge pump and all lines of residual material.

## Water Truck Application/Loading Procedures

- A.** Strictly comply with equipment manufacturer's instructions and recommendations. Use approved watering trucks with the appropriate nozzle whenever possible to achieve best soil coverage.
- B.** To ensure proper application rates, measure and stake area.
- C.** Consult loading chart on below to determine number of bags to be added for the desired area and application rate.
- D.** Add DustRX Hydro to the water tank slowly at the predetermined amount as you fill the water truck allowing suitable time for material to activate. Increased concentration rates can be utilized with equipment capable of spraying higher viscosity solutions.
- E.** Apply evenly over substrate and visually monitor to ensure uniform coverage.
- F.** Upon completion of application, return immediately to water source to repeat mixing and application sequence or to flush equipment. Be sure to thoroughly purge pump and all lines of residual material. Clean out tank at end of application.

## Hydroseeder & Water Truck Application Rate

APPLICATION RATE	
100 lbs/acre [112 kg / Hectare]	Dependent on soil composition and site condition
MIXING	
Mixing Rate	50 lbs/1,000 gallons of water [22.7 kg/ 3,790 liters of water]

Product spills and wet surfaces may present slippery or hazardous conditions. Use caution on truck decks, lids and other surfaces.