

<u>Container Specification</u>	Interior Dimensions (mm)	Door Opening (mm)	Load Capacity (cbm)	Cargo Loadable (cbm)	Max Payload (kg)	Container Weight (kg)	Max Gross Weight (kg)
20FT DRY CONTAINER	L 5,897 W 2,348 H 2,385	W 2,337 H 2,272	33.0		21,710	2,290	24,000
40FT DRY CONTAINER	L 12,031 W 2,348 H 2,385	W 2,337 H 2,272	67.4		26,710	3,770	30,480
40FT ALUM-DRY CONTAINER	L 12,031 W 2,344 H 2,382	W 2,337 H 2,280	67.3		27,530	2,950	30,480
40FT H/C DRY CONTAINER	L 12,031 W 2,348 H 2,690	W 2,337 H 2,577	76.0		26,490	3,990	30,480
20FT STEEL CONTAINER	L 5,455 W 2,290 H 2,262	W 2,290 H 2,227	28.3	26.4	21,040	2,960	24,000
40FT H/C ALUM REEFER CONTAINER	L 11,585 W 2,290 H 2,238	W 2,290 H 2,491	67.0	64.3	28,340	4,160	32,500
40FT H/C STEEL REEFER CONTAINER	L 11,583 W 2,290 H 2,527	W 2,290 H 2,508	67.3	63.3	27,700	4,800	32,500
20FT OPEN TOP CONTAINER	L 5,898 W 2,346 H 2,354	W 2,338 H 2,244	32.6		21,550	2,450	24,000
40FT OPEN TOP CONTAINER	L 12,022 W 2,346 H 2,381	W 2,337 H 2,244	66.4		26,460	4,020	30,480
20FT FLAT RACK CONTAINER	L 5,958 W 2,236 H 2,077		25.0		27,760	2,720	34,000
40FT FLAT RACK CONTAINER	L 11,986 W 2,236 H 1,968		52.7		39,020	5,980	45,000

CARGO LOADABLE: Only used reefer container below cargo limit line- REEFER CONTAINER MAX GROSS WEIGHT: M.G.W. for test to be 35,500 by MANUFACTOR

Weight and Measure Conversion:

AIR FREIGHT	1/6 (1 ton/6cbm) = 1cbm/167 kilos
OCEAN FREIGHT	1/1 (1ton/1cbm) = 1cbm/1,000 kilos
TRUCKING	1/3 (1ton/3cbm) = 1cbm/333 kilos