

## LED Linear Vapor Tight # OG-LED-VT



### SPECIFICATION INFORMATION

LED Brand	Epistar
Driver Brand	Meanwell
Dimming	0-10V
Beam Angles Available	120°
Ingress Protection	IP66
Installation	Surface or suspension cable
Finishes available (colors)	White, Silver, Black
Power consumption	80w, 120w, 160w, 180w, 200w, 240w, 300w
Input Voltage	100 -277VAC, 50/60HZ
Color Temperatures Available	3000K, 4000K, 5000K, 6500K
Options	Motion Sensor, Emergency Backup
Luminous efficiency	≥105LM/W
CRI	83+
Warranty	5 years
Certifications	UL, ETL, CE, Rohs, FCC

### ORDERING INFO

Model No.	Wattage	Dimensions(mm)		Lumens Flux
OG-LED-VT-210-SF-2	20W	2 ft	618X116X74	2000-2200 LM
OG-LED-VT-220-SF-4	40W	4 ft	1215X116X74	4000-4300 LM
OG-LED-VT-230-SF-4	60W	4 ft	1215X116X74	6600-7200 LM
OG-LED-VT-225-SF-5	50W	5 ft	1515X116X74	5000-5300 LM
OG-LED-VT-230-SF-5	60W	5 ft	1515X116X74	6000-6300 LM
OG-LED-VT-420-SF-4	80W	4 ft	1274X140X90	8000-8400 LM