

LED Troffer # OG-PLED



Intertek



SPECIFICATION INFORMATION

LED Brand	Ilumileds
Driver Brand	Meanwell
Dimming	0-10V
Beam Angles Available	120°
Ingress Protection	IP20
Installation	Surface or suspension cable
Finishes available (colors)	White, Silver, Black
Power consumption	80w, 120w, 160w, 180w, 200w, 240w, 300w
Input Voltage	100 -277VAC, 50/60HZ
Color Temperatures Available	3000K, 4000K, 5000K, 6500K
Luminous efficiency	≥105LM/W
CRI	83+
Warranty	5 years
Certifications	UL, ETL, CE, Rohs, FCC

ORDERING INFO

MODEL NO.	WATTAGE	DIMENSION(mm) L * W * H	LUMENS
OG-PLED-420	80W	615x285x100	8400lm/10400lm
OG-PLED-620	120W	615x285x100	12600lm/15600lm
OG-PLED-420	80W	1215x285x100	8400lm/10400lm
OG-PLED-430	120W	1215x285x100	15600lm
OG-PLED-440	160W	1215x285x100	19200lm
OG-PLED-450	200W	1500x285x100	24000lm
OG-PLED-620	120W	1215x285x100	12600lm/15600lm
OG-PLED-630	180W	1215x285x100	23400lm
OG-PLED-640	240W	1215x285x100	28800lm
OG-PLED-650	300W	1500x285x100	36000lm