



DEERE

MOVE THE WORLD

ABOUT DEESTONE

DEESTONE was founded in 1977 by Mr. Suvit Vongsariyanich. The company's vision is to manufacture quality tires for vehicles. Deestone's business philosophy "Integrity, Honesty, and Accountability" have resulted our company with worldwide reputation, qualifies with the global standards and trusted by more than 120 countries. With over 40 years of experience Deestone has been producing quality tires, while continuously developing every product to the highest standard. The use of new technology has allowed Deestone to create innovations that it meets specific application and use, which answers market demand. Deestone also concerns about environmental factors making our company environmental friendly. We ensure that all of our standard certification is up-to-date. All of our goals are to make our customers trust and proud when using our products.

All products of company serves various market demand which consist of high standard of production and certified with global standards. Deestone Group offers the after sales service to customers, with social responsibilities and warranty on the quality of company's products through all channel of communication with completely and clearly information. Product and brand image have been developing for highest customer satisfaction. We develop and produce quality tires for all segments of vehicles to be a part of your journey.





CONTENT

ABOUT US	2
FRONT FARM	4
REAR FARM	6
TRACTOR	9
AGRICULTURAL IMPLEMENT	12
INDUSTRIAL LIFT TRUCK	14
INDUSTRIAL TRACTOR	16
INDUSTRIAL IMPLEMENT	18
FORKLIFT	20
SKID STEER	23
DUMPER	25
ATV	27
GOLF CART	31
GO CART	33
WHEEL BARROW	35
LAWN AND GARDEN	37
EARTH MOVING	41
LOADER & DOZER	43
GRADER & COMPACTOR	45

FRONT FARM



**D401(F-2)**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D401 (F-2)	3.50-6	2	19A6	TT	355	103	7.2	20/140	78/171	30/20	3.00
	3.50-6	4	33A6	TT	355	103	7.2	35/240	115/254	30/20	3.00
	4.00-6	2	20A6	TT	385	112	6.7	18/120	80/176	30/20	3.00
	3.50-8	2	25A6	TT	395	103	6.7	20/140	92.2/204	30/20	3.00
	3.50-8	4	37A6	TT	395	103	6.7	35/240	128/280	30/20	3.00
	4.00-8	2	30A6	TT	435	112	6.7	17/120	106/234	30/20	3.00
	4.00-8	4	43A6	TT	435	112	6.7	35/240	155/340	30/20	3.00
	4.00-10	4	48A6	TT	485	112	6.7	35/240	180/395	30/20	3.00
	4.00-12	4	56A8	TT	539	112	6.7	52/360	225/495	40/25	3.00
	5.60-13	6	68A8	TT	640	150	12.5	56/385	315/695	40/25	4.00
	5.00-15	4	69A8	TT	664	130	16.3	44/300	325/715	40/25	3.00
	5.00-15	6	75A8	TT	664	130	16.3	56/385	387/855	40/25	3.00
	5.50-16	6	82A8	TT	713	150	14.4	56/385	475/1050	40/25	4.00
	6.00-16	6	85A8	TT	739	159	20.1	52/360	515/1140	40/25	4.00
	6.50-16	6	88A8	TT	761	173	20.1	48/330	560/1230	40/25	4.50
	7.50-16	6	94A8	TT	808	203	23.5	44/300	670/1480	40/25	5.50
	7.50-16	8	99A8	TT	808	203	23.5	56/385	775/1710	40/25	5.50
	9.00-16	10	116A8	TT	855	234	24.0	56/390	1250/2755	40/25	6.00
	10.00-16	8	110A8	TT	894	274	27.0	44/300	1060/2340	40/25	8.00
	10.00-16	10	119A8	TT	894	274	27.0	50/340	1360/3000	40/25	8.00
11.00-16	8	114A8	TT	967	315	30.5	40/275	1180/2600	40/25	10.00	
11.00-16	10	122A8	TT	967	315	30.5	45/310	1500/3305	40/25	10.00	
7.50-18	8	102A8	TT	859	203	19.2	56/385	850/1870	40/25	5.50	
4.00-19	4	69A8	TT	717	112	10.5	52/360	325/715	40/25	3.00	
6.00-19	8	93A8	TT	814	165	22.0	48/330	690/1520	40/25	4.50	

REAR FARM





D409

D312A

D312B

D312C

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D409	9.5-24	6	102A8	TT	1048	241	38.4	30/210	850/1870	40/25	8.00
	9.5-24	8	109A8	TT	1048	241	38.4	40/275	1030/2270	40/25	8.00
	9.5-24	10	115A8	TT	1048	241	38.4	50/345	1215/2680	40/25	8.00
D312A	11.2-24	6	106A8	TL	1103	284	23.0	26/180	950/2090	40/25	10.00
	11.2-24	8	113A8	TT	1103	284	23.0	36/250	1150/2540	40/25	10.00
	11.2-24	8	113A8	TL	1103	284	23.0	36/250	1150/2540	40/25	10.00
D312B	12.4-24	6	111A8	TL	1159	315	44.0	24/165	1090/2400	40/25	11.00
	12.4-24	8	117A8	TT	1159	315	44.0	32/220	1285/2830	40/25	11.00
	12.4-24	8	117A8	TL	1159	315	44.0	32/220	1285/2830	40/25	11.00
	12.4-24	10	121A8	TL	1159	315	44.0	40/280	1450/3195	40/25	11.00
D312C	14.9-24	6	119A8	TL	1265	378	37.0	20/140	1360/3000	40/25	13.00
	14.9-24	8	124A8	TL	1265	378	37.0	26/180	1600/3520	40/25	13.00

**D312D****D312E****D317****D321**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D312D	18.4-26	12	142A8	TT	1450	467	38.4	32/220	2650/5840	40/25	16.00
		12	142A8	TL	1450	467	38.4	32/220	2650/5840	40/25	16.00
D312E	13.6-24	6	115A8	TL	1210	345	35.0	22/150	1215/2680	40/25	12.00
		8	120A8	TL	1210	345	35.0	28/190	1400/3080	40/25	12.00
	14.9-24	8	124A8	TL	1265	378	35.0	26/180	1600/3525	40/25	13.00
	13.6-28	8	122A8	TL	1311	345	35.0	28/190	1500/3300	40/25	12.00
	14.9-28	8	126A8	TL	1367	378	35.0	26/180	1700/3740	40/25	13.00
		10	130A8	TL	1367	378	35.0	32/220	1900/4180	40/25	13.00
	16.9-28	8	131A8	TL	1435	429	37.0	24/170	1950/4300	40/25	15.00
		10	134A8	TL	1435	429	37.0	28/190	2120/4680	40/25	15.00
	16.9-30	8	132A8	TL	1485	429	37.0	24/165	2000/4410	40/25	15.00
	18.4-30	8	135A8	TT	1552	467	28.8	20/140	2180/4800	40/25	16.00
		8	135A8	TT	1552	467	40.0	20/140	2180/4800	40/25	16.00
		12	145A8	TT	1552	467	28.8	32/220	2900/6400	40/25	16.00
		12	145A8	TT	1552	467	40.0	32/220	2900/6400	40/25	16.00
	18.4-34	10	143A8	TL	1654	467	40.0	26/180	2725/6000	40/25	16.00
	13.6-38	10	-/A8	TT	1565	345	35.0	33/230	2015/4400	40/25	11.00
	18.4-38	10	145A8	TL	1755	467	40.0	26/180	2900/6400	40/25	16.00
		12	149A8	TL	1755	467	40.0	32/220	3250/7150	40/25	16.00
	20.8-38	10	148A8	TL	1834	528	40.0	22/150	3150/6950	40/25	18.00
12		152A8	TL	1834	528	40.0	28/190	3550/7850	40/25	18.00	
D317	12.4-24	8	117A8	TT	1159	315	30.7	32/220	1285/2830	40/25	11.00
D321	8.3-20	4	88A6	TT	890	211	42.5	24/160	560/1235	30/20	7.00
		6	96A6	TT	890	211	42.5	35/240	710/1560	30/20	7.00
	8.3-24	6	100A6	TT	995	211	39.0	35/240	800/1760	30/20	7.00
	9.5-24	6	106A6	TT	1048	241	37.0	30/210	950/2090	30/20	8.00
	11.2-24	6	106A8	TT	1103	284	48.0	26/180	950/2090	40/25	10.00
		8	113A8	TT	1103	284	48.0	36/250	1150/2540	40/25	10.00
	12.4-24	6	111A8	TT	1159	315	50.0	24/165	1090/2400	40/25	11.00
		8	117A8	TT	1159	315	50.0	32/220	1285/2830	40/25	11.00
	13.6-26	6	116A8	TT	1260	345	50.0	22/150	1250/2760	40/25	12.00
		8	121A8	TT	1260	345	50.0	28/190	1450/3200	40/25	12.00

TRACTOR





D402A

D402B

D405A

D405B

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D402A	3.50-5	2	16A6	TT	330	103	10.6	20/140	71/157	30/20	3.00
		4	31A6	TT	330	103	10.6	35/240	109/240	30/20	3.00
	3.50-6	2	19A6	TT	355	103	10.6	20/140	78/171	30/20	3.00
		4	33A6	TT	355	103	10.6	35/240	115/254	30/20	3.00
	4.00-8	2	30A6	TT	435	112	11.5	18/120	106/234	30/20	3.00
		4	43A6	TL	435	112	11.5	35/240	155/340	30/20	3.00
		4	43A6	TT	435	112	11.5	35/240	155/340	30/20	3.00
	4.00-10	4	48A6	TT	485	112	11.5	35/240	180/395	30/20	3.00
4		48A6	TL	485	112	11.5	35/240	180/395	30/20	3.00	
D402B	6.00-14	4	73A8	TT	674	167	14.0	36/250	365/800	40/25	4.00
		6	81A8	TT	674	167	14.0	52/360	462/1020	40/25	4.00
	7.50-16	4	91A8	TT	805	205	23.0	29/200	615/1355	40/25	5.50
		8	103A8	TT	805	205	23.0	54/370	875/1930	40/25	5.50
D405A	3.50-5	2	16A6	TT	330	103	8.7	20/140	71/157	30/20	3.00
		4	31A6	TT	330	103	8.7	35/240	109/240	30/20	3.00
	3.50-6	2	19A6	TT	355	103	11.0	20/140	78/171	30/20	3.00
		4	33A6	TT	355	103	11.0	35/240	115/254	30/20	3.00
	3.50-7	2	22A6	TT	370	103	11.0	20/140	85/187	30/20	3.00
		4	35A6	TT	370	103	11.0	35/240	121/267	30/20	3.00
	4.00-8	2	30A6	TT	435	112	17.0	18/120	106/234	30/20	3.00
		4	43A6	TT	435	112	17.0	35/240	155/340	30/20	3.00
4.00-9	4	46A6	TT	460	112	17.0	35/240	170/375	30/20	3.00	
4.00-10	4	48A6	TT	485	112	16.0	35/240	180/395	30/20	3.00	
D405B	23x8.50-12 SEG	4	84A4	TL	574	213	14.0	22/150	500/1100	20/15	7.00
		6	93A4	TL	574	213	14.0	34/230	650/1430	20/15	7.00
	23x10.50-12 SEG	4	90A4	TL	579	264	14.4	20/140	600/1320	20/15	8.50
		6	100A4	TL	579	264	14.4	32/220	800/1760	20/15	8.50
		10	118A3	TL	579	264	14.4	54/375	1320/2910	15/10	8.50

**D405C****D407****D408****D413**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D405C	26x12.00-12 SEG	4	100A4	TL	648	307	18.0	20/140	800/1760	20/15	10.50
		6	104A3	TL	648	307	18.0	34/230	900/1985	15/10	10.50
D407	13x5.00-6	4	52A3	TL	320	122	7.7	40/280	200/440	15/10	3.50
	16x6.50-8	4	64A3	TL	406	165	9.6	28/190	280/615	15/10	5.375
D408	26x12.00-12	8	117A4	TL	648	307	18.4	48/330	1285/2835	20/15	10.50
		10	120A4	TL	648	307	18.4	60/415	1400/3085	20/15	10.50
D413	5-12	4	56A6	TT	528	127	23.0	34/235	224/495	30/20	4.00
	180/85D12	4	-/A6	TT	611	173	24.0	23/160	270/595	30/20	5.00
	7-14	4	72A6	TT	691	183	26.0	24/160	355/785	30/20	6.00
		6	80A6	TT	691	183	26.0	36/250	450/990	30/20	6.00
	7-16	4	75A6	TT	742	183	25.0	24/160	387/855	30/20	6.00
		6	84A6	TT	742	183	25.0	36/250	500/1100	30/20	6.00
	8-16	4	83A6	TT	790	211	26.8	18/125	487/1070	30/20	6.00
		6	91A6	TT	790	211	26.8	28/190	615/1360	30/20	6.00
8-18	4	85A6	TT	841	211	26.8	18/125	515/1140	30/20	6.00	
	6	94A6	TT	841	211	26.8	28/190	670/1480	30/20	6.00	

AGRICULTURAL IMPLEMENT





D308(PG)

D315

D402B

D412

D8301

I-1

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH (mm)	INFLATION PRESSURE (PSI/kPa)	MAX. LOAD		MAX. SPEED (KPH/MPH)	RIM WIDTH (Inch)
					OD(mm)	SW(mm)			FREE ROLLING	DRIVE WHEEL		
D308	16.5/85-24	12	162/150A8	TT	1322	417	38.4	42/290	4750/10500	3350/7390	40/25	13.00
		12	162/150A8	TL	1322	417	38.4	42/290	4750/10500	3350/7390	40/25	13.00
	15.5/80-24	12	157/145A8	TL	1240	394	38.4	43/300	4125/9090	2900/6395	40/25	13.00
		12	157/145A8	TT	1240	394	38.4	43/300	4125/9090	2900/6395	40/25	13.00
		16	163/151A8	TL	1240	394	38.4	75/515	4875/10740	3450/7600	40/25	13.00
D315	11.5/80-15.3	14	139/126A8	TL	845	290	9.6	69/475	2430/5355	1700/3750	40/25	9.00
	12.5/80-15.3	14	142/129A8	TL	889	307	10.6	63/430	2650/5840	1850/4080	40/25	9.00
D402B	5.00-10	2	61/48A6	TT	510	135	17.0	18/124	257/565	180/395	30/20	3.50
		4	73/61A6	TT	510	135	17.0	33/225	365/805	275/565	30/20	3.50
D412	11L-15	10	118B	TL	777	279	12.5	44/300	1320/2910	-	50/30	8.00
		12	121B	TL	777	279	12.5	52/360	1450/3200	-	50/30	8.00
	11L-16	10	119B	TL	803	279	12.5	44/300	1360/3000	-	50/30	8.00
		12	122B	TL	803	279	12.5	52/360	1500/3300	-	50/30	8.00
D8301	10.00/75-15.3	10	123/111A8	TL	760	264	15.0	57/400	1550/3415	1900/2405	40/25	9.00
		12	126/114A8	TL	760	264	15.0	68/470	1700/3750	1180/2600	40/25	9.00
		14	130/118A8	TL	760	264	15.0	80/550	1900/4190	1320/2910	40/25	9.00
	11.5/80-15.3	14	139/126A8	TL	845	290	15.0	69/475	2430/5350	1700/3745	40/25	9.00
	12.00/75-18	10	135/123A8	TL	937	299	20.0	47/320	2180/4800	1550/3425	40/25	9.00
		12	139/126A8	TL	937	299	20.0	58/400	2430/5350	1700/3750	40/25	9.00
14		143/140A8	TL	937	299	20.0	72/500	2725/6000	1900/4190	40/25	9.00	
I-1	9.5L-15	10	116B	TL	767	241	7.0	52/360	1250/2760	-	50/30	7.00
	11L-15	10	118B	TL	777	279	7.0	44/300	1320/2910	-	50/30	8.00
	12.5L-15	12	127B	TL	823	318	7.0	52/360	1750/3860	-	50/30	10.00

INDUSTRIAL LIFT TRUCK



**D313(E-4)****D324(E-4)**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D313(E-4)	16.00-25	28	174B	TL	1552	432	50.0	83/570	6700/14770	50/30	11.25
		32	177B	TL	1552	432	50.0	94/650	7300/16100	50/30	11.25
D324(E-4)	18.00-25	40	214B	TL	1670	505	65.0	150/1030	21200/46720	50/30	13.00

INDUSTRIAL TRACTOR




D314(R-4)

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D314(R-4)	16.9-24	10	146A8	TL	1310	429	26.0	32/220	3000/6610	40/25	15.00
		12	149A8	TL	1310	429	26.0	38/260	3250/7160	40/25	15.00
		14	152A8	TL	1310	429	26.0	46/320	3550/7825	40/25	15.00
	17.5L-24	6	132A8	TL	1241	445	26.0	20/140	2000/4400	40/25	15.00
		12	148A8	TL	1241	445	26.0	38/260	3150/6940	40/25	15.00
	19.5L-24	12	151A8	TL	1314	495	27.4	34/230	3450/7600	40/25	17.00
	21L-24	12	155A8	TL	1378	533	27.8	32/220	3875/8540	40/25	18.00
	18.4-26	12	156A8	TL	1425	467	27.0	36/250	4000/8820	40/25	16.00
	16.9-28	12	152A8	TL	1410	429	26.9	38/260	3550/7825	40/25	15.00
		16	156A8	TL	1410	429	26.9	44/300	4000/8815	40/25	15.00
18		160A8	TL	1410	429	26.9	49/340	4500/9920	40/25	15.00	



INDUSTRIAL IMPLEMENT



**D256****D257****D289****D603****D604****D605**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D256	4.10/3.50-4	2	32A3	TL	268	102	4.5	40/280	115/250	15/10	3.25
		2	32A3	TT	268	102	4.5	40/280	115/250	15/10	3.25
		4	47A3	TL	268	102	4.5	85/590	175/390	15/10	3.25
		4	47A3	TT	268	102	4.5	85/590	175/390	15/10	3.25
	4.80/4.00-8	2	57A3	TL	423	108	5.2	35/240	230/510	15/10	2.50
		4	80A3	TL	423	108	5.2	70/480	345/765	15/10	2.50
		6	-A3	TL	423	108	5.2	105/720	440/970	15/10	2.50
D257	3.00-4	2	29A3	TT	256	84	2.8	30/205	103/227	15/10	2.25
		4	52A3	TL	256	84	2.8	50/345	200/440	15/10	2.25
		4	52A3	TT	256	84	2.8	50/345	200/440	15/10	2.25
		6	64A3	TT	256	84	2.8	70/480	280/617	15/10	2.25
D289	4.10/3.50-4	2	32A3	TL	268	102	3.3	40/280	115/250	15/10	3.25
		2	32A3	TT	268	102	3.3	40/280	115/250	15/10	3.25
		4	47A3	TL	268	102	3.3	85/590	175/390	15/10	3.25
		4	47A3	TT	268	102	3.3	85/590	175/390	15/10	3.25
	4.80/4.00-8	2	57A3	TL	423	108	4.1	35/240	230/510	15/10	2.50
		4	71A3	TL	423	108	4.1	70/480	345/765	15/10	2.50
D603	2.50-4	2	14A3	TL	216	61	2.8	30/205	67/147	15/10	1.50
		2	14A3	TT	216	61	2.8	30/205	67/147	15/10	1.50
		4	28A3	TL	216	61	2.8	50/345	100/220	15/10	1.50
		4	28A3	TT	216	61	2.8	50/345	100/220	15/10	1.50
	3.00-4	2	29A3	TL	256	84	3.3	30/205	103/227	15/10	2.25
		2	29A3	TT	256	84	3.3	30/205	103/227	15/10	2.25
		4	52A3	TL	256	84	3.3	50/345	200/440	15/10	2.25
		4	52A3	TT	256	84	3.3	50/345	200/440	15/10	2.25
D604	4.10/3.50-5	2	-A3	TT	294	102	4.9	40/280	130/285	15/10	3.25
		4	52A3	TT	294	102	4.9	85/590	200/445	15/10	3.25
D605	4.10/3.50-6	2	41A3	TT	319	102	1.6	40/280	145/320	15/10	3.25
		4	-A3	TT	319	102	1.6	85/590	225/495	15/10	3.25

FORKLIFT





D301

D333

PATTERN NAME	SIZE	PLY RATING	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD kgs/lbs		MAX. SPEED	RIM
				OD(mm)	SW(mm)	(mm)	PSI/kPa	LOAD WHEEL	STEERING WHEEL	KPH/MPH	Inch
D301	4.00-8	8	TT	414	115	13.9	130/896	-	670/1477	25/15	3.25
	5.00-8	8	TT	469	131	12.7	115/790	-	830/1830	25/15	3.00
	18x7-8	16	TT	465	168	13.4	145/1000	-	1640/3615	25/15	4.33
	21x8-6	14	TT	533	203	18.4	145/1000	2115/4660	1785/3940	25/15	6.00
	6.90/6.00-9	10	TT	545	160	14.2	125/860	1515/3340	1280/2820	25/15	4.00
	6.50-10	10	TT	597	178	15.8	115/790	1725/3805	1455/3210	25/15	5.00
		12	TT	597	178	15.8	140/970	1935/4260	1635/3600	25/15	5.00
	7.50-10	12	TT	647	203	18.2	120/830	2310/5090	1950/4300	25/15	5.50
	7.00-12	12	TT	683	192	18.2	125/860	2445/5395	2065/4555	25/15	5.00
		14	TT	683	192	18.2	145/1000	2670/5885	2255/4970	25/15	5.00
	250-15	18	TT	735	250	19.5	150/1030	4105/9050	3470/7650	25/15	7.50
	300-15	20	TT	840	300	20.7	135/930	5940/13100	4990/11000	25/15	8.00
	7.00-15	12	TT	762	203	18.2	125/860	2835/6245	2395/5275	25/15	6.00
		14	TT	762	203	18.2	145/1000	3090/6810	2610/5750	25/15	6.00
	7.00L-15	12	TT	731	199	18.2	125/860	2805/6185	2370/5220	25/15	5.50
	7.50-15 [30"]	12	TT	762	203	18.2	125/860	2835/6245	2395/5275	25/15	6.00
		14	TT	762	203	18.2	140/970	3505/7725	2965/6535	25/15	6.00
	7.50-15 [32"]	12	TT	808	215	18.2	115/790	3140/6920	2650/5845	25/15	6.00
8.15-15	12	TT	706	221	19.8	120/830	2810/6190	2370/5230	25/15	7.00	
	14	TT	706	221	19.8	140/970	3075/6775	2595/5720	25/15	7.00	
8.25-15	12	TT	847	236	18.2	105/720	3545/7810	2990/6595	25/15	6.50	
	14	TT	847	236	18.2	120/830	3830/8445	3235/7135	25/15	6.50	
D333	5.00-8	8	TT	469	131	18.0	115/790	- / -	830/1380	25/15	3.00
	6.00-9	10	TT	454	160	18.0	125/860	1515/3340	1280/2820	25/15	4.00
	6.50-10	10	TT	597	178	18.0	115/790	1725/3805	1455/3210	25/15	5.00
	7.00-12	12	TT	683	192	18.0	125/860	2445/5395	2065/4555	25/15	5.00
		14	TT	683	192	18.0	145/1000	2670/5885	2255/4970	25/15	5.00
	28x9-15	14	TT	706	221	20.0	140/970	3075/6775	2595/5720	25/15	7.00
	300-15	20	TT	840	300	25.0	135/930	5940/13100	4990/11000	25/15	8.00



D306

D307

D308

PATTERN NAME	SIZE	PLY RATING	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD kgs/lbs		MAX. SPEED	RIM
				OD(mm)	SW(mm)	(mm)	PSI/kPa	LOAD WHEEL	STEERING WHEEL	KPH/MPH	Inch
D306	5.00-8	8	TT	469	131	12.9	115/790	-	830/1830	25/15	3.00
	5.00-8 SOLID	-	Solid	458	143	23.0	-	1415/3120	1090/2405	25/15	3.25A
	6.00-9	10	TT	545	160	15.0	125/860	1515/3340	1280/2820	25/15	4.00
	6.00-9 SOLID	-	Solid	529	173	24.0	-	1885/4155	1450/3195	25/15	4.00E
	6.50-10	12	TT	597	178	15.3	140/970	1935/4260	1635/3600	25/15	5.00
	6.50-10 SOLID	-	Solid	576	191	25.5	-	2340/5160	1800/3970	25/15	5.00F
	7.00-12	14	TT	683	192	15.5	145/1000	2670/5885	2255/4970	25/15	5.00
		16	TT	638	192	15.5	155/1050	2830/6240	2320/5110	25/15	5.00
	7.00-12 SOLID	-	Solid	657	207	26.8	-	2920/6435	2240/4940	25/15	5.00S
	7.00-15	14	TT	762	203	15.4	145/1000	3090/6810	2610/5755	25/15	6.00
	7.50-15	14	TT	808	215	16.0	140/970	3505/7725	2965/6535	25/15	6.00
	8.15-15	12	TT	706	221	15.5	120/830	2810/6190	2370/5230	25/15	7.00
		14	TT	706	221	15.5	140/970	3075/6775	2595/5720	25/15	7.00
	8.25-15	12	TT	847	236	15.5	105/720	3545/7810	2990/6595	25/15	6.50
		14	TT	847	236	15.5	120/830	3830/8445	3235/7135	25/15	6.50
28x9-15 SOLID	-	Solid	700	221	23.0	-	3445/7595	2650/5842	25/15	7.00	
250-15 SOLID	-	Solid	720	225	24.0	-	4745/10460	3650/8046	25/15	7.00	
300-15 SOLID	-	Solid	815	250	24.0	-	5850/12897	4500/9920	25/15	8.00	
D307	5.00-8 SOLID	-	Solid	458	143	17.4	-	1415/3120	1090/2405	25/15	3.25A
	6.00-9 SOLID	-	Solid	529	173	19.0	-	1885/4155	1450/3195	25/15	4.00E
	6.50-10 SOLID	-	Solid	576	191	21.4	-	2340/5160	1800/3970	25/15	5.00F
	7.00-12 SOLID	-	Solid	657	207	21.4	-	2920/6435	2240/4940	25/15	5.00S
	28x9-15 SOLID	-	Solid	693	233	23.8	-	3445/7590	2650/5840	25/15	6.50
D308	4.00-8 SOLID	-	Solid	406	130	18.7	-	950/2095	730/1610	25/15	3.00D

SKID STEER





D304

D305

D311

D316

D322

D323

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D304	27x8.50-15	6	96B	TL	678	213	13.0	45/310	710/1570	50/30	7.00
		8	101B	TL	678	213	13.0	60/415	825/1820	50/30	7.00
	27x10.50-15	6	98B	TL	691	259	13.0	45/310	750/1650	50/30	8.50
		8	103B	TL	691	259	13.0	60/415	875/1930	50/30	8.50
	10-16.5	8	-/A2	TL	773	264	12.7	60/415	1880/4140	10/5	8.25
		10	-/A2	TL	773	264	12.7	75/520	2135/4720	10/5	8.25
	12-16.5	10	-/A2	TL	831	307	16.6	65/450	2540/5600	10/5	9.75
		12	-/A2	TL	831	307	16.6	80/550	2865/6320	10/5	9.75
	14-17.5	14	-/A2	TL	921	349	18.2	80/550	3875/8540	10/5	10.50
	15-19.5	14	-/A2	TL	1019	389	18.2	70/485	4565/10060	10/5	11.75
31x15.50-15	8	116A3	TL	790	398	20.5	45/310	1250/2760	15/10	13.00	
	10	122A3	TL	790	398	20.5	61/420	1485/3270	15/10	13.00	
31.5 x 13.00-16.5	10	128A3	TL	765	330	19.0	70/480	1780/3925	15/10	9.75	
33x15.50-16.5	12	137A3	TL	838	393	21.0	70/480	2295/5060	15/10	12.00	
D305	10-16.5	6	-/A2	TL	773	264	16.6	45/310	1590/3500	10/5	8.25
		8	-/A2	TL	773	264	16.6	60/410	1880/4140	10/5	8.25
	12-16.5	8	-/A2	TL	831	307	17.0	50/340	2180/4810	10/5	9.75
		10	-/A2	TL	831	307	17.0	65/450	2540/5600	10/5	9.75
D311	10-16.5	8	-/A2	TL	773	264	15.0	60/410	1880/4140	10/5	8.25
		10	-/A2	TL	773	264	15.0	75/520	2135/4700	10/5	8.25
	12-16.5	10	-/A2	TL	831	307	16.0	65/450	2540/5600	10/5	9.75
		12	-/A2	TL	831	307	16.0	80/550	2865/6310	10/5	9.75
D316	29x11.50-15	10	122A8	TL	730	270	17.0	65/450	1500/3300	40/25	10.00
	31x15.50-15	10	121B	TL	792	391	17.0	60/410	1450/3200	50/30	13.00
D322	10-16.5	8	-/A2	TL	773	264	30.0	60/410	1880/4140	10/5	8.25
		10	-/A2	TL	773	264	30.0	75/520	2135/4710	10/5	8.25
	12-16.5	10	-/A2	TL	831	307	34.5	65/450	2540/5600	10/5	9.75
		12	-/A2	TL	831	307	34.5	80/550	2865/6320	10/5	9.75
D323	10-16.5	10	135A2	TL	773	264	35.0	60/415	2180/4806	10/5	8.25
	12-16.5	12	135	TL	831	307	35.0	65/44	2575/5677	10/5	9.75

DUMPER





D203 **D302** **D303** **D309** **D403**

PATTERN NAME	SIZE	PLY RATING	LOAD INDEX		TYPE	INFLATED DIMENSION		TREAD DEPTH (mm)	INFLATION PRESSURE (PSI/kPa)	MAX. LOAD (kgs/lbs)		MAX. SPEED (KPH/MPH)	RIM WIDTH (Inch)
			FREE ROLLING	DRIVE WHEEL		OD(mm)	SW(mm)			FREE ROLLING	DRIVE WHEEL		
D203	11.00-20	18	-	710A5	TT	1104	293	20.3	145/1000	-	6000/13225	25/15	8.00
D302	10.5/80-18	10	131	119	TT	885	274	21.5	53/370	1950/4300	1360/3000	40/25	9.00
		10	131	119	TL	885	274	21.5	53/370	1950/4300	1360/3000	40/25	9.00
	12.5/80-18	12	142	129	TT	965	308	21.5	53/370	2650/5840	1850/4080	40/25	9.00
		12	142	129	TL	965	308	21.5	53/370	2650/5840	1850/4080	40/25	9.00
		16	148	135	TL	965	308	21.5	71/490	3150/6940	2180/4805	40/25	9.00
D303	15.00/55-17 [380/55-17]	10	134	122	TL	850	391	24.9	38/260	2120/4670	1500/3305	40/25	13.00
		12	138	125	TL	850	391	24.9	40/280	2360/5200	1650/3635	40/25	13.00
	10.5/80-18EG	10	123	119	TL	885	274	22.0	53/370	1950/4300	1360/3000	40/25	9.00
		16	-	146	TL	885	274	22.0	85/585	4290/9455	3000/6610	40/25	9.00
	12.5/80-18EG	12	142	129	TT	965	308	26.8	53/370	2650/5840	1850/4080	40/25	9.00
		12	142	129	TL	965	308	26.8	53/370	2650/5840	1850/4080	40/25	9.00
	405/70-24	14	-	152	TL	1176	418	33.6	70/480	-	3550/7825	50/30	14.00
	16.00/70-20EG [405/70-20]	14	154	142	TL	1075	418	30.1	51/350	3750/8265	2650/5840	40/25	14.00
D309	10.00-20	16	-	164	TT	1075	278	15.3	130/900	-	5000/11020	25/15	7.50
D403	10.00/75-15.3	8	119	106	TT	760	264	20.1	45/310	1360/3000	950/2095	40/25	9.00
		8	119	106	TL	760	264	20.1	45/310	1360/3000	950/2095	40/25	9.00
		10	123	111	TL	760	264	20.1	57/400	1550/3415	1090/2400	40/25	9.00
	11.5/80-15.3	8	126	114	TT	845	290	22.0	39/270	1700/3745	1180/2600	40/25	9.00
		8	126	114	TL	845	290	22.0	39/270	1700/3745	1180/2600	40/25	9.00
		10	131	119	TL	845	290	22.0	49/340	1950/4300	1360/3000	40/25	9.00
	405/70-20	14	154	142	TL	1075	418	26.0	51/350	3750/8265	2650/5840	40/25	14.00

ATV



**D928****D929****D930**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D928	22x11.00-8	2	36F	TL	559	281	13.5	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	13.5	5/35	155/340	80/50	9.00
		6	48F	TL	559	281	13.5	7/45	180/395	80/50	9.00
D929	16x8.00-7	2	9F	TL	406	204	9.5	4/25	58/128	80/50	6.50
		4	16F	TL	406	204	9.5	5/35	71/157	80/50	6.50
	20x7.00-8	2	16F	TL	508	177	9.5	4/25	71/157	80/50	5.50
		4	23F	TL	508	177	9.5	5/35	87.5/195	80/50	5.50
	22x11.00-8	2	36F	TL	559	281	11.9	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	11.9	5/35	155/340	80/50	9.00
	25x12.00-9	2	44F	TL	635	304	13.5	4/25	160/355	80/50	9.50
		4	51F	TL	635	304	13.5	5/35	195/430	80/50	9.50
D930	16x6.50-8	2	5F	TL	406	166	9.6	4/25	51.5/114	80/50	5.50
		4	12F	TL	406	166	9.6	5/35	63/139	80/50	5.50
		6	17F	TL	406	166	9.6	7/45	73/161	80/50	5.50
	22x11.00-8	2	36F	TL	559	281	12.4	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	12.4	5/35	155/340	80/50	9.00
	22x11.00-9	2	36F	TL	559	281	12.4	4/25	125/275	80/50	9.00
		4	43F	TL	559	281	12.4	5/35	155/340	80/50	9.00
	25x12.00-9	2	44F	TL	635	304	13.4	4/25	160/355	80/50	9.50
		4	51F	TL	635	304	13.4	5/35	195/430	80/50	9.50
	22x11.00-10	2	35F	TL	559	281	12.4	4/25	121/265	80/50	9.00
		4	42F	TL	559	281	12.4	5/35	150/330	80/50	9.00
	24x11.00-10	2	40F	TL	610	281	13.4	4/25	140/310	80/50	9.00
		4	47F	TL	610	281	13.4	5/35	175/385	80/50	9.00
	25x12.00-10	2	44F	TL	635	304	13.4	4/25	160/355	80/50	9.50
		4	51F	TL	635	304	13.4	5/35	195/430	80/50	9.50
	23x8.00-11	2	26F	TL	584	204	12.4	4/25	95/210	80/50	6.50
		4	33F	TL	584	204	12.4	5/35	115/255	80/50	6.50
	24x9.00-11	2	33F	TL	610	227	12.4	4/25	115/255	80/50	7.00
		4	40F	TL	610	227	12.4	5/35	140/310	80/50	7.00
	24x10.00-11	2	36F	TL	610	254	12.4	4/25	125/275	80/50	8.00
4		43F	TL	610	254	12.4	5/35	155/340	80/50	8.00	
25x8.00-12	2	31F	TL	635	204	14.4	4/25	109/240	80/50	6.50	
	4	38F	TL	635	204	14.4	5/35	132/290	80/50	6.50	
25x10.00-12	2	38F	TL	635	254	14.4	4/25	132/290	80/50	8.00	
	4	45F	TL	635	254	14.4	5/35	165/365	80/50	8.00	



D932

D933

D936

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D932	22x11.00-9	6	48F	TL	559	281	21.1	7/45	180/395	80/50	9.00
	25x12.00-9	6	56F	TL	635	304	21.1	7/45	224/495	80/50	9.50
	22x11.00-10	6	47F	TL	559	281	21.1	7/45	175/385	80/50	9.00
	24x11.00-10	6	52F	TL	610	281	21.1	7/45	200/440	80/50	9.00
	25x12.00-10	6	56F	TL	635	304	21.1	7/45	224/495	80/50	9.50
	25x8-12	6	43F	TL	635	204	21.1	7/45	155/340	80/50	6.50
	25x10-12	6	50F	TL	635	254	21.1	7/45	190/420	80/50	8.00
	26x10.00-12	6	52F	TL	660	254	24.9	7/45	200/460	80/50	8.00
	26x12.00-12	6	58F	TL	660	304	24.9	7/45	236/520	80/50	9.50
	27x10.00-12	6	56F	TL	686	254	24.9	7/45	224/495	80/50	8.00
	27x12.00-12	6	60F	TL	686	304	24.9	7/45	250/550	80/50	9.50
	28x10.00-12	6	57F	TL	711	254	24.9	7/45	230/505	80/50	8.00
	28x12.00-12	6	61F	TL	711	304	24.9	7/45	257/565	80/50	9.50
	AT27x10-14	6	53F	TL	686	254	21.0	7/45	206/455	80/50	8.00
AT30x9-14	6	57F	TL	762	227	21.0	7/45	230/505	80/50	7.00	
D933	23x8-11	4	33F	TL	584	204	14.4	5/35	115/255	80/50	6.50
		6	38F	TL	584	204	14.4	7/45	132/290	80/50	6.50
	24x9-11	4	40F	TL	610	227	15.3	5/35	140/310	80/50	7.00
		6	45F	TL	610	227	15.3	7/45	165/365	80/50	7.00
	25x8-12	4	38F	TL	635	204	15.3	5/35	132/290	80/50	6.50
		6	43F	TL	635	204	15.3	7/45	155/340	80/50	6.50
25x10-12	4	45F	TL	635	254	15.3	5/35	165/365	80/50	8.00	
	6	50F	TL	635	254	15.3	7/45	190/420	80/50	8.00	
D936	22x11.00-8	6	48F	TL	559	281	15.3	7/45	180/395	80/50	9.00
	22x11.00-9	6	48F	TL	559	281	15.3	7/45	180/395	80/50	9.00
	25x12.00-9	6	56F	TL	635	304	15.3	7/45	224/495	80/50	9.50
	22x8.00-10	6	36F	TL	559	204	15.3	7/45	125/275	80/50	6.50
	22x11.00-10	6	47F	TL	559	281	15.3	7/45	175/385	80/50	9.00
	23x8.00-10	6	39F	TL	584	204	14.4	7/45	136/300	80/50	6.50
	23x10.00-10	6	46F	TL	584	254	14.4	7/45	170/375	80/50	8.00
	24x11.00-10	6	52F	TL	610	281	15.3	7/45	200/440	80/50	9.00
	25x12.00-10	6	56F	TL	635	304	15.3	7/45	224/495	80/50	9.50
	27x12.00-10	6	60F	TL	686	304	28.8	7/45	250/550	80/50	9.50
	23x8.00-11	6	38F	TL	584	204	15.3	7/45	132/290	80/50	6.50
	24x8.00-11	6	41F	TL	610	204	14.4	7/45	145/320	80/50	6.50
	24x9.00-11	6	45F	TL	610	227	15.3	7/45	165/265	80/50	7.00
	24x10.00-11	6	48F	TL	610	254	14.4	7/45	180/395	80/50	8.00
	25x8.00-11	6	44F	TL	635	204	15.3	7/45	160/355	80/50	6.50
	25x10.00-11	6	51F	TL	635	254	15.3	7/45	195/430	80/50	8.00
	25x8.00-12	6	43F	TL	635	204	15.3	7/45	155/340	80/50	6.50
	25x10.00-12	6	50F	TL	635	254	15.3	7/45	190/420	80/50	8.00
	26x10.00-12	6	52F	TL	660	254	28.8	7/45	200/460	80/50	8.00
	26x12.00-12	6	58F	TL	660	304	28.8	7/45	236/520	80/50	9.50
	27x10.00-12	6	54F	TL	686	254	28.8	7/45	212/467	80/50	8.00
	27x12.00-12	6	60F	TL	686	304	28.8	7/45	250/550	80/50	9.50
28x10.00-12	6	56F	TL	711	254	28.8	7/45	224/495	80/50	8.00	
28x12.00-12	6	63F	TL	711	304	28.8	7/45	272/599	80/50	8.00	

**D942****D943****D944****D985**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D942	AT26x10.00R12	8	52F	T/L	660	254	19.1	7/48	200/440	80/50	8.00
	AT26x12.00R12	8	58F	T/L	660	304	19.1	7/48	236/520	80/50	9.50
	AT27x9.00R12	8	52F	T/L	686	227	19.1	7/48	200/440	80/50	7.00
	AT25x8.00R12	8	43F	T/L	635	204	19.1	7/48	190/440	80/50	6.50
	AT25x10.00R12	8	50F	T/L	635	254	19.1	7/48	200/440	80/50	8.00
	AT26x9.00R12	8	49F	T/L	660	227	19.1	7/48	185/410	80/50	7.00
	AT27x10.00R12	8	55F	T/L	686	236	19.5	7/48	220/485	80/50	7.00
	AT27x12.00R12	8	60F	T/L	686	304	19.1	7/48	250/550	80/50	9.50
	AT28x9.00R12	8	79F	T/L	711	226	19.1	7/48	433/955	80/50	7.00
	AT28x10.00R12	8	84F	T/L	711	264	19.1	7/48	495/1090	80/50	8.00
	AT26x9.00R14	8	48F	T/L	660	227	19.1	7/48	185/410	80/50	7.00
	AT26x11.00R14	8	54F	T/L	660	281	19.1	7/48	212/465	80/50	9.00
D943	AT22.5x10.00-8	6	45F	T/L	572	254	12.7	7/50	165/365	80/50	8.00
	AT22x12.00-8	6	51F	T/L	528	269	12.7	7/50	195/430	80/50	7.00
	AT25x13.00-9	6	59F	T/L	620	320	12.7	7/50	243/535	80/50	10.00
	AT20x10.00-10	4	68F	T/L	511	259	12.7	22/150	315/695	80/50	8.00
	AT22x9.50-10	4	71F	T/L	564	241	12.7	22/150	345/760	80/50	8.00
	AT22x11.00-10	4	77F	T/L	564	272	12.7	22/150	412/910	80/50	8.00
	AT23x11.00-10	4	79F	T/L	582	27	12.7	22/150	437/965	80/50	8.00
	AT24x9.50-10	4	76F	T/L	612	241	12.7	22/150	400/880	80/50	8.00
	AT24x10.50-10	4	81F	T/L	615	262	12.7	24/165	462/1020	80/50	8.00
	AT18x8.50-12	4	56F	T/L	457	198	12.7	22/150	224/495	80/50	7.00
	AT23x8.00-12	4	69F	T/L	584	198	12.7	24/165	325/715	80/50	6.00
	AT23x10.50-12	4	73F	T/L	579	264	12.7	20/140	365/800	80/50	8.50
	AT24x12.0012	4	81F	T/L	610	304	12.7	20/140	462/1020	80/50	9.50
	AT25x8.00-12	4	74F	T/L	635	203	12.7	24/165	375/8250	80/50	6.50
	AT25x9.00-12	4	74F	T/L	635	227	12.7	20/140	375/825	80/50	7.00
AT25x10.5-12	4	82F	T/L	635	264	12.7	24/165	475/1050	80/50	8.50	
D944	26x8.00-14	6	44F	T/L	660	204	20.0	7/45	160/355	80/50	6.50
	26x10.00-14	6	51F	T/L	660	254	20.0	7/45	195/430	80/50	8.00
	27x10.00-14	6	70J	T/L	686	254	20.0	12/40	335/740	100/60	8.00
	27x12.00-14	6	70J	T/L	686	305	20.0	12/40	335/740	100/60	9.50
D985	22.5x12.00-9	6	52F	T/L	572	304	24.3	7/45	200/240	80/50	9.50
	25x9.00-12	6	47F	T/L	635	227	24.3	7/45	175/385	80/50	7.00
	25x11.00-12	6	53F	T/L	635	281	24.3	7/45	206/455	80/50	9.00
	26x9.50-12	6	50F	T/L	660	241	24.3	7/45	190/420	80/50	8.00
	26x12.00-12	6	58F	T/L	660	304	24.3	7/45	236/520	80/50	9.50
	27x9.50-12	6	53F	T/L	686	241	24.3	7/45	206/455	80/50	8.00
	27x12.00-12	6	60F	T/L	686	304	24.3	7/45	250/550	80/50	9.50
	28x9.50-12	6	55F	T/L	711	241	24.3	7/45	218/480	80/50	8.00
28x12.00-12	6	63F	T/L	711	304	24.3	7/45	272/599	80/50	9.50	

GOLF CART



**D258****D270****D271**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH (mm)	INFLATION PRESSURE (PSI/kPa)	MAX. LOAD (KGS/LBS)	MAX. SPEED (KPH/MPH)	RIM WIDTH (Inch)
					OD(mm)	SW(mm)					
D258	205/50-10	4	67A3	TL	459	205	8.6	30/210	307/675	15/10	6.50
D270	18x8.50-8	4	74A3	TL	450	213	6.2	22/150	375/825	15/10	7.00
D271	19x8.00-10	4	-/A3	TL	487	198	5.5	22/150	585/1290	15/10	6.00
	165/60-12	6	-/A3	TL	515	172	5.5	45/310	510/1125	15/10	6.00
	190/50-12	4	-/A3	TL	498	181	5.5	26/180	395/870	15/10	6.00

GO KART



**D190****D191**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D190	11x7.10-5	4	26/S	TL	271	210	4.0	14/96	95/210	180/112	8.00
D191	10x4.50-5	4	-/S	TL	252	129	3.0	14/96	59/130	180/112	4.50
	11x6.00-5	4	-/S	TL	271	172	3.0	14/96	84/185	180/112	8.00



WHEEL BARROW



D601

D602

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D601	4.00-6	2	-/A5	TT	345	101	3.1	30/205	177/390	25/15	2.38
		4	-/A5	TT	345	101	3.1	50/345	304/670	25/15	2.38
		2	-/A5	TL	345	101	3.1	30/205	177/390	25/15	2.38
		4	-/A5	TL	345	101	3.1	50/345	304/670	25/15	2.38
	3.50-8	2	41/A5	TT	373	86	2.4	30/205	177/390	25/15	2.50
		4	51/A5	TT	373	86	2.4	50/345	304/670	25/15	2.50
		2	41/A5	TL	373	86	2.4	30/205	177/390	25/15	2.50
		4	51/A5	TL	373	86	2.4	50/345	304/670	25/15	2.50
	4.80/4.00-8	2	-/A5	TT	406	101	2.4	30/205	304/670	25/15	2.50
		4	-/A5	TT	406	101	2.4	50/345	304/670	25/15	2.50
		2	-/A5	TL	406	101	2.4	30/205	177/390	25/15	2.50
		4	-/A5	TL	406	101	2.4	50/345	304/670	25/15	2.50
D602	4.00-6	2	-/A5	TT	345	101	2.0	30/205	177/390	25/15	2.38
		4	-/A5	TT	345	101	2.0	50/345	304/670	25/15	2.38
		2	-/A5	TL	345	101	2.0	30/205	177/390	25/15	2.38
		4	-/A5	TL	345	101	2.0	50/345	304/670	25/15	2.38
	3.50-8	2	41/A5	TT	373	86	1.8	30/205	145/320	25/15	2.50
		4	51/A5	TT	373	86	1.8	50/345	195/430	25/15	2.50
		2	41/A5	TL	373	86	1.8	30/205	145/320	25/15	2.50
		4	51/A5	TL	373	86	1.8	50/345	195/430	25/15	2.50
	4.80/4.00-8	2	-/A5	TT	406	101	2.5	30/205	197/435	25/15	2.50
		4	-/A5	TT	406	101	2.5	50/345	304/670	25/15	2.50
		2	-/A5	TL	406	101	2.5	30/205	197/435	25/15	2.50
		4	-/A5	TL	406	101	2.5	50/345	304/670	25/15	2.50

LAWN AND GARDEN





D265

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D265	4.00-4	2	29A3	TT	265	100	3.9	24/170	103/225	15/10	3.50
		4	43A3	TT	265	100	3.9	48/330	155/340	15/10	3.50
		6	51A3	TT	265	100	3.9	60/410	195/430	15/10	3.50
	4.10/3.50-4	2	29A3	TL	268	102	3.5	24/170	103/225	15/10	3.25
		4	43A3	TL	268	102	3.5	48/330	155/340	15/10	3.25
		2	29A3	TT	268	102	3.5	24/170	103/225	15/10	3.25
		4	43A3	TT	268	102	3.5	48/330	155/340	15/10	3.25
	11x4.00-5	2	29A3	TL	279	102	2.2	24/170	103/225	15/10	3.25
		4	43A3	TL	279	102	2.2	48/330	155/340	15/10	3.25
		2	26A3	TL	272	104	2.5	22/150	95/210	15/10	3.00
		4	42A3	TL	272	104	2.5	46/320	150/330	15/10	3.00
	13x5.00-6	2	38A3	TL	320	122	2.8	20/140	132/290	15/10	3.50
		4	52A3	TL	320	122	2.8	40/280	200/440	15/10	3.50
	13x6.50-6	2	41A3	TL	330	163	3.0	14/100	145/320	15/10	5.00
		4	55A3	TL	330	163	3.0	18/190	218/480	15/10	5.00
	15x6.00-6	2	45A3	TL	366	155	3.2	14/100	165/365	15/10	4.50
		4	61A3	TL	366	155	3.2	30/210	257/565	15/10	4.50
	4.80/4.00-8	4	66A3	TT	423	121	5.0	40/280	300/660	15/10	3.75
		6	78A3	TT	423	121	5.0	52/360	425/935	15/10	3.75
		2	52A3	TL	423	121	5.0	20/140	200/435	15/10	3.75
		4	66A3	TL	423	121	5.0	40/280	300/660	15/10	3.75
		6	78A3	TL	423	121	5.0	52/360	425/935	15/10	3.75
	16x6.50-8	4	64A3	TL	406	165	5.0	28/190	280/615	15/10	5.375
	16x7.50-8	2	55A3	TL	411	188	3.8	12/80	218/480	15/10	5.375
		4	69A3	TL	411	188	3.8	24/170	325/715	15/10	5.375
		8	83A3	TL	411	188	3.8	42/290	487/1070	15/10	5.375
	18x6.50-8	2	58A3	TL	457	163	4.8	14/100	236/520	15/10	5.00
		4	71A3	TL	457	163	4.8	28/190	345/760	15/10	5.00
	18x8.50-8	2	58A3	TL	450	213	5.7	10/70	236/520	15/10	7.00
		4	74A3	TL	450	213	5.7	22/150	375/825	15/10	7.00
		6	82A3	TL	450	213	5.7	34/230	475/1050	15/10	7.00
	18x9.50-8	2	64A3	TL	462	235	5.7	10/70	280/615	15/10	7.00
		4	78A3	TL	462	235	5.7	20/140	425/935	15/10	7.00
	20x8-8	2	63A3	TL	508	204	4.5	10/70	272/600	15/10	6.50
		4	79A3	TL	508	204	4.5	22/150	437/965	15/10	6.50
	20x10.00-8	2	71A3	TL	508	254	6.2	10/70	345/760	15/10	8.00
		4	87A3	TL	508	254	6.2	22/150	545/1200	15/10	8.00
	20x10-10	2	70A3	TL	508	254	5.3	10/70	335/740	15/10	8.00
		4	86A3	TL	508	254	5.3	22/150	530/1170	15/10	8.00
	23x8.50-12	2	69A3	TL	574	213	5.2	10/70	325/715	15/10	7.00
4		84A3	TL	574	213	5.2	22/150	500/1100	15/10	7.00	
6		93A3	TL	574	213	5.2	34/230	650/1430	15/10	7.00	
23x9.50-12	2	74A3	TL	577	235	5.5	10/70	375/825	15/10	7.00	
	4	88A3	TL	577	235	5.5	22/150	560/1230	15/10	7.00	
23x10.50-12	2	76A3	TL	579	264	6.0	10/70	400/880	15/10	8.50	
	4	90A4	TL	579	264	6.0	20/140	600/1320	15/10	8.50	
	6	100A3	TL	579	264	6.0	32/220	800/1760	15/10	8.50	
24x12.00-12	4	99A3	TL	610	304	6.2	20/140	775/1710	15/10	9.50	
26x12.00-12	2	87A3	TL	648	307	6.7	10/70	545/1200	15/10	10.50	
	4	100A4	TL	648	307	6.7	20/140	800/1760	20/15	10.50	
	6	109A3	TL	648	307	6.7	30/210	1030/2270	15/10	10.50	
	8	117A4	TL	648	307	6.7	38/360	1250/2275	20/15	10.50	

**D265T****D266****D267**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D265T	16x6.50-8	2	49A3	TL	406	165	2.8	14/100	185/410	15/10	5.375
D266	11x4.00-5	2	26A3	TL	272	104	2.5	22/150	95/210	15/10	3.00
		4	42A3	TL	272	104	2.5	46/320	150/330	15/10	3.00
	15x6.00-6	4	61A3	TL	366	155	3.2	30/210	257/565	15/10	4.50
	16x6.50-8	4	64A3	TL	406	165	3.7	28/190	280/620	15/10	5.375
		6	71A3	TL	406	165	3.7	46/330	375/825	15/10	5.375
	18x7.50-8	4	73A3	TL	457	191	4.8	24/170	365/805	15/10	6.00
	18x8.50-8	2	58A3	TL	450	213	4.3	10/70	236/520	15/10	7.00
		4	74A3	TL	450	213	4.3	22/150	375/825	15/10	7.00
	18x9.50-8	4	78A3	TL	462	235	6.2	20/140	425/935	15/10	7.00
	20x10.00-8	4	87A3	TL	508	254	6.2	22/150	545/1200	15/10	8.00
	20x10.00-10	4	86A3	TL	508	254	6.2	22/150	530/1170	15/10	8.00
		6	89A3	TL	508	254	6.2	34/230	580/1280	15/10	8.00
	23x10.50-12	4	90A4	TL	579	264	5.0	20/140	600/1320	20/15	8.50
6		100A4	TL	579	264	5.0	32/220	800/1760	20/15	8.50	
D267	22x11.00-8	4	94A3	TL	559	276	5.7	22/150	670/1480	15/10	8.50

**D837****D838**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D837	11x4.00-4	2	29A3	TL	279	102	2.2	24/170	103/225	15/10	3.25
		4	43A3	TL	279	102	2.2	48/330	155/340	15/10	3.25
	11x4.00-5	2	26A3	TL	272	104	2.5	22/150	95/210	15/10	3.00
		4	42A3	TL	272	104	2.5	46/320	150/330	15/10	3.00
	13x5.00-6	2	38A3	TL	320	122	2.8	20/140	132/290	15/10	3.50
		4	52A3	TL	320	122	2.8	40/280	200/440	15/10	3.50
	13x6.50-6	2	41A3	TL	330	163	3.0	14/100	145/320	15/10	5.00
		4	55A3	TL	330	163	3.0	28/190	218/460	15/10	5.00
	15x6.00-6	2	45A3	TL	366	155	3.2	14/100	165/365	15/10	4.50
		4	61A3	TL	366	155	3.2	30/210	257/565	15/10	4.50
		6	72A3	TL	366	155	3.2	46/320	355/782	15/10	4.50
	16x6.50-8	2	49A3	TL	406	165	3.7	14/100	185/410	15/10	5.375
		4	64A3	TL	406	165	3.7	28/190	280/620	15/10	5.375
		6	71A3	TL	406	165	3.7	46/330	345/760	15/10	5.375
		10	73A3	TL	406	165	3.7	36/250	365/800	15/10	5.375
18x8.50-8	2	58A3	TL	450	213	4.3	10/70	236/520	15/10	7.00	
	4	74A3	TL	450	213	4.3	22/150	375/825	15/10	7.00	
	6	82A3	TL	450	213	4.3	34/230	475/1050	15/10	7.00	
D838	16x6.50-8	4	64A3	TL	406	165	7.2	28/190	280/615	15/10	5.375
	18x8.50-8	4	74A3	TL	450	213	7.2	22/150	375/825	15/10	7.00
	23x9.50-12	6	96A3	TL	577	235	8.2	30/210	710/1565	15/10	7.00
	23x10.50-12	6	100A4	TL	579	264	8.2	32/220	800/1765	15/10	8.50
	24x12.00-12	6	109A3	TL	610	304	8.2	32/220	1030/2270	15/10	9.50

EARTH MOVING



**D313(E-3)****D319(E-3)****D320(E-7)**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D313(E-3)	14.00-24	24	165B	TL	1368	375	25.0	83/575	5150/11350	50/30	10.00
		28	168B	TL	1368	375	25.0	94/650	5600/12340	50/30	10.00
		28	168B	TT	1368	375	25.0	94/650	5600/12340	50/30	10.00
	15.5-25	12	149B	TL	1278	394	25.3	36/250	3250/7150	50/30	12.00
		16	154B	TL	1278	394	25.3	47/325	3750/8250	50/30	12.00
	17.5-25	12	153B	TL	1348	445	29.1	33/225	3650/8050	50/30	14.00
		16	158B	TL	1348	445	29.0	44/300	4250/9350	50/30	14.00
		20	164B	TL	1348	445	29.0	58/400	5000/11000	50/30	14.00
	20.5-25	20	170B	TL	1493	521	32.0	47/325	6000/13200	50/30	17.00
		24	174B	TL	1493	521	32.0	58/400	6700/14770	50/30	17.00
	23.5-25	16	125B	TL	1617	597	41.3	33/225	6150/13600	50/30	19.50
		20	177B	TL	1617	597	41.3	44/300	7300/16100	50/30	19.50
		24	180B	TL	1617	597	41.3	51/350	8000/17600	50/30	19.50
26.5-25	28	188B	TL	1750	673	38.4	51/350	10000/22000	50/30	22.00	
29.5-25	28	193B	TL	1874	749	35.4	47/325	11500/25400	50/30	25.00	
D319(E-3)	23.5-25	20	177B	TL	1617	597	36.1	44/300	7300/16100	50/30	19.50
		24	180B	TL	1617	597	36.1	51/350	8000/17600	50/30	19.50
D320(E-3)	20.5-25	20	170B	TL	1493	521	15.8	47/325	6000/13200	50/30	17.00
	23.1-26	12	153A6	TL	1560	590	27.5	25/175	3650/8050	50/30	20.00
		16	159A6	TL	1560	590	27.5	33/230	4375/9650	50/30	20.00

LOADER AND DOZER





D318(L-2)

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D318(L-2)	15.5-25	12	168A2	TL	1278	394	24.3	58/400	5600/12300	10/5	12.00
	17.5-25	12	171A2	TL	1348	445	27.7	51/350	6150/13600	10/5	14.00
		16	177A2	TL	1348	445	27.7	69/475	7300/16100	10/5	14.00
	20.5-25	16	181A2	TL	1493	521	32.1	51/350	8250/18200	10/5	17.00
		20	186A2	TL	1493	521	32.1	65/450	9500/20900	10/5	17.00



GRADER



COMPACTOR


D310(G-2)

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D310(G-2)	13.00-24	12	143A8	TT	1278	333	24.0	44/300	2725/6000	40/25	8.00 TG
		12	143A8	TL	1278	333	24.0	44/300	2725/6000	40/25	8.00 TG
		14	147A8	TL	1278	333	24.0	51/350	3075/6775	40/25	8.00 TG
	14.00-24	12	147A8	TT	1348	362	27.0	36/250	3075/6800	40/25	8.00 TG
		12	147A8	TL	1348	362	27.0	36/250	3075/6800	40/25	8.00 TG
		14	151A8	TL	1348	362	27.0	44/300	3450/7600	40/25	8.00 TG
		16	153A8	TT	1348	362	27.0	51/350	3650/8050	40/25	8.00 TG
		16	153A8	TL	1348	362	27.0	51/350	3650/8050	40/25	8.00 TG

**DC-1****DC327**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
DC-1	9.00-20	14	159A2	TT	1016	259	-	105/725	4375/9650	10/5	7.00
	11.00-20	16	167A2	TT	1083	293	-	105/725	5450/12000	10/5	8.00
DC327	9.00-20	14	159A2	TT	1016	259	16.0	105/725	4375/9650	10/5	7.00
	14.00/70-20	14	158A2	TT	990	358	16.0	73/500	4250/9365	10/5	11.00



DEESTONE LIMITED

84 Soi Sinprasong, Moo 7, Petchkasem Road,
Oamnoi, Krathumban, Samutsakhon 74130 Thailand
Tel : (+662)420 0038, 023 4756 Fax : (+662)420 5680

Email : global-business@deestone.com

Website : www.deestone.com