

PRODUCT DATASHEET

OMEGA UNICRYL Interior Putty 6002

General Description

A high quality, water-based putty for interior substrates designed to smooth surfaces for painting, fills wall imperfections, cracks and faults on the surface. Forms an excellent bonding to the base concrete or plastered surface with very good adhesion and sanding properties, creating a smooth ripple free surface for a beautiful paint finish.

Recommended Use

For priming and filling interior walls of plaster, drywall, masonry, and wood in commercial, institutional and residential properties. Use under latex or alkyd finishes.

Two coats may be required in severe cases; allow the putty to dry thoroughly for best results.

Features

- ✓ Elongates the life of the top coat paint when applied on to walls before painting
- ✓ Reduces deterioration of walls by making it water, flake, and abrasion resistant
- ✓ Can be used as primer for latex, alkyd based systems
- ✓ Apply with spatula, filing knife, or steel trowel

Limitations

Not for use on external substrates/surfaces, and in areas that are continually wet like showers. Moisture content must be below 12% and well ventilated.

Technical Data

Color	White
Finish	Flat
Vehicle Type	Water-based Putty
Pigment Type	Titanium Dioxide
Volatile Organic Compounds (VOC)	65 gm/Ltrs
Solids Contents	43% +/- 2% by volume
Dry Film Thickness (DFT)	Dry: 100 µm (indicative) Wet: 230 µm
Dry Time	To touch: 1 hour To recoat: 2 hours (putty on putty), 4 hours (30 °C) High humidity and cool temperatures will result in longer dry, recoat and service time
Dries by	Evaporation
Theoretical Spreading Rate (TSR) at Dry Film Thickness	7m ² per liter (depending on the nature and condition of the substrate)
Viscosity	-
Flash Point	None
Specific Gravity	1.55 – 1.75 gm/cm ³
Surface Temperature at Application	Maximum humidity during application and curing is 85% and dew point above 3 °C
Thin With	Sweet Water, 5-15%
Clean Up Thinner	Sweet Water
Available Package Size	25 KG
Shelf Life	12 months, sealed and kept at normal temperature (not in direct sunlight)

PRODUCT DATASHEET

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure for 30 days before applying base coat. Cured plaster should be hard, have a slight sheen; soft, porous or powdery plaster indicate improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound.

Caution: Moisture content must be below 12% and well ventilated. Product should not be applied on surfaces / substrates that are subject to continuous seepage or dampness or during rain.

Difficult substrates: Works well on internal substrates as a primer/filler. For difficult substrates where a specialty primer might be needed, our family of products offers a variety of specialty primers. Consult your Omega representative for further guidance.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear an approved respirator to control lead exposure. Carefully clean up with a vacuum and a wet mop.

Application Method

Stir thoroughly before and during use. Apply one or two coats by spatula, filing knife, or steel trowel. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains.

System Specification

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. This product is used best for Internal Water-based Emulsion Systems: plaster, masonry, drywall, and wood.

Storage and Handling

The product must be stored in accordance with national regulations and should be kept in a cool and well ventilated place. Protect from heat and direct sun light, handle with care and stir well before use.

Health and Safety

Apply under well-ventilated conditions. Do not breathe or inhale mist. When applying, wear air-mask and avoid skin contact. Spillage on skin should be immediately removed with suitable cleanser, soap, or water. Eyes should be well flushed with water and medical attention to be sought immediately.

Disclaimer

The information is given in good faith. We warrant our product is of good quality and manufactured in accordance to rigid standards. Failure of this product due to misuse or bad storage is beyond the manufacturer warranty. The company pursues a policy of continuous improvement in product innovation, and as such, reserves the right to change the given data without prior notice. Contact Omega's representative or visit www.omegapaints.net for more info.

Revision date: September 2020. This datasheet supersedes the previous issue.

unitco

Manufactured and Distributed by Unitco Group of Companies, Established in 1981, CR No. 1493
PO Box 1018 Manama, Kingdom of Bahrain, Tel: 1773 0015, Fax: 1773 2288, Web: unitcogroup.com

