

PRODUCT DATASHEET

OMEGA Rust Converter 9990

General Description

A specially formulated water-based product on proprietary technology including sustainable raw material. This product gives long lasting results of rust conversion to rusted surfaces. It can be seen by color change from red/brown color of the rust to black color.

Recommended Use

An effective rust converter for any rusted surface. Can be coated on rusted pipe or as a primer for a rusted steel surface. Top coat can be applied on rust converted surface.

For best results, two coats is preferred.

Features

- ✓ Water-based product
- ✓ Easy handling
- ✓ No foaming
- ✓ Long-shelf life
- ✓ Available in 5 USG, and 200 Ltrs

Application Method & Drying

Apply using airless spray, brush or roller. No dilution is necessary. This product will take approximately 30-45 minutes for drying. The best result can be seen overnight.

The conversion of rust will last for a long time.

Specification

Physical Appearance	Light to dark brown color
Chemical Composition	Proprietary
Solid Content (%)	15% +/- 1%
Specific Gravity	1.02 – 1.08 gm/cm ³
Viscosity (30°C)	Max. 100
pH	1-4

Storage and Handling

Omega Rust Converter must be stored in a polyline, plastic, or SS container under shade and should be protected from direct sunlight. Equipment's used in handling this product can be easily washed with water before it dries up. When comes in contact with skin or eye, wash with plenty of clean water and if any abnormal symptoms persists, seek immediate medical help.

This product is water-based and is non-inflammable

Health and Safety

Apply under well-ventilated conditions. Do not breathe or inhale mist. When applying, wear air-mask and avoid skin contact. Spillage on skin should be immediately removed with suitable cleanser, soap, or water. Eyes should be well flushed with water and medical attention to be sought immediately.

Disclaimer

The information is given in good faith. We warrant our product is of good quality and manufactured in accordance to rigid standards. Failure of this product due to misuse or bad storage is beyond the manufacturer warranty. The company pursues a policy of continuous improvement in product innovation, and as such, reserves the right to change the given data without prior notice. Contact Omega's representative or visit www.omegapaints.net for more info.

Revision date: February 2021. This datasheet supersedes the previous issue.

unitco

Manufactured and Distributed by Unitco Group of Companies, Established in 1981, CR No. 1493
PO Box 1018 Manama, Kingdom of Bahrain, Tel: 1773 0015, Fax: 1773 2288, Web: unitcogroup.com

