



Omega Unicryl Emulsion

Area: Internal Walls and Ceilings

Substrate: Cement Plaster, Concrete, Block Work, Gypsum Board, etc.

Surface Preparation

1. Ensure that the plastered surface is cured at least 21-30 days;
2. Remove all loose particles, sharp edges, nibs, etc., by abrading the surface with sand paper, scrapper, rubbing stone, etc.;
3. Ensure that surfaces to be painted must be clean, dry, and free of dirt, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew;
4. Make sure the moisture content is below 12% and well-ventilated before painting

Recommended Paint System - Matt Finish

Coat Stage	Product Code	Product Name	VOC (g/L)	DFT (µm)	No. Of Coats	Drying Time / Over coating Interval*	Application Tool
Primer	2010	Omega Unicryl Primer (Wb)	25	30	1	1 h	Roller, Brush, Spray
Prep	6004	Omega Powder Filler	0	-	1	1 h	Stainless Steel Trowel
Prep	6000	Omega Unicryl Putty	5	100	1	2 h	Stainless Steel Trowel, Filling Knife, Spatula
Top Coat	4050	Omega Unicryl Matt Emulsion	20	30	2	2 h	Roller, Brush, Spray

Refer to Omega Paints Technical Data Sheets for more information

**High humidity and cooler temperatures will result in longer dry, re-coat and service time.*

Recommended Paint System - Silk Finish

Coat Stage	Product Code	Product Name	VOC (g/L)	DFT (µm)	No. Of Coats	Drying Time / Over coating Interval*	Application Tool
Primer	2010	Omega Unicryl Primer (Wb)	25	30	1	1 h	Roller, Brush, Spray
Prep	6004	Omega Powder Filler	0	-	1	1 h	Stainless Steel Trowel
Prep	6000	Omega Unicryl Putty	5	100	1	2 h	Stainless Steel Trowel, Filling Knife, Spatula
Primer	2010	Omega Unicryl Primer (Wb)	25	30	1	1 h	Roller, Brush, Spray
Top Coat	4005	Omega Unicryl Silk Emulsion	20	40	2	2 h	Roller, Brush, Spray

*High humidity and cooler temperatures will result in longer dry, re-coat and service time.

Recommended Paint System - Wet Areas

Coat Stage	Product Code	Product Name	VOC (g/L)	DFT (µm)	No. Of Coats	Drying Time / Over coating Interval*	Application Tool
Prep	6004	Omega Powder Filler	0	-	1	1 h	Stainless Steel Trowel
Primer	2110	Omega Undercoat	366	55	1	6 h	Roller, Brush, Spray
Top Coat		Omega Unicryl Emulsion	0-20	30 - 55	2	2 h	Roller, Brush, Spray

Refer to Omega Paints Technical Data Sheets for more information

*High humidity and cooler temperatures will result in longer dry, re-coat and service time.