



# TECHNICAL DATA SHEET

## TREMSTOP® ACRYLIC SP

Sprayable, Acrylic Latex  
Firestop Sealant

---

### PRODUCT DESCRIPTION

TREMstop® Acrylic SP is a sprayable, acrylic latex sealant designed for use in firestopping applications, including both joints and through-penetrations.

---

### BASIC USES

TREMstop Acrylic SP is for use on metal pipe (Canada only), static joints, and dynamic joints in fire-rated concrete, wood, floor/ceiling, gypsum wall assemblies and perimeter fire barrier joints. It can also be used to restore the STC of sound rated assemblies.

---

### FEATURES & BENEFITS

TREMstop Acrylic SP is an easy to apply, all-purpose sealant that accepts paint once fully cured. The spray application method provides significant labor savings over a gun-grade sealant, particularly on long joint runs.

TREMstop Acrylic SP features excellent movement and superb unprimed adhesion to a wide range of substrates. When installed in accordance with a tested firestop system, TREMstop Acrylic SP affords code compliance for both through-penetrations and fire-rated joints. It also provides a fast and easy solution for restoring the STC rating of a sound-rated assembly.

TREMstop Acrylic SP meets or exceeds the requirements of the following specifications:

- UL 1479 (ASTM E814)
- UL 263 (ASTM E119)
- UL 723 (ASTM E84)
- UL 2079 (ASTM E1966)
- ASTM E1399
- ASTM E2307
- CAN/ULC-S115
- CAN/ULC-S101M

The Greenguard Gold certification on TREMstop Acrylic SP ensures safety for use in the most sensitive indoor environments including hospitals and schools.

---

### AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 5 gal (19 L) pails.

---

### COLORS

Available in Rust Red, Limestone, and White. Custom colors are available upon request. Contact Tremco Customer Service for more information.

---

### LIMITATIONS

Not recommended for use with passive fire containment systems not listed or approved by Tremco. Refer to UL listings at [www.UL.com](http://www.UL.com). Contact Tremco Technical Services for additional information.

## WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Flame Spread	ASTM E84	15
Smoke Development	ASTM E84	0
Movement Capability	ASTM C719, UL2079; Class I, II, III	± 25%
Peel Strength	ASTM C794	10 to 20 ( <i>substrate dependent</i> )
VOC Content		40 g/L
Antifungal		Contains an antifungal additive

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TSASP-DS/0123



Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



[tremcosealants.com](http://tremcosealants.com) | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)