



1000A

1090+ / 1100 / 1105 Corded Scanner



Reliable Scanning Built with Affordability

CipherLab's affordable handheld corded scanners deliver reliability at its finest for streamlining workflow. With fast paced scanning always in demand, these handheld scanners will accelerate your productivity in the retail, healthcare and manufacturing industries with ease, all the while minimizing total cost of ownership.



General Corded Scanner



1000A

1090+

1100

1105

	1000A	1090+	1100	1105
Performance				
Category	Linear imaging scanner (for barcodes up to 150mm wide)	CCD contact scanner (for barcodes up to 90mm wide)	Linear imaging scanner	
Optical sensor	1500 pixels	2048 pixels	3648 pixels	2048 pixels
Light source	Red LED (650 nm)		Red LED (630 nm)	
Resolution	3 mil	4 mil	3 mil	4 mil
Depth of field 13 mil barcode	0 to 12cm / 0 to 4.72 in.	0 to 5cm / 0 to 2 in.	2.5 to 20cm / 1 to 7.9 in.	
Scanning angle	Pitch $\pm 70^\circ$ Skew $\pm 40^\circ$	Pitch $\pm 70^\circ$ Skew $\pm 70^\circ$	Pitch $\pm 70^\circ$ Skew $\pm 70^\circ$	
PCS	Minimum 30%			
Scan rate	200 scans / second	100 scans / second	100 scans / second	
Auto-sense mode	N / A		Yes	
Interfaces supported	RS232, Keyboard wedge, USB	RS232, Keyboard wedge, USB HID, USB Virtual Com, IBM 4683 / 4694	RS232, Keyboard wedge, USB HID, USB Virtual Com, IBM 4683/4694	
Barcodes supported	Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Italian and French Pharmacodes, Plessey, Telepen, UPC / EAN / GS1-128, and more			
Programmable features	Data editing, interface selection, symbology configuration			
Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German			
Physical				
Dimension L x W x H	17 x 8 x 4.8 cm / 6.7 x 3.1 x 1.9 in.	18.2 x 10.4 x 6.4 cm / 7.2 x 4.1 x 2.5 in.	14.5 x 9.3 x 7.4 cm / 5.7 x 3.7 x 2.9 in.	
Weight without cable	203 g / 7.2 oz. (w / cable)	148 g / 5.2 oz.	165 g / 5.8 oz.	
Color	Ivory or Black	Ivory	Light gray or dark gray	
Switch	Rubber switch		Micro switch	
Electrical				
Voltage	+5V $\pm 5\%$		+5V $\pm 10\%$	
Power consumption Standby / Operating	30mA / 120 mA	45 mA / 105 mA	60 mA / 190 mA	
User Environment				
Operating temperature	0 ° to 50°C / 32° to 122°F			
Storage temperature	-20° to 60°C / -4° to 140°F			
Operating/storage humidity Non-condensing	10% to 90% / 5% to 95%			
Impact resistance Multiple drops onto concrete	1.0 m / 3.3 ft. Drops		2m / 6.6 ft. Drops	
Electrostatic discharge	Conforms to ± 15 kV air discharge and ± 8 kV contact discharge			
Regulatory compliance	BSMI, CE, RCM, FCC, IC, KC, RoHS, REACH, WEEE, ErP		BSMI, CE, RCM, FCC, IC, RoHS, REACH, WEEE, ErP	
Configuration	Setup options include Windows*-based ScanMaster/ScanManager, by direct connection or printing out barcode settings. OPOS driver ready.			
Accessories	Includes attached cable		Detachable cable, desk / wall mount included with 1100 Optional auto-sense stand for 1100	
Warranty	5 years			

ACCESSORIES

1100/1105 Auto-sense Stand



1100/1105 Holder

Can be used on tabletop
or wall mounted



HEADQUARTERS
CipherLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec.2
Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

**CipherLab Electronics Trading
(Shanghai) Co., Ltd.**
J Room, 4F, No.728 West Yan'an Rd.
Changning District, Shanghai
China 200050
Tel +86 21 3368 0288
Toll Free 400 920 0285
Fax +86 21 3368 0286

CipherLab USA Inc.
2552 Summit Ave STE 400
Plano, Texas, USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab Europe
Flight Forum 40,
5657 DB Eindhoven, The Netherlands
Tel +31 40 295 1510