

MS836 Affordable 1D laser with hands-free stand Includes 5-Year no hassle Warranty*

The Unitech MS836 is the most cost-efficient 1D laser barcode scanner in the market. With excellent and reliable reading performance; the MS836 has the capability to easily read 3 mil 39 barcodes, including long labels up to 40 alphanumeric characters. A brilliant choice for various industrial application requirements.

The MS836 1D laser scanner comes with: Hands-free stand and 5-year no hassle warranty!

In the AIDC 1D laser scanner range, auto-sensing option is very limited. Unitech is determined to go beyond market expectation and is committed to making your day-to-day business operation more convenient; making MS836 the perfect choice in increasing work efficiency, while meeting requirements for all industrial usage by supporting trigger mode, presentation mode and auto-sensing mode.

Ergonomic and durable Design

This ergonomic design makes the MS836 fit comfortably in any hand, reducing fatigue during long-time scanning tasks. Additionally, the MS836 features an IP42 rating and can withstand multiple drops to concrete from 1.5 meters, ensuring durability and reliability.

Cost-effective 1D scanning solution

It's time to enjoy the great 1D scanning performance of the MS836 at a great competitive price! It becomes even more competitive since it comes standard with hands-free stand. The MS338 can be used in a wide variety of markets and applications such as: point-of-sale (POS), retail, warehousing, manufacturing to back-office environments.

The MS836 reads 3 mil barcodes and is designed to meet your 1D barcode scanning needs at great pricing!

Features

- All-in-one box; the MS836 comes standard with 1.9m USB cable, hands-free stand and 5-year no hassle warranty.
- Quality 1D laser at great price!
- Snappy performance; capability to easily read 3 mil 39 barcodes, including long labels up to 40 alphanumeric characters
- Multiple scanning modes; supports trigger mode, presentation mode and auto-sensing mode
- Supports print contrast reading up to 15%
- Durable design: 1.5 Meter drop test and IP42-rated





Hands-free stand included



Operational & Performance

Technology Laser engine

Light Source Visible Laser Diode 650nm

Scan pattern Single scan Scan rate 100 scans/sec

Minimum resolution 3 mil Scanning Depth of field 250mm Scanning width 220mm

15% UPC / EAN 100% Print contrast

Indicator Buzzer, LED

Symbologies

EAN-8, EAN-13, UPC-A, UPC-E, Code 39,

Code 128, EAN128, Codabar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, GS1, etc

Power Source

DC 3V to 5V Operation Voltage

Current consumption: Operation mode: < 85 mA

Standby mode: < 36 mA

Enclosure

Scanner dimension L95 mm x W70 mm x H160 mm

Scanner weight 150a

Operation modes

Trigger Mode, Automatic Mode.

Communication

Interface USB (USB cable 1.9 m straight)

Regulator approvals

CE, FCC DOC compliance

Accessories

Hands-free stand, USB cable



Environmental

IP42 IP rate

Operating Temperature 0°C to 45°C -20°C to 60°C Storage Temperature

Relative Humidity 5% to 85% relative humidity,

non-condensing

Mechanical Shock 1.5 M

Warranty*

5-Year No Hassle Warranty (scanner only)

1 Year warranty USB cable and hands-free stand warranty is limited to defective-on-arrival warranty.

Unitech Europe

Tilburg, The Netherlands

- Tel.: +31 (0)13 460 9292
- Email: Info@eu.ute.com
- Website: http://www.eu.ute.com





Unitech America Unitech Asia Pacific Unitech Europe

Unitech Japan

Unitech Taiwan

^{*} General warranty: Unitech reserves the right to call back the defect units at her discrete sole deshipping cost will be borne by Unitech except tax and duty if any. Unitech has full decision to stop abused, sabotage, and/or caused by the acts of God Specifications subject to change without not * NO Hassle Warranty: In case of defect during its valid warranty period, customer can simply regiportal. Unitech's logistic partner or service centre will send a replacement unit to the customer. The nitech may find it necessarily. Upon the calling, the returning verage before expiration if the defect is found due to

the defect symptom and serial number of the unit at Unitech stomer does not need to return the defect unit*