

Friction ring®



Product Name	Safe working Load	Ø A	Ø B	Ø C	Ø D	Ø Rope Recommended	Weight
	SWL					Halyard/Listening	
	Kg	mm	mm	mm	mm	mm	gr
Fr 10	700	7	10	12	24	4/6	2
Fr 14	1000	10	14	16	34	6 /10	4
Fr 20	1500	14	20	22	49	10/16	16
Fr 14 HT	1200	10	14	16	34	6/10	6
Fr 20 HT	2500	14	20	22	49	10/16	24



Nodus Friction ring® ~ Friction ring

Fr®, the Nodus Factory® friction ring is self-lubricating, very light, reliable and strong.

- The Nodus friction ring is used in numerous applications and for all types of rope.

Use

- ❑ Mast foot, in-hauler.
- ❑ Barber, in-haulers or as spare pulley
- ❑ Hoists (mainsail, vang, running backstay,...etc)

Advantages

- ❑ Treated with MoS2, mechanical lubricant
- ❑ Weight/strength ratio
- ❑ Performance, lightness and reliability
- ❑ Reliable and maintenance free

Specifications

- ❑ Friction ring material in Self-lubricating technical plastic resin – MoS2 self-lubricating ~ black

Nodus and tricks

Create the deck plan under your control!

- Block-Loop®, textile with core and sheath made of 100% Dyneema® R2 12fx pre-stretched, coated ~ Light grey / black
- Block®, clamping and holding ring, made of technical PA, which can lock and quickly fix a low-friction ring.

