

smartlink®



CYCLOPS MARINE

Wireless load sensor that sends data to smartphones and instruments



| Model | | nano | 2t | 5t | 10t | 20t |
|----------------------|--------|--|----------|----------|----------|-----------|
| Maximum Working Load | tonnes | 0.6 | 2 | 5 | 10 | 20 |
| Dimensions | mm | 64x55x17 | 79x55x19 | 83x66x22 | 93x74x25 | 107x88x39 |
| Aperture max. width | mm | 17.5 | 30.3 | 37.4 | 37.3 | 38.8 |
| Aperture max. height | mm | 9.0 | 13.0 | 14.5 | 16.6 | 19.2 |
| Strop diameter** | mm | 4.0 | 9.0 | 10.7 | 12.4 | 15.0 |
| Metal body | | Al6082-T6 | Ti6Al-4V | | | |
| Housing | | CNC machined Acetal Housing (IP67 rated) | | | | |
| Weight | grams | 72 | 160 | 210 | 360 | 790 |
| Battery Life | | 220 hours | | | | |
| RRP (incl. GST) | | \$1,926 | \$3,466 | \$4,239 | \$4,818 | \$5,976 |

*Load data available via free smartphone app, optional gateway package available (AU\$652 inc. GST) to connect on leading marine electronics.

**Basket strop configuration assumes two diameters of strop through aperture.

Higher MWL units available, contact us for more information.

www.cyclopsmarine.com
info@cyclopsmarine.com

