

# Product Bulletin

## SLIDE OUT

### FOOD GRADE DRY SILICONE SPRAY

#### FEATURES:

Concentrated formula. A little SLIDE OUT goes a long way.  
Reduces friction between moving parts even for metal-to-metal contact surfaces.  
Clean, dry spray does not leave a sticky residue behind.

#### DESCRIPTION:

SLIDE OUT is designed to lubricate equipment used in the packaging and processing industry. Slide Out leaves a non-staining, dry, pure silicone film to lubricate moving parts, reducing friction and wear. SLIDE OUT is heat stable from -30°F to 300°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Complies with FDA regulations, CFR Title 21, paragraph 178.3570 when fully cured. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.

#### APPLICATIONS:

Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. An excellent product for food processing plants, restaurants, apparel and accessory manufacturing, tank closure seals, plastic products, RV dealers, hotels/motels, machine shops, homes, service hinges, auto/RV repair shops and institutions.

#### DIRECTIONS:

Read cautions carefully before use. Area to be lubricated should be clean and dry. Shake well before use. Hold can 6-8 inches from surface. Spray in short bursts. Spray no more than required to lubricate surface. Do not spray electrical equipment while in use. Wait 5-10 minutes before operating electrical equipment after using. Spray is dry. Do not expect a liquid. Used as directed, it will not harm most surfaces.

#### SPECIFICATIONS:

FORM:.....Solvent-Based Aerosol  
ODOR:.....Mild Solvent  
COLOR:.....Clear  
COLD STABILITY:.....0°F  
TOXICITY:.....400 ppm OSHA TLV  
STORAGE STABILITY:.....1 Year +

FLASH POINT:.....<5°F TCC  
FLAME EXTENSION:.....None  
SOLUBILITY IN WATER:.....40%  
SPECIFIC GRAVITY:.....0.76  
% VOLATILE BY VOLUME:.....96%  
PROPELLANT:.....Hydrocarbon

FOR FURTHER INFORMATION REFER TO THE MATERIAL SAFETY DATA SHEET

#### PACKAGING:

Available in 12 - 20 oz. cans per case.

PRODUCT CODE:.....5380



## SOUND RESTAURANT SUPPLY, INC.

2505 Frank Albert Road, Suite B 120  
Fife, Washington 98424

Toll Free 1-800-300-0965

Fax 253-926-1577

[www.SoundRestaurantSupply.com](http://www.SoundRestaurantSupply.com)