

HETHON FEEDER PARTLIST 51-FS-GE

V1.3

| Pos. | Drw-Number | Description | Material | Wearing parts | Qty |
|------|----------------|---|----------------------|---------------|-----|
| 1 | 40/50-001-15 | FRAME | AISI304 | | 1 |
| 2 | 40/50-612-00 | GEARED MOTOR IE3 0,18 kW 3f 50Hz 230/400 V | | | 1 |
| 3 | 40/70-512-90 | BLIND PLATE | AISI304 | | 1 |
| 4 | 40/70-512-91 | CLIP | POM Acetal Copolymer | | 4 |
| 5 | 40/50-500-01 | PADDLE BEARING HOLDER front | AISI304 | | 2 |
| 6 | 40/50-505-00 | PLAIN BEARING (Paddle front/back) | Tin Bearing Bronze | X | 4 |
| 7 | 40/50-004-01 R | PADDLE RIGHT | AISI304 | | 1 |
| 8 | 40/50-004-01 L | PADDLE LEFT | AISI304 | | 1 |
| 9 | 40/50-004-05 | PADDLE BLOCK RING | AISI304 | | 2 |
| 10 | 40/50-010-04 | FORK | DURAL | | 2 |
| 11 | 40/50-010-02 | GUIDE ON FORK | POM Acetal Copolymer | X | 4 |
| 12 | 40/50-505-05 | DISTANCE WASHER FORK - 6mm Right side | POM Acetal Copolymer | X | 1 |
| 13 | 40/50-505-06 | DISTANCE WASHER FORK - 2mm Left side | POM Acetal Copolymer | X | 1 |
| 14 | 40/50-010-05 | BREAK PIN - DIN 1481 5 x 32 | | | 2 |
| 15 | 40/50-501-00 | BALL BEARING for main drive shaft front | | X | 1 |
| 16 | 40/50-502-00 | BALL BEARING for main drive shaft back and excenter shaft | | X | 3 |
| 17 | 40/50-018-00 | EXCENTER assembly | | | 1 |
| 18 | 40/50-007-00 | MAIN DRIVE SHAFT assembly | AISI304 | | 1 |
| 19 | 40/50-007-02 | KEY 5 x 5 x 10 | | | 1 |
| 20 | 40/50-017-00 | DISTANCE BUSH main drive shaft | AISI304 | | 1 |
| 21 | 40/50-513-18S1 | SPROCKET T18 Motor | 430 | X | 1 |
| 22 | 40/50-514-15S1 | SPROCKET T15 Main drive shaft | 430 | X | 1 |
| 23 | 40/50-515-18S1 | SPROCKET T18 Excenter | 430 | X | 1 |
| 24 | 40/50-516-12S1 | SPROCKET T12 Chain tensioner | 430 | X | 1 |
| 25 | 40/50-021-00 | BOLT CHAIN TENSIONER (012.9 SC SHLDSCR H8 (M8)10X20) | AISI304 | X | 1 |
| 26 | 40/50-532-00 | PLAIN BEARING for sprocket chain tensioner | Tin Bearing Bronze | X | 1 |
| 27 | 40/70-021-03 | WASHER for bolt chain tensioner | AISI304 | | 1 |
| 28 | 40/70-022-01 | GUIDE NUT DIN 508 M8 for bolt for sprocket | AISI304 | | 1 |
| 29 | 40/50-009-02 | BEARING SUPPORT | AISI304 | | 1 |
| 30 | 40/50-023-00 | FILL PLATE BEARING SUPPORT | AISI304 | | 1 |
| 31 | 40/50-521-00 | BUSH BEARING SUPPORT | AISI304 | | 2 |
| 32 | 40/50-517-02 | CHAIN | AISI304 | X | 1 |
| 33 | 40/50-518-01 | CHAIN LOCK | AISI304 | X | 1 |
| 34 | 50-014-01 | HOPPER SUPPORT | AISI304 | | 1 |
| 35 | 50-013-01 | FRONT PANEL | AISI304 | | 1 |
| 36 | 40/80-511-23 | STARLOCK WASHER 12 | AISI304 | | 8 |
| 37 | 40/50-511-50 | TURN LOCK assembly | | | 6 |
| 38 | 40/50-011-01 | SIDE PANEL | AISI304 | | 2 |
| 39 | 40/50-012-01 | BACK PANEL | AISI304 | | 1 |
| 40 | 40/50-511-18 | LOCK BUSH BACK PANEL | AISI304 | | 2 |
| 41 | 40/80-511-30 | O-RING For lock bolt back panel | Rubber | | 2 |
| 42 | 40/70-508-05 | FOOT | Rubber | | 4 |
| 43 | 50-510-00 | HOPPER (standard) | | X | 1 |
| 43 | 50-510-10 | HOPPER (Food grade) | | X | |
| 43 | 50-510-20 | HOPPER (Anti static) | | X | |
| 43 | 50-510-30 | HOPPER (Chlorine resistant) | | X | |
| 44 | 40/70-006-00 | HOPPER SHAFT | AISI316 | X | 1 |
| 45 | 50-005-00 | HOPPER BEARING | POM Acetal Copolymer | X | 1 |
| 45 | 50-005-01 | HOPPER BEARING (Air flushed) | POM Acetal Copolymer | X | |
| 46 | 40/50-503-00 | SEAL (NBR) | Rubber | X | 1 |
| 46 | 40/50-503-01 | SEAL (Viton) | Rubber | X | |
| 47 | 40/80-000-01 | TYPE PLATE | AISI304 | | 1 |
| 48 | 40/80-000-00 | NAME STICKER | Sticker | | 2 |
| 49 | 40/80-000-02 | SAFTEY STICKER | Sticker | | 1 |
| 50 | 50-506-01 | NOZZLE AND INNER CLAMP | AISI304 | | 2 |