



The Go Chair® is #1 for portability! With convenient feather-touch disassembly, the Go Chair® allows you to experience lightweight travel and independence on the go. Enjoy dual swing-away storage bins and a compact turning radius for outstanding maneuverability. Available in an array of contemporary colors, it's time to get out there with the Go Chair®!

Variety of color options











Specifications 4-Wheel

Weight Capacity	300 lbs.
Maximum Speed ¹	Up to 3.7 mph
Ground Clearance ³	1.7" at anti-tip, 1.8" at motor, 2.7" at footplate
Turning Radius ³	25.5" with foot platform
Overall Length ³	33" with front rigging
Overall Width ³	25.5"
Seat-to-Ground Height	22"-23"
Seat-to-Deck Height	16.25"-17.25"
Front Tires	6" solid (caster)
Rear Tires	9" solid (drive)
Suspension	Limited
Range Per Charge ^{1,2}	Up to 8.7 miles standard, 10.9 miles extended range
Total Weight Without Batteries ^{3,7}	67 lbs. (front & rear base)
Heaviest Piece When Disassembled ³	36 lbs. (rear)
Standard Seating	Foldable, compact, lightweight 18"x17"
Drive System	Two-motor rear-wheel drive
Dual Braking System	Electronic, regenerative
Battery Requirements ^{3,4,5}	(2) 18 AH, or (2) 18 AH extended range
Battery Charger	2-amp, off-board, 3.5 amp extended range
Warranty	5-year limited on frame; 13-month limited on batteries 13-month limited on electronics; 13-month limited on drive motors;

HCPCS Code: K0899

POWER MOBILITY DEVICE, NOT CODED BY DME PDAC OR DOES NOT MEET CRITERIA

Features

- 18" x 17", 5-point swivel seat with latch release
- Compact turning radius
- Dual swing-away, under seat storage bins
- Height and width adjustable armrests
- Large footplate
- One hand feather-touch disassembly
- 60" lap belt
- The heaviest piece is only 36 lbs.

Accessories

- Armrest mount cane clip
- Cane/crutch holder (3" single, 3" double)
- Cup holder
- Lap belt (50", 70")
- Oxygen tank holder
- Rear mount bracket
- Saddlebag
- Safety flag
- Weather cover
- XLR USB charger

ptions

- 18 AH extended range batteries
- Additional battery pack

Military Patches





Pride offers a variety of lifts to transport your mobility product with ease. To find a compatible lift for your vehicle and mobility product, use our new Lift Finder application at pridemobility.com/lift-finder/

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition tire type and condition. These specifications can be subject to a variance of +10%, -5%.
- 2 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3 AGM or Gel-Cell type required.
- 4 Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5 Battery weight may vary based on manufacturer.
- 6 Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA and ISO 7176 series standards. All specifications subject to change without notice.









