



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product name	1100 FS Product Series
MSDS name	1100 FS Product Series - Various Colors
Product name(s) covered	See Section 16 for Product Names Covered.
CAS #	Mixture
Product use	Adhesive and/or Sealant
Generic description	Moisture Cure Polyurethane Based Formulation
Manufacturer	Bostik, Inc. 11320 Watertown Plank Rd Wauwatosa, WI 53226 USA
24 hour emergency assistance	Telephone: 1-800-227-0332 (Outside U.S.) 1-703-527-3887
General assistance	Telephone: 1-800-843-0844
MSDS assistance	Telephone: 1-800-843-0844

2. Hazards Identification

Emergency overview	Contact with this material can cause irritation to the skin, eyes and mucous membranes. Thermal decomposition/burning may produce toxic gases and fumes. Closed containers may rupture when exposed to high temperatures, or when the product has been contaminated with water. Avoid breathing hot mists and vapors. This product contains a respiratory and skin sensitizer. Causes respiratory tract irritation and may cause allergic respiratory reaction. May cause permanent respiratory damage. Product vapors are potentially irritating to skin. May cause allergic skin reaction and dermatitis.
Potential health effects	
Eyes	This product may cause irritation to the eyes. May cause temporary corneal injury.
Skin	This product may cause irritation to the skin. Isocyanates may react with skin protein and moisture to cause itching, reddening, swelling, scaling or blistering. Individuals previously sensitized to this material may experience these symptoms from exposure to very small amounts of liquid or vapor.
Inhalation	This product may cause irritation to the respiratory system. Single large doses, and/or repeated exposures, may lead to sensitization to diisocyanates or polyisocyanates (asthma or asthma-like symptoms), causing an individual to experience adverse effects at exposure levels well below exposure limits or guidelines. Symptoms may include chest tightness, wheezing, shortness of breath, coughing or asthmatic attack, and may be delayed up to several hours. Extreme asthmatic reactions can be life threatening. Once sensitized, an individual may experience adverse symptoms upon exposure to dust, cold air or other irritants. Sensitization can last several months, years or be permanent in some cases.
Ingestion	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. This product may produce corrosive damage to the gastrointestinal tract if it is swallowed.
Target organs	The lungs and skin may be targeted and damaged by components of this product.
Signs and symptoms	Signs and symptoms of overexposure to this product include headache, irritation of upper respiratory tract, asthmatic symptoms, chest tightness, breathing difficulty, coughing, sore throat, eye irritation, skin irritation and/or diarrhea.
Hazard statements	This product contains Methylene Diphenyl Isocyanate (MDI) which is a potential skin sensitizer and has been shown to alter cells in certain experiments. Although inconclusive, these cellular changes are thought to indicate potential carcinogenicity. Risk to your health depends on duration and concentration of exposure.

3. Composition / Information on Ingredients

Hazardous components	CAS #	Percent
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Methylene Diphenyl Isocyanate (MDI)	101-68-8	0.1 - 1
Phenylethane	100-41-4	0.1 - 1
Carbon black	1333-86-4	0.1 - 1

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Skin contact	For skin contact flush with large amounts of water while removing contaminated clothing. If skin irritation persists, call a physician. For severe exposure, immediately get under a safety shower and begin rinsing.
Inhalation	If inhaled, immediately remove the affected person to fresh air. Call a physician if symptoms develop or persist. Administer oxygen or artificial respiration as needed.
Ingestion	If the material is swallowed, get immediate medical attention or advice. Do not induce vomiting without medical advice. Never give anything by mouth to a victim who is unconscious or is having convulsions.

Notes to physician

Provide general supportive measures and treat symptomatically. Contact Bostik to determine whether any additional information is available. Eyes: Stain for evidence of corneal injury. If cornea is burned, apply antibiotic/steroid preparation as needed. Skin: This product contains a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn. Ingestion: Treat symptomatically. Inhalation: This material contains a known pulmonary sensitizer. Any individual experiencing dermal or pulmonary sensitization should be removed from exposure to any diisocyanate. May aggravate existing heart conditions, particularly those with abnormal heart rhythms.

5. Fire Fighting Measures

Hazardous combustion products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Additional decomposition products include oxides of nitrogen, amines, hydrogen cyanide and isocyanate-containing compounds.
Extinguishing media	
Suitable extinguishing media	Dry chemical, foam, carbon dioxide, water fog.
Fire fighting equipment/instructions	Firefighters should wear full protective clothing including self contained breathing apparatus. Avoid contact with isocyanates. During a fire, isocyanate vapors and other irritating and highly toxic gases may be produced.
Flash point	160 °F (71.1 °C)

6. Accidental Release Measures

Emergency action	Wear appropriate personal protective equipment. Do not allow product to enter sewer or waterways. Follow all Local, State, Federal and Provincial regulations for disposal. Regulations vary. Consult local authorities before disposal.
Spill or leak procedure	Scrape up material and place in steel drums that are in good condition. Thoroughly clean area where spill occurred. Remove sources of ignition. Ventilate area of spill.

Containment procedures

Isolate spill area. Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Liquid spills: Cover spills with absorbent clay or sawdust and collect material in open container and neutralize with a solution containing 2% liquid detergent, 3% concentrated ammonium hydroxide and 95% water. Wash spill area clean with the neutralization solution. Remove container to a safe place, cover loosely and allow to stand for 24 to 48 hours letting evolved carbon dioxide escape. Collect and contain for disposal.

Pellet or chip spill: Collect and contain for salvage or disposal. Molten adhesive spill: Placard hot material, allow to cool and remove. If material is not cured once cooled, follow neutralization directions for liquids listed above. Collect and contain for disposal.

Reporting

See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements.

7. Handling and Storage

Handling

Do not get this material in your eyes, on your skin, or on your clothing. Wash hands after handling and before eating. Do not breathe gas/fumes/vapor/spray. Wear respiratory protection if the material is heated, sprayed, used in a confined space or if exposure limit is exceeded. This product can produce asthmatic sensitization. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must avoid fumes from this product. Wear appropriate protective equipment to avoid contact with skin and eyes.

Storage

Keep in a dry, cool and well-ventilated place. Keep away from heat. Keep away from direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition.

Empty container precaution

Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

8. Exposure Controls / Personal Protection

Engineering controls

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. Explosion proof exhaust ventilation should be used.

Personal protective equipment

Eye protection

Wear safety glasses with side shields.

Skin and body protection

Use impervious gloves. Work clothing sufficient to prevent all skin contact should be worn, such as coveralls and long sleeves.

Respiratory protection

Avoid breathing vapor and/or mists. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA) or a supplied air respirator.

General

Eyewash fountains and emergency showers should be readily available.

Additional exposure data

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m³ & ppm

Phenylethane	100-41-4	ETHYL BENZENE 20 PPM
Methylene Diphenyl Isocyanate (MDI)	101-68-8	METHYLENE BISPHENYL ISOCYANATE (MDI) 0.005 PPM
Xylenes (o-, m-, p- isomers)	1330-20-7	XYLENE (O, M AND P ISOMERS) 100 PPM

US NIOSH Pocket Guide to Chemical Hazards: Ceiling Limit Value and Time Period (if specified)

Methylene Diphenyl Isocyanate (MDI)	101-68-8	METHYLENE BISPHENYL ISOCYANATE 0.2 MGM3 - 0.020 PPM 10-min
-------------------------------------	----------	--

US OSHA Table Z-1-A: Time Weighted Average (TWA): mg/m³ & ppm

Phenylethane	100-41-4	ETHYLBENZENE 435 MGM3 - 100 PPM
Xylenes (o-, m-, p- isomers)	1330-20-7	XYLENE (O-, M-, P- ISOMERS) 435 MGM3 - 100 PPM

9. Physical & Chemical Properties

Target solids	96 %
Density	1.22 g/cc
Odor	Solvent
Color	Various
Physical state	Paste
Freeze protect	No

VOC (Volatile Organic Compounds) 2.7 % (33 g/L)

10. Chemical Stability & Reactivity Information

Hazardous reactions/decomposition products Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Additional decomposition products include oxides of nitrogen, amines, hydrogen cyanide and isocyanate-containing compounds.

Hazardous polymerization Hazardous polymerization can occur with elevated temperatures or contact with water.

Conditions to avoid Avoid Strong Acids. Avoid amines, strong bases, alcohols and metallic hydrides. Keep away from sources of ignition.

Stability This product is stable under normal conditions but will react slightly with water to release some heat and carbon dioxide. The reaction is not violent. Carbon dioxide, carbon monoxide and in high temperature (800° F) low oxygen atmospheres such as in fire situations, hydrogen cyanide may be released.

11. Toxicological Information

Carcinogenicity If this product contains any carcinogens, they will be noted below: This product contains Methylene Diphenyl Isocyanate (MDI). MDI is not listed by the NTP, IARC or regulated by OSHA as a carcinogen. However, it has been shown to alter cells in certain experiments. Although inconclusive, these cellular changes are thought to indicate potential carcinogenicity.

Local effects Single large does, and/or repeated exposures, may lead to sensitization to diisocyanates or polyisocyanates (asthma or asthma-like symptoms), causing an individual to experience adverse effects at exposure levels well below exposure limits or guidelines. Symptoms may include chest tightness, wheezing, shortness of breath, coughing or asthmatic attack, and may be delayed up to several hours. Extreme asthmatic reactions can be life threatening. Once sensitized, an individual may experience adverse symptoms upon exposure to dust, cold air or other irritants. Sensitization can last several months, years or be permanent in some cases. Chronic exposure may cause lung damage, including fibrosis and decreased lung function, which may be permanent.

12. Ecological Information

Ecotoxicological information No data available for this product.

13. Disposal Considerations

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. Empty containers must be handled with care due to product residue. Do not heat or cut empty container with electric or gas torch.

14. Transport Information

DOT

Not regulated as hazardous goods.

IATA

Not regulated as hazardous goods.

IMDG

Not regulated as hazardous goods.

15. Regulatory Information

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200

Federal regulations

All components are on the U.S. EPA TSCA Inventory List.

US CWA Section 311 Reporting Quantities of Hazardous Substances: Reportable quantity

Phenylethane 100-41-4 ETHYLBENZENE 1000 LBS

Xylenes (o-, m-, p- isomers) 1330-20-7 XYLENE (MIXED) 100 LBS

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Phenylethane 100-41-4 ETHYLBENZENE US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Methylene Diphenyl Isocyanate (MDI) 101-68-8 METHYLENEBIS(PHENYLISOCYANATE) (MDI) US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Xylenes (o-, m-, p- isomers) 1330-20-7 Xylene (mixed isomers) US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

State regulations

If this product contains any California Proposition 65 chemicals at reportable levels they will be listed below:

Di-Isodecyl Phthalate (DIDP)

Phenylethane

Methanol

Restriction of Hazardous Substances (RoHS)

The product(s) covered by this (M)SDS do not contain or are under the prescribed levels of prohibited substances listed under 2011/65/EU Hazardous Substances Restricted or Prohibited in Electrical Equipment, including lead (CAS # 7439-92-1), mercury (CAS # 7439-97-6), cadmium (CAS # 7440-43-9), hexavalent chromium (CAS # 7440-47-3), polybrominated biphenyls (PBB) and polybrominated diphenyl ethers (PBDE).

International regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

Substances of Very High Concern (SVHC)

The product(s) covered by this (M)SDS do not include any of the substances above a concentration of 0.1% weight by weight (w/w) in the Candidate List of Substances of Very High Concern (SVHC) for authorization published or proposed by ECHA on the following dates:

- October 28, 2008
- August 31, 2009
- January 13, 2010
- March 8, 2010
- June 18, 2010
- October 14, 2010
- December 15, 2010
- June 20, 2011
- December 19, 2011
- February 17, 2012
- June 18, 2012
- December 19, 2012
- June 20, 2013
- December 16, 2013

HMIS Ratings

Health: 2*

Flammability: 2

Physical hazard: 0

Personal protection: X

SARA 311/312 HAZARD CATEGORIES

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

WHMIS status

Controlled

WHMIS labeling**WHMIS classification**

D2A - Other Toxic Effects-VERY TOXIC

D2B - Other Toxic Effects-TOXIC

16. Other Information

Product name(s) covered

A19200 - 1100 FS WHITE	L
A19200-7C - 1100 FS WHITE	5GL
A19200-95 - 1100 FS WHITE	52GL
A19217 - BOST 1100FS WHITE	24/10.1
A19221 - 1100FS WHITE S/PK	12/20.3
A25600 - 1100 FS BLACK	L
A25614 - BOST 1100FS BLACK	24/10.1
A25617 - BOST 1100FS BLACK S/P	24/10.0
A25618 - 1100 FS BLACK	L
A26800 - 1100 FS STONE	L
A26814 - BOST 1100 FS GRAY	12/30.0
A26815 - BOST 1100FS GRAY	24/10.1
A26816 - 1100FS GRAY S/PK	12/20.3
A44400 - 1100 FS PUTTY	L

Disclaimer

The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Further information

If there are any characters following an individual item number, they are just designations for the various types of packaging that are available for this product. For example, a product "G12345-XX" is item number "G12345" with a packaging designation of "XX". These characters do not indicate a different product nor a different regulatory, health, safety and/or environmental status. This document covers the item numbers listed above for all of their packaging types.

Issue date

05/06/2014

Prepared by

Bostik, Inc. Regulatory Affairs

Supersedes

02/18/2014