



Letzring, Inc
Inventory List

A 1: Cooper Cameron Valve

Size 3 SN: VS0014011
Class: 300 Date 08-06
Mop 750 @ 100F

A 2: Walworth Valve

12 in 300WLB WH65332 MT 150 VO8R590

A 3: Neway

Size: 20 FP Class: 150 Body: LF2
Stem: LF2/ENP Ball LF2/ENP Seat: Nylon-12
O-Ring: Lt Nitrile Mop 285@-50F Wog 252@225F
FigNo: TB3-F200R01L6-S18 SN: 15349-140-6
F-F: 36in Date: 05/07

A 4: Stainless Valve

Size 6in Model No: 600-150 Body: CF8M
Ball/Stem: 316 Seat: R-T

A 5: Shafer Explosion Proof Valve

Cat No: 56804N8 Class: 1 Group: C.D
1 Amp 125 Volts A.C
10 Amp 28 Volts D.C
Test 3000Psi

A 6: Hydril Valve

Model: 43G-0001-012 Type 4BFB
Assy PN-436-0001-012

A 7: Large Stainless Tank

Diam: 54" Height: 124 13/16"
Nominal Capacity: 1000 Gallons Design Pressure: -.5 to 2.5

PSIG

Design Temp: -50F to 250F

A 8: Caldon LEFM Transmitter with Caldon LEFM 200 Ultrasonic Flow Meters

Model No: 280C-TA-6-40-SS-600-EX
Part Code: H8TX11651000000
Serial No: 080128003A Year 2008
Supply Voltage 120 VAC 50-60 Hz

A 9" Valve Gaskets

(5) Gasket, SPWD: 28in Pipe, 300lb, 304 SS wind
(5) Gasket, SPWD: 34in Pipe, 300lb, 304 SS wind
(1) Gasket, SPWD: 36in Pipe, 600lb, 304 SS wind

A: (1) Series '80 Pneumatic Valve Positioner
(4) TK Valve Size 3x3, API 1500

B: (5) Valve, Ball, 4", 300#, RF, RP, ASTM A352 LCC Body, Floating Ball, PTFE Seats, 316SS Ball & Stem, Lever Operated, NACE MR-0175, QL-3

C: (1) Hudson Auto-Variable Fan, Hub Model: 2104HPL , Hub SN: T 10603

D: (4) Hubbell Killark Cat No. XB-684, SN 09092 &10492 & 08392 Vol 176 cu. In.

With Texsteam Super G Plug Valves
Part No: SK1172GA Size: 4 x 3 1/8
API: 1500 SN: AT03368(9)(76-77)

E; (1) Texsteam Super G Plug Valve

P/N: 9D-SK2024GABPMA Size: 8RP Class: 1500
S/N: 112216335-1 3695 PSI MOP @ +250F
Body: LCC 3750 PSI MOP @ -50F
Plug: 410SS SEAT NI/BRZ

DOM 10/11

Cameron 6FA

F-H: (3) Rotork

Serial Number: C11744/1201 & C11745/0801 & 1302
Actuator Type: EH325-3-DA
Max Pressure: 3000
Hydraulic Schematic: HS18667
Wiring Diag. No.: WD18735

- I: (3) TK Vlave**
Size: 8x6 API:300 Sn: 0644803904004-6
Body: LF2 Impact: Dom: 4/06
Ball: 4140 Stem: 4140 Seat: Teflon
Mop: 740 @ -20F Min
Mop: 665 @ 250F Max 6FA
- J: (5) TK Valves**
(2) Maxon
- K: (1) Valtek lg**
(1)Valtek sm
(1)Red
(1)Kitz 300SCLSLMM-NACE 3 MOD Gate 3 300# LCC RF BB
316/NACE (Orange Top)
- L: (1) Flowserve Dynamic Balance Valve**
Size: 3R Fig: P6949 DSP
Body: LCC API-6D 2500
Plug: Steel 6FA 6D-0116
Stem: 17-4PH B16.34 2500
SN: 61-485320 B: 1684847
250 6160 5710 8/29/11
MGR 250F 450F
NACE MR0175 -50F Spec
- M: Hubbell Killark w/TSGP**
Cat No: XB-864
Serial No: 08392 (& 10492)
Volume: 176 Cu. In.
Texsteam Super G Plug Vlave (TSGP)
Part No: SK1172GA Size: 4 x 3 1/8
API: 1500 SN: AT03369(&8)
Mop: 3680 Body: A352-LCC
Plug: 4130 Seat NI BRZ'
Temp: -50/+275 07/92 API-6D-0127
Valve, Plug: 4in, ANSI 1500, RTJ FLG, GR LCC Body, Regular
Pattern,
4140 Plug, 316 SS Tubing, Bun-N, O-Ring & Seal
- 1: Cameron Texsteam Super G Plug Valve**
P/N: 9D-SK1747GABP Size 4x2.62
S/N: 709491 3695 PSI Mop +250F

Body LCC **3750 PSI Mop -50F**
Plug: 410SS/CHR **Seat: NI/BRZ**
Dom: 05/08

Rotork Gears Control Mar-08

SN: C0245102-002 **Ratio 160 : 1**
Type: IW4 IR1 **Weight: 30Kg**
Tag No: PGC11988 **C1198802**
Spec: Low Temp (-60C) **File Ref: 100**

Rotork Actuator Control

SN: C119880201
Wiring Diag: 3000-000-08
Actuator Type: IQ 12FA10B4
Model: IQFM
Speed: 86
Torque Max 47.00

2&3: Pilot Valve – Anderson Greenwood Crosby

Type: 9 399C06SST ADF **Trim: T**
Set Press: 2.50 **Size 6in**
SN: 08/47391
Capacity: 4795.2 scfm air
Vacuum Set: 0.5
Capacity: 1675.0 scfm air

4: (2) Rotork Controls & Gear Boxes

Gears **Dec-06**
SN: C0186606-001 **Ratio 70 : 1**
Type: IW4 **Weight: 21Kg**

4cont: Controls

SN: C1174406/02
Wiring: 3000-400-06
Actuator Type: IQ12 **Base: FA10** **Coupling: B4**
Model: IQFM **Speed: 43rpm** **Torque Max: 81Nm**
NEMA/Enclosure: 6/WT **EP**
Temp. Code: T4

**Lub: Mobil 624 Motor Rating: .26kW 15min
Motor Supply: 480-3—60**

5: Flowserve Dynamic Balance Valve

Size: 3R Fig: N6945 DSP

Body: LCC APL-6D 2500

Plug: Steel 6FA 6D-0116

Stem: 17-4PH B16.34 2500

SN: 61-491776 BM: 1684846

6250 6160 5710 11/30/11

Mop 250F 450F

NACE MR0175 -50F SPEC40001R2

6: Cameron Gate Valve

5-1/8in 5000lbs CS Body

Pneumatic Actuator Operated

7: Fisher Controls

SN: 4491924 Type: 656 Size: 60

Flow Pipe

8: Manufacture TXT D-Plug Double Valve

Size 8" Rating: 1500 Passed Hydro

9: Red Valve

3 5225

Series

Pneumatic Positioner

10: Ball Valve

6in 300lb RF FLG CS Body

Reduced Port Lever Operated NACE MR-01-75

-20 to 250 Deg F

11: a: Rotork Control

SN: Z618550101

Wiring Diag: C22-00-2

Actuator Type: CVQ2400FA10

Output Max: 271 NM

Conduit Thread: 3/4 NPT

nema 6

Actuator Supplu: 100-240VAC

Rated Current: 2amps

b: LCC Check Valve

3in 300 LCC

c: Cameron Valve TK Valve

Size: 3x3 API: 150 SN: 112517873-4
Body: F316 Impact: -50 Dom: 08/12
Ball: CB7CU-1 Stem: 17/4 Seat: Teflon
Mop: 275 @ -50F Min Seat Test: 6FA
Mop: 215 @ 215F Max

d: DSI Valve

Size: 2 Body: CF8M Disc: CF3M
Pin: 316 Seat: CF8M
ASME B16.34 150 275 PSI 100F
Temp. 1000F Max API Trim No. 10

12: Cameron Valve

Size: 4x4 Api: 150 SN:11251367..
Body: F316 Impact -50
Ball: CB70CU-1 Stem: 17-4
Mop: 275 @ -50F Min Seat Test:
Mop: 215 @ 310F Max 6FA

13: Milton Roy Actuator

G63J4PEB711 147.00'GPH
SN: 02646790-1 100PSI

(2)Milton Roy Back Pressure Valve

Product Code: GVB166
Rating: 10 – 150 PSI Set: 50
SN: 1102465

14: Forum C-6710-71-2536-ZR-NL-349

Size: 4 Class: 150
285 Mop @ -50F 235 Mop @ 275F
DBB NACE API 907-6FA
Body: A350 LF2
Ball: CF8M+TC Seat: 174P+TC
Stem: 316 Seal: BUNA LT
SN: 1411587 Assy: 10 24 12
MO: 628398-3-1

15: (3) Bray Control

PN: 431000-11001466
SN: 701094101
ASME B16.34
B16.34 Class, P/T Rating

CL300#740psig/100F
Flg Drilling: 300#
Body: 516/70 Size 10in
Disc: CF8M Seat: RPTFE
Stem: 17-4 2009

16: (8) Cameron TK Valve

Size: 2x2 Api: 150 SN:
Body: F316 Impact: -50
Ball: F316 Stem: 17/4
Mop 275 @ -50F
Mop 215 @ 310F

AGFI Company PBV Valve C-6710-71-2536-ZR-NL 349

Size: 2 Class: 150
285 Mop @ -50F 235 Mop @ 275F
DBB NACE API 607-6FA
Body: A350 LF2 Ball: CF8M Seat: 174P
Stem: 174P Seal Buna Lt
SN: 1409641 MO: 628398-1-1 Assy: 08 20 12

17: Forum Ball Valve S-6410-31-3600-FT-NI 12 307

Size: 3 API Class 150
Body: CF8M Ball: CF8M Stem: 316 Seat: TFM
Seal: PTFE 275 mop @ -50F 170 mop@ 430F
SN: 1422910 Assy: 01 13 14

Neway Ball Valve ISO17292/BS5351

Size 2x1 ½ Class 150 Body CF8M Stem 316
Seat PTFE Ball 316 Mop 275 @ 100F Wog
Fig No: FE1-R20R01A

(5) Cameron TK Valve

Size 4x4 API 150 SN: 112513674-9
Body F316 Impact -50 Dom: 08/12
Ball CB7CU-1 Stem: 17/4 Seat: Teflon
Mop 275 @ -50F Min Seat Test
Mop 215 @ 310F Max 6FA

18: (2) Cameron Texsteam Super G Plug Valve

PN: 9D-L4015J42X6BP Size 4RP Class 1500
SN: 703137 3600 PSI Mop @ +250F

Body LCC 3600 PSI Mop @ -50F

Plug 410SS/CHR Seat NI/BRZ Dom 05/07

19: Cameron Texsteam Super G Plug Valve

PN 9D-SK201_GABPM Size 4RP Class1500

SN: 715200 3695 Psi Mop @ +250F

Body LTCS3750 Psi Mop @ -50F

Plug 410ss/CHR Seat NI/BRZ Dom 09/09 API 6D