

RECOMMENDED LUBRICANTS, FLUIDS AND CAPACITIES

UNIT	CAPACITY			GRADE
	U.S. GALLONS	U.K. PINTS	LITRES	
ENGINE AND FILTER	1.72	11.4	6.5	15 W 40
	1.78	11.8	6.75	20 W 40 ABOVE - 10°C (14°F) 20 W 50
				15 W 40 *10 W 30 BELOW - 10°C (14°F) 5 W 20
*THE USE OF 10 W 30 MULTI-GRADE OIL IS NOT ADVISABLE UNLESS THE TEMPERATURE WARRANTS IT. HOWEVER, IF A 10 W 30 MULTI-GRADE OIL IS USED TO ASSIST STARTING IN COLD WEATHER, IT MAY REMAIN IN THE SUMP AS LONG AS THE TEMPERATURE DOES NOT RISE ABOVE + 10°C				
MANUAL GEARBOX (INCLUDES FINAL DRIVE)	0.97	6.5	3.7	TO MEET SPEC MIL - L 2105C OR API - GL5. *SAE 75W BELOW - 10°C (14°F) SAE 80W ABOVE - 10°C (14°F)
*WHERE SAE 75W OIL IS NOT AVAILABLE SAE 80W OIL MAY BE USED				
FINAL DRIVE AUTOMATIC	0.42	2.6	1.5	SAE 80W { MIL - L 2105C API GL5
AUTOMATIC TRANSMISSION (CONVERTER)	1.57	10.5	6.0	ATF TYPE DEXTRON 11, ELF RENAULT MATIC D2 OR MOBIL ATE 220
BRAKE CIRCUIT		1.3	0.764	DOT 4
COOLING SYSTEM	2.9	19.37	11.0	ETHYLEN GLYCOL BASED (CONTAINING NO BORAX). MINIMUM 50/50 MIXTURE WITH WATER. TO BE USED ALL YEAR ROUND AND REPLACED ANNUALLY.
CLUTCH CIRCUIT		.66	0.378	DOT 4
WINDSHIELD WASHER RESERVOIR		9	5.5	
AIR CONDITIONING REFRIGERANT OIL	2.50 POUNDS		1.40 GRAMMES	SUNISO 5GS OR TEXACO CARPELLA 'E' OR EQUIVALENT R-12 - FREON OR ARCTON
FUEL TANK	13.5	11.5 IMP. GALLONS	51.6	91 OCTANE (UNLEADED)
WHEEL BEARINGS				SEALED FOR LIFE
STEERING RACK	0.3 U.S. PINT	.26	0.15	API SERVICE GL-5 (SAE - EP 90)