

CSI MasterFormat® Filing: Division 7: Thermal & Moisture Protection

07 21 00 Thermal Insulation
07 21 29 Sprayed Insulation

Division 9: Finishes

09 81 00 Acoustic Insulation
09 81 29 Sprayed Acoustic Insulation
09 83 00 Acoustic Finishes
09 83 16 Acoustic Ceiling Coating



MANUFACTURER INFORMATION:

International Cellulose Corporation
12315 Robin Boulevard | Houston, Texas 77045
(713) 433-6701 or (800) 444-1252 | FAX: (713) 433-2029

1. PRODUCT DESCRIPTION:

K-13 Special Blend, or KFC, is a **Thermal** and **Acoustical** cellulose insulation is used as an insulation/exposed finish for its acoustic and thermal benefits. K-13 Special Blend is a specification blending K-13 and SonaSpray "fc" and is often selected for a more refined finish while still meeting project requirements for thermal & acoustical performance. K-13 Special Blend has a **Refined Natural Texture** and is available in seven standard colors and custom integral colors.

2. BASIC USE:

K-13 Special Blend is typically used as an exposed ceiling finish for its acoustic and thermal benefits. It is appropriate in both interior and covered exterior applications such as parking decks.

3. MATERIAL COLORS:

K-13 is available in seven standard colors can also be specified in specially-matched custom colors.

STANDARD COLORS:



Color selection will affect the final price.

4. SURFACE PREPARATION:

K-13 Special Blend adheres to properly prepared substrates and conforms to any ceiling configuration including metal decking, barrel-vaults, concrete "T" corrugated decks, and other complex surfaces. Surfaces to receive K-13 Special Blend are to be inspected prior to installation to determine if pre-treatment is required.

5. APPLICATION:

K-13 Special Blend is installed by an international network of professional contractors licensed by ICC. These contractors are required to install K-13 using approved equipment, materials, and procedures. Due to the inherent texture of the material and application techniques, the installed material will have thickness variances. Compliance with applicable building codes and project requirements is the responsibility of the user and/or installing contractor.

SUSTAINABLE CREDIT CATEGORIES:

MATERIALS + RESOURCES:

RECYCLED CONTENT: 80% Pre-Consumer

REGIONAL MATERIALS: Manufactured by International Cellulose Corporation in Houston, TX.

MATERIAL INGREDIENT REPORTING: Inventoried to 1,000 PPM in accordance with the HPD Collaborative.

INDOOR ENVIRONMENTAL QUALITY:

INDOOR AIR QUALITY: UL GREENGUARD Gold Certified
May Contribute Towards:

LEED v4: Indoor Air Quality Assessment

LEED v4: Enhanced Indoor Air Quality Strategies

THERMAL COMFORT: K-13 has exceptionally low heat-loss characteristics with an R-Value of 3.75

ACOUSTICAL PERFORMANCE

LOW EMITTING MATERIALS:

M1 Classified as a Low Emitting Building Material
Compliant With:

LEED v4: Low Emitting Materials

CDHP/ California Section 01350

SCAQMD Rule 1168

CHPS- Acoustical Ceiling

TECHNICAL DATA:

ASTM STANDARDS COMPLIANCE

ASTM C 423	Sound Absorption
ASTM C 518	Thermal Conductivity
ASTM C 739	Cellulosic Fiber
ASTM C 1149	Spray-Applied Cellulose Insulation
ASTM D 2244	Light Reflectance
ASTM E 84	Surface Burning Characteristics
ASTM E 90	Sound Transmission
ASTM E 736	Cohesion/Adhesion - Bond Strength
ASTM E 759	Bond Deflection
ASTM E 859	Air Erosion
ASTM E 1042	Acoustical Absorption

ASTM C 423: Sound Absorption (NRC)

K-13 Special Blend Applied on Solid Backing

Inches	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
10 mm (.4")	.15	.28	.59	.86	.95	1.02	.65
15 mm (.6")	.15	.33	.69	.95	.98	.97	.75
20 mm (.8")	.16	.33	.75	.96	.98	.97	.75
25 mm (1")	.20	.44	.89	1.01	.98	.93	.85
35 mm (1.3")	.26	.62	1.02	1.07	1.01	.96	.95
45 mm (1.8")	.33	.77	1.12	1.11	1.01	.93	1.00

ASTM C 518: Thermal Conductivity

R-Value 3.75 PER INCH

AVERAGE APPLICATION THICKNESS	R-VALUE
1"	3.75
2"	7.5

ASTM D 2244: Light Reflectance

White: 84+	Tan: 46+
Light Gray: 73+	Gray: 45+
Beige: 71+	Black: 17+

ASTM E 84: Surface Burning Characteristics

CLASS 1, CLASS A RATED per ASTM E-84, UL-723, NFPA-255, & UBC-42

Flame Spread 5

Smoke Development 5

K-13 has been rated and approved by Factory Mutual Research Corporation for use in categories: I, II, III, & IV.

ASTM E 736: Cohesion/Adhesion - Bond Strength

Bond Strength >100psf

MISCELLANEOUS CODE APPROVALS & SPECIFICATIONS

- Underwriters Laboratories - Classified Code Compliance Report UL ER 5499
- Factory Mutual Research - Report Nos. 19678, 20399, and 24703
- Federal Defense Logistics Agency Cage Code: ONJU2
- Federal Specification - SS-S-111C
- Corps of Engineers Guide Specifications - CE-201.01
- Department of the Navy Guide Specifications - NFGS-07218
- EPA 40 CFR Part 248
- Los Angeles - RR-24311
- New York - MEA 65-96-M
- Meets California Bureau of Home Furnishings Standards
- Resource Conservation and Recovery Act

K-13 Special Blend does not contain silica dust, asbestos, mineral or glass fibers, or PCB's.

