



PRO-SPEC® 0W/20 SYNTHETIC MOTOR OIL

- **EXCELLENT FUEL ECONOMY**
- **HIGH VISCOSITY INDEX**
- **OUTSTANDING CORROSION PROTECTION**
- **EXCELLENT THERMAL AND OXIDATION PERFORMANCE**
- **EXCELLENT LOW TEMPERATURE PUMPABILITY**
- **FOR THE LATEST GASOLINE ENGINES**

The harsh Canadian climate poses a special problem for motor oils. Motor oils must flow at -40°C to provide constant lubrication in the winter, while maintaining film strength during operating temperatures in excess of 100°C . PRO-SPEC 0W/20 Synthetic Motor Oil meets this challenge, providing constant lubrication and film strength in the harshest environments.

PRO-SPEC® 0W/20 EXCELLENT FUEL ECONOMY

Today's new engines are built with such tight tolerances that in order to meet federal regulations motor oils are being manufactured lighter and lighter. Using a synthetic lower viscosity oil allows the engine to perform at optimum levels providing better fuel economy over the oil drain interval.

PRO-SPEC® 0W/20 HIGH VISCOSITY INDEX

Viscosity Index is an indicator of a lubricant's ability to resist viscosity changes when exposed to temperature changes. PRO-SPEC 0W/20 has an extremely high viscosity index of 163. This explains why PRO-SPEC 0W/20 provides constant protection regardless



of temperature. With a pour point of -51°C , PRO-SPEC 0W/20 can perform in the cold Canadian climate.

PRO-SPEC® 0W/20 OUTSTANDING CORROSION PROTECTION

Using an oil fortified with superior corrosion protection additives will ensure longer life for vehicles. Pro-Spec 0W/20 offers outstanding protection against wear, rust and corrosion. A must when dealing with large amounts of precipitation.

PRO-SPEC® 0W/20 EXCELLENT THERMAL AND OXIDATION PERFORMANCE

One of the most important aspects needed in today's motor oils is the ability to resist both thermal breakdown and oxidation. PRO-SPEC 0W/20 contains additive packages to enhance its ability to resist thermal breakdowns for extended periods as well as resist oxidation which greatly reduces the oils ability to protect lubricated parts.

PRO-SPEC® 0W/20 EXCELLENT LOW TEMPERATURE PUMPABILITY

Cold weather starts can put a great amount of stress on an engine so an oil is needed that offers low temperature fluidity. PRO-SPEC 0W/20 permits easier cold weather starts and reduces wear during low temperature start-up and operation.

PRO-SPEC[®] 0W/20

Synthetic Motor Oil

SPECIFICATIONS

Meets or exceeds API Service SN, SM, SL, SJ, and SH, as well as exceeding ILSAC GF-5/GF-4/GF-3/GF-2 for API Certified Gasoline Engine Oils. Use the appropriate viscosity grade as recommended in your vehicle owner's manual.

Specifications: API SN Plus, dexos1[™] second generation

TYPICAL PROPERTIES	ASTM TEST METHOD	RESULTS
Kinematic Viscosity		
Viscosity cSt @ 40°C	D445	44.5
Viscosity cSt @ 100°C	D445	8.3
Viscosity Index	D2270	163
Flash Point (COC)	D92	206°C
Pour Point	D97	-51°C
API Gravity		36.1
Calcium, Wt %		0.210
Sulfated Ash %		0.800
Zinc, Wt %		0.087
Base Type:		Group III Base Stock
• API Service Category		SN
• ILSAC Classification		GF-5
• API Resource Conserving		YES

Handling Information: For safe handling of the product, read the Safety Data Sheet (SDS).



CANADA

TEXAS • ONTARIO • SASKATCHEWAN

Phone: 800-827-0711 • www.texasrefinery.ca

**PRINTED 2020
CB105020E**