

How to Setup Your Paddle board and paddles. (Family)



Inflating the board.

1. Remove the board from the bag, undoing all the straps, (remember to keep the straps and bag safe).
2. Lay the board flat and undo both valve covers, making sure the valves are sitting up (Pictures Below).



3. Insert the hose into the board and connect to the pump where it states inflate (by the gauge) by twisting clockwise until tight. Make sure you pay attention to the black lever. This should be in the double action position (Pictures Below).



4. Pump the board until you find it hard to pump, then move the lever into the single action position (this will make it easier to pump). Carry-on pumping until you reach 18psi on the gauge. This should take around 15-20 minutes with two people pumping with both pumps supplied.



5. Release the hoses by twisting anti-clockwise and secure the valve covers.
6. Next turn over the board and insert the 3 fins by angling to the front and pushing down into the slot. Once in the slot slide backwards to secure the fins (See Below).



7. Next put the paddles together by inserting the tubes together. Press on the button to enable insertion. To extend the paddles length open the handles collar clip and extend to desired length before re-clipping.



8. Store the pumps and the bag in a safe location, ideally locked in a car.

Deflating the board.

1. Disassemble the paddles and dry before storing in the bag.
2. Turn upside down and release the fins by moving them forward to slot and pull upwards and out.
3. If possible, please can you dry off the board with a towel.
4. Undo both valve covers and push/twist the valves down until air comes out, this will be very loud. Leave for 10 mins to deflate.
5. Fold the board in half vertically and then start folding from the front, use the strap to keep tight once rolled. Replace board back in the bag with your paddles, fins and pumps.