

Free Delivery all Zones

Foundation Inspections

Depending on size of structure, where you are located and the intended use of the building, you may be required to pull a permit for your building & foundation. In this case there are several possible changes to how your post/foundation is constructed:

1. 15" Diameter holes vs 12"
2. Poured concrete vs pole pads
3. Wind cleats nailed to bottom of posts
4. Jobsite downtime due to inspections
5. An additional trip to complete foundation.

Due to these requirements by the Ohio and P.A. Building Codes, any foundation under inspection will be charged the following fee:

FOUNDATIONS UNDER INSPECTION:

ADD \$900

#1

Concrete Blocks



#2

Block / 4x4" Base



#3

4x6" Post Foundation



#4

6x6" Post Foundation



#5

Post/Rim



**ALL POST
FOUNDATIONS
MUST HAVE
SKIDLOADER ACCESS.**

	#1 - Blocks				#2 - Block/4x4" Base				#3		#4	
	0-12" slope	0-6" slope	6-12" slope	12-18" slope	up to 2' slope	0-4' slope	4-6' slope	4-8' slope				
8x8	85	265	305	345	1820	*	*	*				
8x10	125	265	305	345	2431	*	*	*				
8x12	125	265	305	345	2431	*	*	*				
10x10	175	305	350	395	2606	*	*	*				
10x12	175	305	350	395	2606	*	*	*				
10x14	225	385	430	475	2606	*	*	*				
10x16	225	385	439	493	3115	*	*	*				
10x20	275	465	529	593	3115	*	*	*				
12x12	*	390	444	498	2799	*	*	*				
12x14	*	490	544	598	2799	*	*	*				
12x16	*	490	555	620	*	3311	*	*				
12x20	*	*	*	*	*	3311	4052	*				
12x24	*	*	*	*	*	3820	4778	*				
14x16	*	*	*	*	*	3325	4073	*				
14x20	*	*	*	*	*	3325	4073	*				
14x24	*	*	*	*	*	3862	4816	*				
14x28	*	*	*	*	*	4167	5231	*				
14x32	ALL POST FOUNDATIONS MUST HAVE SKIDLOADER ACCESS.				*	4167	5231	*				
16x20					*	3525	*	4241				
16x24					*	4052	*	4988				
16x28					*	4584	*	5736				
16x32					*	4584	*	5736				
20x20	*	*	*	*	*	3588	*	4300				
20x24	*	*	*	*	*	4125	*	4915				
22x20	*	*	*	*	*	3620	*	4315				
22x24	*	*	*	*	*	4167	*	5089				
22x28	*	*	*	*	*	4721	*	5852				
22x32	*	*	*	*	*	4721	*	5852				

#1 Solid concrete blocks placed underneath runners of building. Only suited for smaller buildings.

#2 4x4"s placed crossways underneath building. 4x4"s supported with concrete patio blocks on low side and dug into ground on high side of slope.

#3 4x6" posts with 12" diameter hole & 12"diameter x 8" deep concrete pole pads... 2x8" stringers fastened to both sides of posts with 4" ledgerlock screws.

#4 6x6" posts with 12" diameter hole & 12"diameter x 8" deep concrete pole pads... 2x8" stringers fastened to both sides of posts with 4" ledgerlock screws.

#5 Post/Rim Foundation. 4x6" posts 8' o.c. with 12" diameter hole & 12" diameter x8" deep pole pads... 2x8 stringers and 2x8" cap. \$40 per linear ft....SITE MUST BE LEVELED OFF PRIOR TO INSTALLING THIS FOUNDATION.

FREE DELIVERY FOR ZONES 1-4

Alpine Structures Sales Book 2025

Page 7