



4285 West 1385 South  
 Salt Lake City, Utah 84104  
 Phone: 1.801.521.0360  
 Fax: 1.801.532.7407  
 www.semiservice.com

**QUOTATION**  
**JEM00795**

**CUSTOMER:** Corwin Ford Reno  
**CONTACT:** Andy Ludel  
**ADDRESS:** 3600 Kietzke Ln  
 Reno NV 8950  
**MOBILE:** 775-544-1346  
**WORK:** 775-329-8800  
**FAX:**  
**EMAIL:** aludel@corwin.com

**QUOTE NUMBER:** JEM00795  
**QUOTE DATE:** 9/1/2022  
**QUOTE VALID UNTIL:** 10/1/2022  
**SALESPERSON:** Jason Madsen  
**MOBILE:** 801-514-0118  
**WORK:** 385-234-6257  
**FAX:**  
**EMAIL:** jmadsen@semiservice.com

<b>YEAR:</b> 2023	<b>MAKE:</b> FORD	<b>MODEL:</b> F-450	<b>SINGLE/DUAL:</b> DRW
<b>CAB TO AXLE:</b> 60.0	<b>CAB TO TANDEM:</b>	<b>CAB TYPE:</b> CREW	<b>VIN:</b>

QTY	DESCRIPTION	PRICE EACH	AMOUNT
1	<b>SERVICE BODY</b>	<b>\$26,874.13</b>	<b>\$26,874.13</b>
1	9' Reading RS300 Reading Service Body, Standard Height 40", Part # RETRSS108DRW2FA621301 MODEL# RETRSS108D  CHASSIS APPLICATION: Dual Wheel 60" Cab to axle STANDARD SHELVING: Standard Shelf and divider equipment TAILGATE: Slam-Action Tailgate, Removable Stainless Steel Tailgate Knee Brace. FLIP LIDS: None FLOOR: Galvannealed pressed diamond floor plate and tailgate inner panel DOORS: Double paneled door construction heavy duty 18 gauge steel outer skin, A60 Coating Weight Steel Spring Loaded Door Holders On Vertical Doors DOOR SEALS: 1st - 5/8" Wide Automotive Quality Bubble Type Seal LOCKS: Stainless Steel Rotary Action For Maximum Corrosion Protection UNDERCOATING: Fully primed and undercoated LIGHT KIT: Rubber isolated LED lights include clearance, stop, tail and turn lights. Standard on all models FF: Fuel fill cut-out located roadside front of wheelhouse OVERALL LENGTH-----108" OVERALL WIDTH-----91 1/2" FLOOR WIDTH-----48 1/2" SIDE COMPARTMENT HEIGHT----40" SIDE COMPARTMENT DEPTH----21 1/2" FLOOR HEIGHT-----24" BODY WEIGHT (APPROX)-----1259 lbs.  WARRANTY: Exclusive 6-year guarantee to the original owner (see Reading warranty for details)  PAINT: Factory Paint finish Reading White.  **NOTE: MODELS LISTED ARE FOR CURRENT MODEL YEAR ONLY**		
1	Freight to Reno NV		
1	Factory installed street side compartment overlay to support future install of compressor/welder not to exceed 800lb		



4285 West 1385 South  
 Salt Lake City, Utah 84104  
 Phone: 1.801.521.0360  
 Fax: 1.801.532.7407  
 www.semiservice.com

**QUOTATION**  
**JEM00795**

QTY	DESCRIPTION	PRICE EACH	AMOUNT
1	Reading Adapter Harness, Ford Chassis to Reading body, Part # RET14302338		
1	Reading Dome lights: (6) Six Dome Lights With Switch on Light in Each Compartment. (Factory Installed). For Reading Bodies, Model #'s 78, 98, 108, SW & DW, HD-108 & HD-120. Part # RETDL-6		
1	Reading Straight bumper, Pooched Quick Mount, galvanized steel, DW 91.5" wide, Polyurea spray lined in Black Part # RETBPSNDRP2FA011257		
1	Mounting Kit Mounting Kit Ford 108/132 Body Ford 350-550 CC MY2017/Newer. Part# RETYKDK090002.		
1	Reading SP-4 Front 4-Bolt Spring Mounting Kit (Supplied with Aluminum Service Body, optional on Steel Service Body) Approx. Part # RET10012603		
1	Five-drawer units: — One (1) 6" drawer; Three (3) 3" drawers; One (1) 2" drawer		
1	Dual Rear Wheel Mud Flaps 24" X 18". Part # MUD2311715		
1	Lubricate and Adjusts Doors on Service Body. Part # MTALUBE		
1	Labor to Install (OEM Supplied) factory back up camera for cab and chassis truck.  ***Truck must be ordered and equipped with factory wiring to rear of truck***		
1	Buyers Class V Receiver Hitch for Service Bodies. Max Gross Trailer Weight: 20,000 lbs, Max Vehicle Load: 2,000 lbs. Receiver Tube Size: 2 1/2". Part # BUY1801052		
1	7 Way flat light receptacle (REAR) Part # TOWPO-11-893		
1	Auto Crane Model EC-2, 2,000 LBS Lift (Max), Manual, Part# TECAU370870020  <ul style="list-style-type: none"> <li>• 6,500 ft.-lb. capacity</li> <li>• 4' 2" to 7' 1" manual telescopic boom</li> <li>• 325 degree manual rotation with manual brake (Econo-Ton II)</li> <li>• 355 degree electric power rotation (Econo-Ton IIR)</li> <li>• 10 ft. Remote Control Pendant</li> <li>• 25 ft. of 1/4" 4,200 lbs. breaking strength cable</li> <li>• 20 ft. high current battery cable</li> </ul> *** Truck must be equipped with jackleg extending minimum 3' 9" (1.14 m.) from centerline of truck. ***  *** 5,200 GVWR minimum chassis requirement. (Does not include bodies and accessories). ***		
1	Buyers Fabricate Outriggers Using (2) Jack Leg 2.5" Drop. Part # BUY0091340		
1	Reinforce Right Rear Compartment For Crane Install		

<b>Quote Total:</b>	<b>\$26,874.13</b>
<b>Sales Tax:</b>	<b>\$0.00</b>
<b>Total Due:</b>	<b>\$26,874.13</b>



4285 West 1385 South  
Salt Lake City, Utah 84104  
Phone: 1.801.521.0360  
Fax: 1.801.532.7407  
www.semiservice.com

**QUOTATION**  
JEM00795

Signature Required to Process Order

PO Number

Date

QTY	SUGGESTED ITEMS	PRICE EACH	AMOUNT

- ◆ Labor and installation are included in all pricing unless specified.
- ◆ Quoted price does not include any applicable F.E.T., sales taxes, and delivery charges.
- ◆ Quote price does not include any unforeseen obstructions or modifications.
- ◆ Quotation valid until above stated expiration date.
- ◆ Terms are due upon receipt unless prior credit arrangements are made at the time of order.
- ◆ FOB Salt Lake City, Utah 84104
- ◆ 50% down payment required with special order items, NON-REFUNDABLE.
- ◆ We only Accept Cash, Check, Visa and MasterCard.