



**AIRMAN**<sup>®</sup>  
AIR COMPRESSORS

**PDS375DP-6E1**  
375-330 cfm

**AIRMAN air compressors are manufactured to the highest quality**, consistently delivering the industry's best return on investment.

ANA is committed to supplying the finest products with unmatched performance and support, maintaining their value over time.

- 375-330 cfm Free Air Delivery
- Best-in-Class Fuel Efficiency
- Kubota Diesel Engine
- EPA Tier 4F & CARB Compliant



**Alliance North America**

Phone: 562-450-3570

E-mail: [sales@anacorp.com](mailto:sales@anacorp.com)

[www.anacorp.com](http://www.anacorp.com)

**California:** 12311 Industry St. • Garden Grove, CA 92841  
**Texas:** 10440 Brockwood Road • Dallas, Texas 75238  
**South Carolina:** 4220 S. Church St. • Roebuck, SC 29376

© COPYRIGHT 2020, ANA • 020420

AIRMAN is a trademark of HOKUETSU INDUSTRIES CO., LTD.

Features and specifications may change without notice. Please consult ANA for all current information.

## SPECIFICATIONS



# AIRMAN<sup>®</sup>

AIR COMPRESSORS

# PDS375DP-6E1

375-330 cfm

### COMPRESSOR SPECIFICATIONS

Type	Dual Pressure, Oil Cooled, Screw-Type
Free Air Delivery	375 cfm @100 psi; 330 cfm @ 150 psi
Working Pressure	100 psig
Max. Working Pressure	150 psig
Air Outlets	2" x 1; ¾" x 2
Engine Coupling Type	Rubber coupling
Lubrication System Type	Forced lubrication by compressed air
Lubrication System Capacity	10.6 gal.
Oil Cooler Type	Separate side-by-side oil cooler and radiator

### ENGINE SPECIFICATIONS

Model / EPA Emission Level	Kubota V3800 / Tier 4 Final
Engine Type	Water Cooled 4-Cycle, Direct-Injection, Turbocharged Air-To-Air Intercooled, EGR, DOC+DPF, SCR Tier 4F & CARB Compliant
Cylinders	4
Displacement	230 cu.in. (3.769 L)
Fuel Type	Diesel
Output	110.4 HP (82.3 kW)
Low Idle	1300 rpm
High Idle	2400-2700 rpm
Fuel Tank Capacity	47.0 gal.
Oil Capacity	3.4 gal.
DEF Tank Capacity	5.3 gal.
Cooling System Capacity	4.1 gal.
Battery	12V 130F51

### FUEL CONSUMPTION

FULL load	5 gph @100 psi; 5.1 gph @ 150 psi
75% load	3.75 gph @100 psi; 3.825 gph @150 psi
50% load	2.5 gph @100 psi; 2.55 gph @150 psi
Run time @ full load	9.25 hr.

### WEIGHTS AND DIMENSIONS

Dry Weight	3,737 lb.
Weight w/ Towing Frame	3,975 lb.
Operating Weight	4,233 lb.
LxWxH w/o Towing frame	106" x 55" x 60"
LxWxH w/ Towing frame	174" x 57" x 69"

### OPERATING PARAMETERS

Min. Ambient Temperature	5° F
Max. Incline	15°
Sound Level	76 dBA



**Alliance North America**

Phone: 562-450-3570

E-mail: [sales@anacorp.com](mailto:sales@anacorp.com)

[www.anacorp.com](http://www.anacorp.com)

**California:** 12311 Industry St. • Garden Grove, CA 92841

**Texas:** 10440 Brockwood Road • Dallas, Texas 75238

**South Carolina:** 4220 S. Church St. • Roebuck, SC 29376