

Filter Specifications

Order:

(858) 208-0830

sales@kiswater.com

DeepWave Model Number	DW-8	DW-9	DW-10	DW-12HF	DW-12-1.5
Tank Size (inches)	8 x 44	9 x 48	10 x 54	12 x 52	12 x 52
Total Height (inches)	48.5	52.25	58.5	57	57
Outside Diameter (inches)	9	10	11	13	13
Height to In/Out Ports (inches)	47	50.5	57	56.25	54.5
Maximum Flow Rate (GPM)	8	10	12	18	30
Minimum Flow Rate (GPM)	0.2	0.2	0.2	0.2	0.4
Pressure Drop (PSI)	8	8	9	10	8
Maximum Operating Temp. (F)	125	125	125	125	125
Maximum Operating Pressure (PSI)	120	120	120	120	120
Maximum Hardness (GPG)	25	25	25	25	25
Capacity (million gallons)	1.5	2	2.5	3.3	3.6
Capacity (years)*	10	13	15	20	22

*Capacity data based on a family of 5

NOTE:

Maximum flow rate in an average home is 10 GPM.

Middle of inlet and outlet are 3" apart except on DW-12-1.5 which is inline 1.5" female threaded ports (no bypass).

When viewing household hard plumbing: water out (in to filter) is on the left, water in (out of filter) is on the right.