GENERAL SPECIFICATION:

Length (mm)	12555	Chassis Make:	VOLVO
Width (mm)	2500	Chassis Model:	B10BLE
Height (mm)	3180	Body Make:	ANSAIR
Weight unladen Front (kg)	4041	Body Model:	ORANA
Weight unladen Rear (kg)	7560	Seats:	43
Weight laden Front (kg)	6000	Standing:	19
Weight laden Rear (kg)	10000	Total Capacity:	62
Wheelbase (mm)	6405	Total No:	125
Overhang Front (mm)	2680	STA Class:	VL

Placed in Traffic: 1997-1999 Overhang Rear (mm) 3270 Turning Circle Wall/Wall (mm) Fleet Nos.: 3847-3971

Turning Circle Kerb/Kerb (mm) Door Opening Front (mm) 1350 Door Opening Rear (mm) 1150 Step height 1 Front/Rear (mm) 325/325 Step height 2 Front/Rear (mm) N/A Step height 3 Front/Rear (mm) N/A Ceiling height Front/Rear (mm) 2515/1806

325 Floorheight Entry (mm) Floorheight Centre Door (mm) 325

BODY:

Construction Steel Tube Fixed Windows

Saloon Ventilation Airconditioned

BRAKES:

Type Disc front / Retarder

Handbrake Spring

ELECTRICAL:

Bosch X 2 Alternator

Voltage (V) 24

Twin 80 Amp Amps (A) Interior lighting Fluorescent **Destination Equipment** Alcatel

SUSPENSION:

Type Air Bellows 275/70R22.5 Tyre Size

Tyre Press Front (kPa) 760 Tyre Press Rear (kPa) 660 Fitted with Kneeling Yes Fitted with Suspension lift Yes

CAPACITIES (Itr):

Fuel 210 40 **Engine Oil** Gearbox 22 21 Differential Power steering 8 33 Coolant

ENGINE:

DH1DA245 Type

Position Rear horizontal in line

Capacity (Itr) 9.6 No. Cylinders 6 20:1 Compression Ratio





Click here for larger image



Bore (mm) 120.65 Stroke (mm) 140.00 Max kW (DIN) at (RPM) 180/2000 Max Torque (Nm) at (RPM) 1050/1400 Max Gov. speed (RPM) 2000 Fuel Pump & Injectors Bosch Speed Limiter Yes Electronic Diesel Control Yes

For more site information: Email <u>info@tripfinder.com.au</u> or visit our site builders: <u>www.tripfinder.com.au</u>

TRANSMISSION:

Туре	ZF-5HP500
1 st Ratio	3.43:1
2nd Ratio	2.01:1
3rd Ratio	1.42:1
4th Ratio	1.00:1
5th Ratio	0.83:1
Reverse Ratio	4.84:1
Rear Axle Type	RAE\85
Final Drive Ratio	4.87:1
Max speed with speed lim	80 KPH