

# SIA-025

Signature Integrated Amplifier



Signature Series | *EXTREME*

v i t u s **V A** a u d i o

[vitusaudio.com](http://vitusaudio.com)

# SIA-025

## Signature Integrated Amplifier

### The SIA-025 was created after many customer requests for a Signature Series Integrated Amplifier

The SIA-025 has been designed to accommodate many of our customers requests, for a real integrated amplifier in our high performance Signature Series.

But as usual, our design team went an extra mile. The result is not only an amplifier with 5 inputs (balanced and unbalanced), a preamplifier output (for biamping purposes) and balanced speaker outputs - it raises our technology to a new level of integration of parts. Integration was a major challenge, but necessary to fit all the parts into the fairly small chassis, which the SIA-025 shares with its siblings - the SS-010 and SS-050.

The output stage of the SIA-025, is taken from the SM-010 monaural amplifiers - sized to fit within one chassis with a balanced input buffer. The main task for this buffer, is to separate the new simplified relay based volume control from the selected source. By putting all our efforts into developing this true balanced integrated class A amplifier, we succeeded in making the new higher level of integration perform to the standards that any customer would expect from our Signature Series.

SIA-025 adds more flexibility in terms of more inputs, the possibility of bi-amping should it be needed and lastly a full bypass function for enabling compatibility with external surround processors. Together with our SCD-010, this amplifier will form a simple, cool looking system that delivers an incredible performance.

INPUT	XLR analog	RCA analog
Available	3	2
Sensitivity	0,7 Vrms	1,4 Vrms
Impedance	100K $\Omega$	100K $\Omega$
Slew rate	35V/ $\mu$ s	35V/ $\mu$ s

OUTPUT	Speaker L	Speaker R
Available	1	1
1x Unbalanced sub-out output (RCA)		
Impedance	75 k $\Omega$	75 k $\Omega$
Power WRMS	25W Class A / 150W Class AB	
Frequency response	+800kHz	+800kHz
Signal to noise ratio	>100dB	>100dB
THD + noise	> 0,01%	> 0,01%

POWER CONSUMPTION	
Standby	3WRMS
Class AB	90WRMS

DIMENSIONS	
Hight	130 mm
With	435 mm
Depth	430 mm
Weight	~42 Kg

v i t u s **V A** a u d i o