

# AIRDUO SK - CK



## Range : SK-CK range with 14 models available:

- AIRDUO RSK-RCK: cooling only version
  - AIRDUO ISK-ICK: heat pump version
- SP-CP range with 9 models available:
- AIRDUO RSK-RCP: cooling only version
  - AIRDUO ISK-ICP: heat pump version



## Range of use :

Cooling Capacity: 21 to 135 kW  
Heating Capacity: 22.5 to 144.5 kW

## Use :

AIR-TO-AIR SPLIT SYSTEM units designed for the air conditioning and heating of small premises (town centre stores and high street shops, shopping centre shops, service stations, etc.) and open air shopping centres.

Horizontal or vertical ductable indoor units which can be installed in suspended ceilings or mechanical rooms.

# AIRDUO SK - CK



## Description :

- R410A refrigerant
- 1 or 2 independent refrigerant circuits
- 1 or 2 SCROLL compressors
- High efficiency Air-cooled condenser with U-shaped coils up to model 320, and V-shaped coils for models 360 to 600
- Mixing box for fresh and return air, free cooling management and/or active recovery (range SK-CP) incorporated: High quality indoor air filtration.
- Efficient AVANT controller :
  - Control perfectly suited to your needs with the option for communication with a BMS via a RS 485 output (several communication protocols)
  - Plant Visor PRO 2 supervision software.

