




ULTRASHIELD AR551



SLAT PROFILES



FEATURES & BENEFITS

- Insulation
- Security
- Available for wider spans
- Ideal for garage doors
- Reduced greenhouse emissions
- Protection from the elements
- Light control

TECHNICAL SPECIFICATIONS

Weight (per m ²)	3.4kg
Maximum Curtain Width	4.2m
Maximum Area (m ²)	11.8
Gauge of Aluminium	0.32mm
Profile Slat Height	55mm
Profile Slat Thickness	11mm
Standard Guide Dimensions	77mm
Standard Bottom Bar Dimensions	50mm
Standard Axle	50mm circular

The Ultrashield profile is a double walled cavity with PU foam injected during the roll forming process. This profile is available for use on openings up to 50% larger than our standard domestic profiles while maintaining the same level of strength and insulation qualities.

The Ultrashield is a curved profile which uses a minimal head box size, making it an ideal substitute for garage doors or commercial door applications where room for roll up is limited. Available in multiple colours, the Ultrashield has two profile lines on the convex side with a smooth finish on the concave.

BOX COLOUR OPTIONS



ROLLER SHUTTER COLOUR OPTIONS



White

Cream

Sand

Please note: Colours displayed are a guide only and have been matched as closely as possible. Due to the nature of the printing process, some degree of colour variation may occur. We recommend that you use production line prepared samples for final colour selection or approval.

CONTROL OPTIONS

MANUAL



Strap



Winder

MOTORIZED



ODS with E-Port



E-Trans



SOMFY 240V with Inis Uno



SOMFY 240V with Key Switch



SOMFY 240V RTS with Transmitter



SOMFY 240V with CSI override

BOXING OPTIONS

SQUARE BOXING (SQ45)

Sizes Available

Maximum Overall Height

250mm

3100mm

Please note: Only when using Ozroll's 50mm circular axle.

A large majority of home break ins are accessed through unprotected windows.

Based on insurer statistics

