

## T68 Grade Vacuum Pump Oil

**AirVAXX** T68 Grade Vacuum Pump Oil is a mineral turbine oil specifically formulated for rotary vane vacuum pumps operating in harsh industrial environments.

Fill With  
**AirVAXX**

**T68**  
GRADE  
VACUUM PUMP OIL

Phone: +617 3271 5899  
Website: [www.airgas.com.au](http://www.airgas.com.au)  
Email: [enquiries@airvaxx.com.au](mailto:enquiries@airvaxx.com.au)  
19 Industrial Ave, Wacol QLD 4076  
PO Box 282 Carole Park QLD 4300

CHARACTERISTICS	METHODS	UNITS	<b>AirVAXX T68</b>
Density at 15 °C	ISO 3675	kg/m <sup>3</sup>	884
Viscosity at 40 °C	ISO 3104	mm <sup>2</sup> /s	68
Viscosity at 100 °C	ISO 3104	mm <sup>2</sup> /s	8.7
Viscosity Index	ISO 2909	-	100
Flash Point	ISO 2592	°C	240
Pour Point	ISO 3016	°C	-9

Above characteristics are mean values

### ADVANTAGES

Long drain intervals  
Simplified maintenance

Ageing Protection

High oxidation resistance, antifoam, air and water release performances.

High antiwear properties.

High antirust and anticorrosion performances.

Important hydraulic properties especially hydrolysis stability and filterability

**ORANGE SCENTED OIL AVAILABLE ON REQUEST**

For more information on our services and products contact us:-



**Air & Gas Industries**

Ph: (07) 3271 5899 Fax: (07) 3271 5726

[mail@airgas.com.au](mailto:mail@airgas.com.au)