## THE AQUARIUM PUMP

## FOR FRESHWATER AND SALTWATER AQUARIUMS





93 GPH thru 725 GPH Pump



70 GPH Pump

## **70 GPH PUMP** ITEM# 06503 70 GPH Maximum Flow Rate Maximum Pumping Height 6′ Cord Length 115V, 60Hz Power Includes Slip-Fit Tubing Adapters 1/4" and 1/2" 93 GPH PUMP ITEM# 06507 Maximum Flow Rate 93 GPH Maximum Pumping Height 2.5' Includes Slip-Fit Tubing Adapters 1/4" and 1/2" 120 GPH PUMP ITEM# 06513 Maximum Flow Rate 120 GPH Maximum Pumping Height 3′ 1/4" and 1/2" Includes Slip-Fit Tubing Adapters **200 GPH PUMP** ITEM# 06517 Maximum Flow Rate 200 GPH Maximum Pumping Height 6.5' Includes Slip-Fit Tubing Adapters 1/4" and 1/2"

## **FEATURES**

- For Fresh & Saltwater Aquariums
- New Vertical Flow Control Design Increases Flow Range
- Energy-Efficient Magnetic Drive Technology
- Models 70 thru 200 for Submersible Use Only Models 290 thru 725 for Submersible or In-line Use
- 6' Grounded Power Cord
- Packed 6 Per Master Carton (70 to 200)
- Packed 4 Per Master Carton (290 to 725)
- 2-Year Limited Warranty



290 GPH PUMP	ITEM# 06523
Maximum Flow Rate	290 GPH
Maximum Pumping Height	6.5′
Inlet Size	1/2" MPT
Includes Threaded Tubing Adapters	1/2", 5/8" and 3/4"
400 GPH PUMP	ITEM# 06527
Maximum Flow Rate	400 GPH
Maximum Pumping Height	8.5'
Inlet Size	1/2" MPT
Includes Threaded Tubing Adapters	1/2", 5/8" and 3/4"
530 GPH PUMP	ITEM# 06533
530 GPH PUMP Maximum Flow Rate	<b>ITEM# 06533</b> 530 GPH
Maximum Flow Rate	530 GPH
Maximum Flow Rate Maximum Pumping Height	530 GPH 9'
Maximum Flow Rate Maximum Pumping Height Inlet Size	530 GPH 9' 1/2" MPT
Maximum Flow Rate Maximum Pumping Height Inlet Size Includes Threaded Tubing Adapters	530 GPH 9' 1/2" MPT 1/2", 5/8" and 3/4"
Maximum Flow Rate Maximum Pumping Height Inlet Size Includes Threaded Tubing Adapters 725 GPH PUMP	530 GPH 9' 1/2" MPT 1/2", 5/8" and 3/4" ITEM# 06537
Maximum Flow Rate Maximum Pumping Height Inlet Size Includes Threaded Tubing Adapters 725 GPH PUMP Maximum Flow Rate	530 GPH 9' 1/2" MPT 1/2", 5/8" and 3/4" ITEM# 06537 725 GPH

PUMP	FLOW AT 0'	FLOW AT 2'	FLOW AT 4'	FLOW AT 6'	FLOW AT 8'	SHUTOFF	WATTS	AMPS
MODEL 70	<i>7</i> 0	-	-	-	-	2′	3W	.03A
MODEL 90	93	20	-	-	-	2.5′	6W	.07A
MODEL 120	120	50	-	-	-	3′	6.5W	A80.
MODEL 200	200	140	85	35	-	6.5′	14W	.19A
MODEL 290	290	270	205	50	-	6.5′	17W	.24A
MODEL 400	400	360	285	155	30	8.5′	30W	.45A
MODEL 530	530	500	420	305	135	9′	50W	.68A
MODEL 725	725	690	615	515	420	12′	70W	.50A

Note: 290 through 725 Pumps can be used Submersible or In-line.