

## Garage Doors

### Keeping garage doors operating smoothly

Tighten all door fasteners while the door is in closed position at least once a year. Ensure that you do not over tighten fasteners found on wood doors otherwise you may strip the wood where wood screws are used to fasten stiffener brackets across the width of the door.

Ensure all roller/hinge assembly fasteners are tight. Do not over tighten these fasteners as you may pull the head of the fastener through from the front or outside of the wooden door.

Aluminum doors require a check of fastening assemblies, ensure that you do not over tighten fasteners.

Apply **CarWell Rust Cop** to all rollers, guides, pivot points, large spring across the top of the door and to pulley guide wires that lift the door.

Treat the wires on the pulley assembly while the door is in the up position by spraying **Rust Cop** to the top of the wire on the pulley and then to the sides. Ensure that enough **Rust Cop** is applied to cover the cable so that a tiny amount of excess moves to the bottom of the pulley while in contact with the wire.

NOTE: Do not use **Rust Cop** to treat the screw assembly that the motor assembles onto. Use manufacturers recommended grease for lubricant.

This tune up to your garage door should be performed at least once a year which will increase the life of your garage door system for years.

### Keeping garage doors looking new

Metal Doors—Use **Bullfrog Fast Wax** to refresh the metal and protect the finish. **Bullfrog Fast Wax** is a high quality Liquid Carnauba Wax with UV blocker and VpCI corrosion inhibitors to protect all metal surfaces from corrosion and oxidation.

#### Note:

Go to Products Link on our site for details on Rust Cop and Bullfrog Fast Wax 98198.

Go to Buy Now Link on our site for retail locations.

Go to Contact Link on our site for industrial sales and further questions.



### Solutions for Rust and Corrosion