

Model	B2B3BT	B2B4BT	B2B3BO	B2B4BO	B2B3ST	B2B4ST	B2B3SO	B2B4SO
Weight	125LBS	130LBS	120LBS	125LBS	125LBS	125LBS	120LBS	120LBS
Height	61"							
Length	44"							
Width	26"							
Number of Tankless	3	4	3	4	3	4	3	4
Hot/Cold Manifold Material	Rigid Copper (L)							
Hot Water Manifold Diameter	2"							
Hot Manifold Connection Type	2" PIPE							
Hot Branch Diameter	3/4"							
Hot Branch Connection Type	3/4" MIP							
Cold Water Manifold Diameter	2"							
Cold Manifold Connection Type	2" PIPE							
Cold Branch Diameter	3/4"							
Cold Branch Connection Type	3/4" MIP							
Gas Manifold Diameter	1-1/2"							
Gas Manifold Connection Type	1-1/2" MIP							
Gas Branch Diameter	3/4"							
Gas Branch Connection Type	3/4" MIP							
Gas Line Material	Iron							
Condensate Manifold Diameter	3/4"							
Condensate Branch Diameter	1/2"							
Condensate Branch Connection Type	1/2" FIP							
Condensate Material Type	PVC							
Electrical Requirements								
Prewired Electrical Assembly	YES							
Voltage	AC 120V							
Max Current (Amperes)	15							
Outdoor	YES							
Horizontal Support	1-5/8" 12 Gauge Strut Channel							
Vertical Support	13/16" Back to Back 14 Gauge Strut Channel							
Frame Material	Galvanized Steel							
Include Condensate Treatment Kit	Yes	Yes	NO	NO	YES	YES	NO	NO
Hot/Cold Connections Same Side (SAME) or Opposite sides (OPPOSITE)	SAME	SAME	SAME	SAME	OPPOSITE	OPPOSITE	OPPOSITE	OPPOSITE