



KEY FEATURES

- Lightweight Systems for Ceiling Installations
- Highest Sound Absorption Efficiency & Performance
- Wide Selection of Standard Colors, Prints, Textures & Finishes
- Decorative Fabric Facings from Guilford of Maine as well as Designer Selections from Maharam, Carnegie, DesignTex, Knoll, & More!
- *fresco* ™ Finishes Optionally Available in Standard White or Custom
 Color Match using Sherwin Williams (See *fresco™ Wall & Ceiling Products*)
- Durable and Resistant to Damage
- Standard and Custom Sizes & Shapes Available
- Easy to Install with Fully-Concealed Mounting Hardware Included
- LEED Credit Eligibility With Installation of These Products
- Indoor Air Quality (IAQ) & Low VOC Meets GREENGUARD Children & Schools Certification and California Title 24

* Standard materials have dimensional and weight variations. Calculations are approximate and represent material averages to the best of our knowledge.

©Copyright 2019, AVL Systems, Inc. - The use or reproduction of any trademarks/information/terminology listed on this document is prohibited without the expressed written consent of AVL Systems, Inc. AVL Systems' interature, presentations and published data are correct to the best of our knowledge at time of publication. AVL Systems inc. reserves the right to change or amend any of the products or the information presented or published without liability or notice.

TECHNICAL FEATURES

- Core: (2) Layers of 6-7 PCF Fiberglass Bonded Together
- Overall Thickness: 1", 1½", 2", 4"
- Sizes: Any Size Up to 48" x 120"
- Special Sizes & Shapes: Available Upon Request
- **Edge Profile:** Square, Bevel, Radius, Miter, Others Available Upon Request
- Fabric/Facing: Decorative Fabric Facings, Designer Selection, *fresco* ™or C.O.M.
 Standard: Guilford FR701-2100 Series / Premium: Guilford Anchorage 2335
 (See *fresco™ Wall & Ceiling Products* for Decorative Coated Finish Information)
- Fasteners: Eyelets or D-Rings
- Dimensional Tolerance: +/- 1/16" (.0625")
- Fire Performance: Class 1/A, UL 723 / ASTM E84

ACOUSTICAL DATA

Acoustical Performance - Absorption Coefficients							
Frequency (Hz)		125	250	500	1K	2К	4К
ATBF 1.0	1" Baffle	0.29	0.78	1.45	1.67	1.73	1.80
ATBF 1.5	1½" Baffle	0.49	0.89	1.51	1.78	1.79	1.98
ATBF 2.0	2" Baffle	0.57	1.16	1.54	1.81	1.88	1.96
ATBF 4.0	4" Baffle	0.82	1.32	1.59	1.92	1.99	1.98

LEED CREDITS

- Schools EQ Prerequisite 3 & Credit 9
- MR 4.1 & 4.2
- MR 5.1 & 5.2

WARRANTY

AVL Systems' *Limited Warranty* extends for ONE FULL YEAR from the original date of shipment.

ACOUSTECHTM CEILING BAFFLES

IEQ 4.1 & 4.2

58%

Innovation in Design (ID)

TOTAL RECYCLED CONTENT* 31% Pre-Consumer Recycled

27% Post-Consumer Recycled