

<b>Application</b>	Ceilings and walls.
<b>Shapes</b>	Panels can be pre-curved and custom engineered to attain a wide range of unique shapes. Minimum curving radius for outside is 16" (400mm) and for inside it is 24" (600mm).
<b>Sizes</b>	Recommended maximum panel size is 48" in width and 60" in length for Ceilencio® suspension system. Larger sizes are possible with other ceiling and wall mounting systems.
<b>Thickness</b>	<p>Quadrillo core is available in three thicknesses:</p> <ul style="list-style-type: none"> <li>• QPP-19 is ¾" (19mm)</li> <li>• QPP-25 is 1" (25mm)</li> <li>• QPP-50 is 2" (50mm)</li> </ul>
<b>Grooving</b>	<ul style="list-style-type: none"> <li>• 3/16" (5mm)</li> <li>• 5/16" (8mm)</li> <li>• 3/8" (10mm)</li> <li>• 5/8" (15mm)</li> </ul> <p>Create your own custom patterns by specifying profile spacing. Solid portions must be multiples of 5mm.</p>
<b>Weight</b>	Weight depends on panel thickness and frame. Generally a QPP-25 panel having an overall thickness of 1-3/8" (35mm) weighs an average of 3.5 lbs. per sq. ft. (17.1 kg/m <sup>2</sup> ), and a QPP-50 panel with thickness of 2-3/8" (60mm) weighs an average of 5.5 lbs. per sq. ft. (26.85 kg/m <sup>2</sup> ). Solid wood border frames can add significantly to these weights.
<b>Wood Veneers</b>	Select one of our nine standard wood veneers or specify your own. Decoustics has the capability to source a variety of different veneers as well as custom stain wood to match different wood species. Quadrillo veneer lay-up is quarter sliced and as slip matched as a standard. Other veneer cuts and lay up options are available by request.
<b>Color/Stain</b>	Custom lacquer toning, tinting and sheen to match other wood finishes. Custom color matching to any paint chip. Glossy, matte, metallic options also available.
<b>Edges</b>	Variety of Design Return options is available.
<b>Back</b>	Perforated hardboard.