

TC-W3 Two-Cycle Engine Oil

- Specifically Designed for Severe TC-W3 Applications
- Widely Adopted for Universal Two-Cycle Engine Usage
- Recommended for Both Mixing With Fuel & Use As An Injection Oil
- Reduces Piston Deposits
- Prevents Ring Sticking
- Increases Powerhead Life
- Reduces Plug Fouling
- Unsurpassed Lubricity & Protection from Scuffing & Scoring
- Minimum Smoking

Today's two-cycle engines are working harder than ever before. They run hot and they run hard and they test the very limits of lubrication technology.

SWEPCO 313 TC-W3 Oil is a new generation heavy-duty two cycle engine oil specially formulated to exceed the performance demands of today's high-horsepower two-cycle air and water cooled engines. It can be mixed with fuel or used as an injection oil. It's superior anti-wear performance insures protection of hardworking two-cycle engines in a wide range of applications in forestry, landscaping, grounds maintenance and other industries.



Whether its hardworking chain saws in forestry applications or a wide variety of other demanding two-cycle engine applications, SWEPCO 313 provides unexcelled protection and cleanliness.

In addition, SWEPCO 313 is licensed by the National Marine Manufacturers Association (NMMA) and exceeds major water-cooled two-stroke engine manufacturers' test requirements for the boating industry.

SWEPCO 313 TC-W3 is designed for use in engines featuring more



Marinas



Outboard Motors



Landscaping



Forestry

advanced technology and extends the previously proven TC-W/TC-W2 technology and beyond. It provides an extra margin of lubrication safety which can result in significantly less maintenance and costly downtime, while significantly increasing powerhead life, even those exposed to hostile salt water marine environments and "dirty gasoline".

Prolongs Engine Life

SWEPCO 313 TC-W3 oil helps eliminate many of the lubrication problems encountered with today's high performance two-cycle engines. SWEPCO's exclusive formulation means the lubricant does not contribute to spark plug fouling, which is one of the major causes of loss of power, hesitation, high-speed stumbling, missing and pre-ignition. This feature also helps reduce sticky valves, rings and premature engine failures caused by harmful metal deposits. A heavy-duty anti-wear additive provides superior protection against wear, scuffing, scoring and piston seizure.

Clean & Hard Working

SWEPCO 313 is a "quick mix" lubricant which disperses quickly and evenly throughout the fuel to promote both uniform lubrication and cleaner, more complete burning with less smoke. Whether mixed or injected, its ashless/high detergency formula helps keep the engine free from deposits which can cause loss of

horsepower and performance. Its outstanding detergency, anti-corrosion and anti-oxidation characteristics not only help prevent formation of power-robbing deposits such as sludge, gum and varnish, but help clean out those already present. Special anti-rust and corrosion additives provide excellent protection even during extended storage periods. It exceeds the most rigorous OEM specifications and industry requirements for water and air cooled two-cycle engines, including bench tests that evaluate fuel/oil miscibility, rust prevention, fluidity, filterability, lubricity, preignition and detergency.

Physical Properties

Density @ 60°F, Lbs / Gal	7.2
Density @ 60°F, Kg / L	0.86
Viscosity, SUS @ 100°F	160
Viscosity, SUS @ 210° F	48
Viscosity, cSt @ 40°C	33
Viscosity, cSt @ 100°C	6.35
Pour Point, °F (°C)	-40 (-40)
Flash Point, COC, °F (°C)	130 (54)
Color	Blue
TBN	8.24

Chemical Characteristics

Sulfated Ash, % Wgt	<0.001
Nitrogen, % Wgt	0.50

Performance Properties

OMC 40 HP, Average Piston Deposits	Pass
OMC 40 HP, Average 2nd Ring Sticking	Pass
OMC 70 HP, Average Piston Deposits	Pass
OMC 70 HP, Average 2nd Ring Sticking	Pass
Lubricity, Torque @ 300	Pass
Lubricity, Torque @ 325	Pass
Lubricity, Torque @ 350	Pass
Preignition	Pass



A Product of SPX Technology™.

... the cutting edge performance SWEPCO
Customers have come to expect.



Southwestern Petroleum Corporation

Fort Worth, Texas • Phone: (800)359-5823 or (817)332-2336 • Fax: (800)736-5823 • Web: www.swepcolube.com
N.V. Southwestern Petroleum Europe S.A. • Southwestern Petroleum Canada Ltd.