


# CR662RM RoadMix Material Transfer Vehicle and Paver



## Tractor

- Smartrac™ self-tensioning track system
- Wide stance improves maneuverability
- Crawler-mounted Three-Point suspension
- Oscillating bogie wheel assemblies
- Independent hydrostatic drive for each track
- Replaceable, 18 in (457 mm) wide rubber track
- Patented Frame Raise System
- Oscillating push rollers or truck hitch
- Power tilt hood with integral radiator
- Fume recovery system mitigates fumes
- Operator's umbrella
- Back-up alarm

## Conveyors

- Hydraulically adjustable discharge height
- Short delivery conveyor
- Long 55° swiveling conveyor for offset paving
- Hydraulically operated conveyor chain
- Rebuildable crawler-tractor style conveyor chains
- Bolt-on conveyor flights

## Feed System

- 16.7 ton (15 t) receiving hopper
- Reinforced, sealed, tilting hopper wings with beveled corners
- Twin counter-rotating Remix augers
- Independently controlled right & left feed systems
- System interlocks stop feed when paver stops

## Controls

- Operator swing console with spring loaded center lock and variable position cam lock
- Full instrumentation gauges
- De-tracking warning light
- Electric-over-hydraulic propel control steering wheel with dial-in working speed
- Lockout/tagout capable E-stop and master electrical switch

## Hydraulic System

- Engine-mounted, enclosed, Poly Chain® belt pump drive
- Variable-displacement pumps for tractor drives, right and left feed systems and auxiliary circuits
- Centralized filter locations
- Remote control solenoids with function-check LED
- Front gearbox Remix auger drive

## Optional Equipment

- Stretch 20® screed with oil or electric heat
- 30 ft (9144 mm) hose reel for spray-down
- Additional umbrella
- 500 hour filter kit

## Material Transfer Vehicle

MTV width	10 ft 8 in (3.25 m)
Operating speed	up to 225 ft/min (68.6 m/min)
Travel speed	up to 7.0 mph (11.3 km/hr)
Brakes	multiple disc parking

## Weight

Tractor	39,400 lbs (17,872 kg)
with conveyor assembly	50,800 lbs (23,042 kg)
with optional Stretch 20	48,300 lbs (21,910 kg)

## Conveyor

Throughput	up to 600 TPH (544 t/hr)
Swivel left/right of center	55°
Discharge height (min)	73.2 in (1859 mm)
Discharge height (max)	115.8 in (2941 mm)
Conveyor width	30 in (762 mm)

## Engine

Make/Model	Cummins QSB6.7
Type	Tier 3 turbocharged diesel
Horsepower	260 hp (194 kW) @ 2200 rpm
Electrical	105 amp, 12 vdc

## Capacities

Diesel fuel	82 gal (310 L)
Hydraulic oil	75 gal (284 L)
Cooling system	6.5 gal (25 L)

## Hopper

Length & width	8 ft 2 in x 10 ft 4 in (2489 x 3150 mm)
Volume	267 ft³ (7.56 m³)
Capacity	16.7 tons (15 tonnes)
Feed tunnel width (each)	30 in (762 mm)
Remix augers (diameter)	12 in (305 mm)
Auger thickness	5/8 in (16 mm)
Trough liner thickness	3/8 in (9.5 mm)



**TEREX**  
Roadbuilding

Terex | Cedarapids • 1-888-TEREXRB • www.terexrb.com