

SUBMITTAL DATA SHEET

Model: Camila SPHP-07

Air Handler Heat Pump System	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



SPECIFICATION		
Compressor Type		GMCC
Compressor Model		KSK75D35UEZD3
Refrigerant		R32
Refrigerant Charge(oz)		13
Indoor Air Flow (CFM)		235
Noise level		48/45/42
Dimension (W×H×D)	mm	935*543*198
	inch	36.81*21.38*7.8
Package (W×H×D)	mm	1130*612*305
	inch	44.49*24.09*12
Net/Gross Weight	lbs	77/85

EFFICIENCY			
Cooling		Heating	
SEER2	13.83	HSPF2	7.77
EER2	9.15	COP	2.68

PERFORMANCE of Cooling	
Cooling (Btu/hr)	
Rated Capacity	7080
Maximum Capacity	8000
Standard Operating Range(°F)	63~115
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

Heating (Btu/hr)	
Rated Capacity	7120
Maximum Capacity	8100
1. @ 47°F Rated	7120
1. @ 17°F Rated	4328
2. @ 5°F Rated: Capacity	
Standard Operating Range(°F)	17~75
Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
1. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
2. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

ELECTRICAL	
Power Supply (V/Hz)	115V,60Hz,1Ph
MCA	6.1
MAX.FUSE	10
System Power Input @ Cooling (W)	846
System Power Input @ Heating (W)	704

Optional Heater 1 KW (A)	8.63
Optional Heater .6 KW (A)	5.22

Max Fuse with 1 KW	20
Max Fuse with .6 KW	15
Optional Heater 1 KW Capacity (Btu/hr)	3412
Optional Heater .6 KW Capacity (Btu/hr)	2047

