

NYLON FRAME FIXING ANCHORS

#PREMIUM **

ANF-CR - ANCHOR BODY POLYAMIDE PA6 WITH COUNTERSUNK STAINLESS STEEL A2 SCREW **



FEATURES

PROFILED INTERNAL GEOMETRY,
DESIGNED TO FIT BOTH HEXAGONAL FLANGE AND COUNTERSUNK HEAD.
EQUAL EMBEDDED DEPTH FOR ALL BASE MATERIALS, 70MM RESULTING IN HIGHER LOADING.
MULTI AXIS EXPANSION
THROUGH FIXING

SUITABLE BASE MATERIAL

CONCRETE
AERATED CONCRETE
HARD NATURAL STONE
SOLID BRICK
HOLLOW BRICK
SANDLIME BRICK


MATERIAL

ANCHOR BODY MADE FROM HIGH QUALITY POLYAMIDE PA6.
SCREW MADE OF GALVANIZED STEEL, STAINLESS STEEL A2/A4

APPLICATIONS

CLADDING / FAÇADE INSTALLATION
FIXING METAL OR WOODEN SUB-CONSTRUCTION
DOOR & WINDOW FRAMES

CODE	ART NO.	PLUG Φ	PLUG LENGTH	SCREW DIA X LENGTH	SPANNER SIZE	DRILL HOLE Φ	EMBEDDED DEPTH MIN.	MAX. FASTENABLE THICKNESS MM	SAFE PERMISSIBLE LOAD KN SOLID BRICK >Mz12 TENSION	SAFE PERMISSIBLE LOAD KN CONCRETE >C12/15 TENSION
ANF-CR-08080	8463210	8	80	6x85	T30	8	60	20	0.6	1.3
ANF-CR-08100	8463211	8	100	6x105	T30	8	60	40	0.6	1.3
ANF-CR-08120	8463212	8	120	6x125	T30	8	60	60	0.6	1.3
ANF-CR-08140	8463213	8	140	6x145	T30	8	60	80	0.6	1.3
ANF-CR-08160	8463214	8	160	6x165	T30	8	60	100	0.6	1.3
ANF-CR-10080	8463215	10	80	7x89	T40	10	70	10	0.8	1.5
ANF-CR-10100	8463216	10	100	7x109	T40	10	70	30	0.8	1.5
ANF-CR-10120	8463217	10	120	7x129	T40	10	70	50	0.8	1.5
ANF-CR-10140	8463218	10	140	7x149	T40	10	70	70	0.8	1.5



NOTE:

*ALL LOAD TOLERANCES CAN BE ACHIEVED IN ACCORDANCE WITH THE SPECIFIED DIMENSIONS MENTIONED ABOVE.
*ANY MODIFICATIONS TO THE PRODUCT PORTFOLIO CAN BE IMPLEMENTED WITHOUT PRIOR NOTIFICATION TO THE STAKEHOLDERS.
*SPECIAL LENGTHS CAN BE PROVIDED UPON REQUEST, SUBJECT TO A MINIMUM ORDER QUANTITY REQUIREMENT.
*KN= KILONEWTON (1KN = 100KGS)