

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Date of issue: 15/01/2020 Revision date: 15/01/2020 Version: 1.00

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

: Ceramic Pro Bravo

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture

: Consumer use : Industrial use Automotive Care Products. Surface treatment COATING SOLUTION

### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

### Supplier

Ceramic Pro Car GmbH Bültenweg 42 38106 Braunschweig - Germany T 0531/87897810 - F 0531/87897812 <u>kontakt@ceramic-pro.de</u> - <u>www.ceramicpro-car.de</u>

#### 1.4. Emergency telephone number

Emergency number

: National Health Service (NHS) 24 hour national number consumer England and Scotland: 111 Wales: 0845 46 47 Northern Ireland: call your local General Practitioner

Email competent person

sds@kft.de

Call 999 if there is a life-threatening incident.

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 Full text of H statements : see section 16

### Adverse physicochemical, human health and environmental effects May cause drowsiness or dizziness.

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (CLP) :

Signal word (CLP) Hazardous ingredients Hazard statements (CLP)



- : 2-methoxy-1-methylethyl acetate
- : H336 May cause drowsiness or dizziness.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Precautionary statements (CLP)	<ul> <li>P101 - If medical advice is needed, have product container or label at hand.</li> <li>P102 - Keep out of reach of children.</li> <li>P261 - Avoid breathing mist, vapours, spray.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P405 - Store locked up.</li> <li>P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</li> </ul>
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable
2.3. Other hazards	

PBT: not relevant - no registration required vPvB: not relevant - no registration required

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier		Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methoxy-1-methylethyl acetate	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7	>=25 - <50	Flam. Liq. 3, H226 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and eff	fects, both acute and delayed
Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
4.3. Indication of any immediate media	cal attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measures	8
5.1. Extinguishing media	
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide.
5.3. Advice for firefighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel Emergency procedures	: Ventilate spillage area. Avoid breathing mist, vapours, spray.
6.1.2. For emergency responders Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
Other information	: Disposal must be done according to official regulations.

### 6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing mist, vapours, spray.	
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions	: Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.	
Information about storage in one common storage facility	: Keep away from food, drink and animal feeding stuffs.	

### 7.3. Specific end use(s)

No additional information available

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

2-methoxy-1-methylethyl acetate (108-65-6) EU - Occupational Exposure Limits	
IOELV TWA (mg/m³)	275 mg/m³
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m <sup>3</sup> )	550 mg/m³
IOELV STEL (ppm)	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (mg/m³)	274 mg/m³
WEL TWA (ppm)	50 ppm
WEL STEL (mg/m³)	548 mg/m <sup>3</sup>
WEL STEL (ppm)	100 ppm

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

2-methoxy-1-methylethyl acetate (108-65-6)			
Remark (WEL)		Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference		EH40/2005 (Third edition, 2018). HSE	
2-methoxy-1-methylethyl acetate (108	8-65-6)		
DNEL/DMEL (Workers)			
Acute - local effects, inhalation	550 i	ng/m³	
Long-term - systemic effects, dermal	796 ו	ng/kg bodyweight/day	
Long-term - systemic effects, inhalation	275 i	ng/m³	
DNEL/DMEL (General population)	·		
Acute - systemic effects, oral	500 i	ng/kg bodyweight/day	
Long-term - systemic effects,oral	36 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	33 mg/m <sup>3</sup>		
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day		
Long-term - local effects, inhalation	33 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	0.63	5 mg/l	
PNEC aqua (marine water)	0.064	4 mg/l	
PNEC aqua (intermittent, freshwater)	6.35 mg/l		
PNEC (Sediment)	·		
PNEC sediment (freshwater)	3.29 mg/kg dwt		
PNEC sediment (marine water)	0.329	0.329 mg/kg dwt	
PNEC (Soil)			
PNEC soil	bil 0.29 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	100 ו	ng/l	

### 8.2. Exposure controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

### Hand protection:

In case of repeated or prolonged contact wear gloves. Nitrile rubber. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

### Eye protection:

Use splash goggles when eye contact due to splashing is possible. EN 166

### Skin and body protection:

Wear suitable protective clothing. EN 340. EN 13034

### **Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment. EN 143. A-P2. Breathing apparatus with filter. Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust

### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product. The above mentioned instructions regarding the protective equipment refer to the industrial use of larger quantities.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: yellowish.
Odour	: No data available
Odour threshold	: No data available
рН	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 62 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.9 - 0.95 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: < 5 mPa·s
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing.
Explosive limits	: No data available

# 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

High temperature.

#### 10.5. Incompatible materials

No additional information available.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
ffects		
: Not classified (Based on available data, the classification criteria are not met)		
: Not classified (Based on available data, the classification criteria are not met)		
: Not classified (Based on available data, the classification criteria are not met)		
: Not classified (Based on available data, the classification criteria are not met)		
: Not classified (Based on available data, the classification criteria are not met)		

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

# 12.2. Persistence and degradability

2-methoxy-1-methylethyl acetate (108-65-6)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90 - 99 % (28 d; (OECD 301F method))

# 12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate (108-65-6)	
Log Pow	1.2 (20 °C; pH 6.8; (OECD 117 method))
Bioaccumulative potential	Bioaccumulation unlikely.

### 12.4. Mobility in soil

2-methoxy-1-methylethyl acetate (108-65-6)	
Surface tension	29.4 mN/m (20 °C)

### 12.5. Results of PBT and vPvB assessment

Ceramic Pro Bravo	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	
Component	
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Disposal must be done according to official regulations. European waste catalogue. Do not discharge into drains or the environment. Do not dispose of with domestic waste.	
Product/Packaging disposal recommendations	: Recycle or dispose of in compliance with current legislation.	
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.	

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number		•	•	
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping	g name	•	•	•
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard c	lass(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards	•	•	•
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information	n available	•	•	•

### 14.6. Special precautions for user

Overland transport Not applicable Transport by sea Not applicable Air transport Not applicable Inland waterway transport Not applicable Rail transport Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
Reference code	Applicable on
3(a)	2-methoxy-1-methylethyl acetate
3(b)	Ceramic Pro Bravo ; 2-methoxy-1-methylethyl acetate
40.	2-methoxy-1-methylethyl acetate
Contains no subst	ance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
Data sources	: ECHA (European Chemicals Agency). Information provided by the manufacturer.
Department issuing data specification sheet:	: KFT Chemieservice GmbH Im Leuschnerpark. 3 64347 Griesheim Germany
	Phone: +49 6155-8981-400 Fax: +49 6155 8981-500 Safety Data Sheet Service: +49 6155 8981-522
Contact person	: Dr. Barbara Ridder
Full text of H- and EUH-state	ments:
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

H226	Flammable liquid and vapour.	
H336	May cause drowsiness or dizziness.	
Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Classification and procedure used to	derive the clas	sification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

KFT SDS EU 00

H226

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.