

Catalog

80d

Item number:


24157

Description:

3 Ply 600 3/8in x 1/8in

International Designation:

N/A



Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% Tension	24.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	20.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	18.00 in
Minimum Pulley Diameter- Tail	18.00 in

Construction:

Compound Top Cover	Black SBR
Color	Black
Top Cover Thickness (in)	(9.53 mm) 3/8 in
Top Cover Description	Smooth
Compound Bottom Cover	Black SBR
Bottom Cover Thickness (in)	(3.18 mm) 1/8 in
Bottom Cover Description	Smooth
Number of Plies	3
Overall Gauge (in)	(18.03 mm) 45/64 in
Unit Weight- lb/PIW	0.3400 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black SBR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Splice Instructions:

Splice Step Size	16.00 in
Splice Process	Step Hot

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	BR-10/R6
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Belt Strength:

Tension Rating (PIW)	600 PIW
----------------------	---------

Special Characteristics:

This belt offers high strength and impact resistance, coupled with abrasion resistance and long flex life. Used primarily on high-tension conveyors with long centers or in abusive situations.