



SEE IT IN ACTION



TGS

Standard Features

- Enclosed 12-Volt Electric High-Torque Spinner Motor
- Variable Speed Control
- Adjustable Feed Gate
- Poly Adjustable Material Deflector
- 12" Diameter Urethane Spinner**
- Low-Profile Poly Hopper Design
- Choose Your Attachment System*
- Solid Poly Hopper Cover
- Stabilizer Arms and Tie-Down Straps
- Top Screen With Bag Splitter
- Swing-Away Spinner Assembly***
- Feed Paddle***

Optional Accessories

- Category 1 or 2, 3-Point Hitch*
- TGS Vibrator Kit*
- RT3 Attachment System*
- Material Saver System** (Standard on TGS 300.)
- Hitch Reducer 2½" to 2"

Product Specs

TGS 300*

Auger

3 cu.ft. | 200 lbs
Hopper Capacity Limit†††

22"H x 29"W x 15"D
Hopper Dimensions

4'-30'
Spreading Width

70 lbs plus mount
Spreader Weight

TGS 600*

Auger

6 cu.ft. | 400 lbs
Hopper Capacity Limit†††

26"H x 38"W x 21"D
Hopper Dimensions

4'-30'
Spreading Width

101 lbs plus mount
Spreader Weight

TGS 800**

Paddle Wheel

8 cu.ft. | 780 lbs
Hopper Capacity Limit†††

48"H x 36"W x 21"D
Hopper Dimensions

4'-30'
Spreading Width

220 lbs plus mount
Spreader Weight

TGS 1100*

Auger

11 cu.ft. | 800 lbs
Hopper Capacity Limit†††

34"H x 44"W x 24"D
Hopper Dimensions

4'-30'
Spreading Width

152 lbs plus mount
Spreader Weight

*Excludes TGS 300. **Excludes TGS 800. ***Available only on TGS 800. †Designed to spread dry, free-flowing material (i.e., salt, deicers, etc.). ††Designed to spread sand, salt or a combination of both. See Spreader Material Guide on pages 60 and 61 for more details on material spreading options. †††Capacity weight maximum.