

MODERNDAY[®]

CENTRAL VACUUM

Unique Applications Covered

Central vacuum needs beyond the typical residential application can look to Modern Day to meet the challenge. The models within this line address the need for high waterlift, high CFM, and long life motor options which include metal motors as large as 8.4" diameter.

Built to Last

Designed and assembled in the USA, Modern Day is built with 18 and 20 gauge steel, powder-coated inside and out, and features the highest quality electronics. Modern Day is backed with a ten-year warranty for long term, trouble-free operation.

Built to Clean

Modern Day utilizes the Tru-Seal[®] Microfiltration System featuring a 5-ply, closed bag microfilter that holds 8 gallons of debris and effectively removes particles as small as .3 microns from the air stream without hindering vacuum performance.



Five Models Available
See Reverse for Details

Features

- 10 Year Transferable Warranty
Lifetime on Manufacturing
- True 8 Gallon Capacity
- Filters to .3 Microns
5-Layer Microfiltration
- Ventable Exhaust
- Dual Debris Intake
- Utility Valve Hose Connection
- Two-Stud Bracket
Easy to Hang & Remove
- All 18 & 20 Gauge Steel
- Powder Coated



Designed & Assembled in USA
www.builtinvacuum.com
1-800-525-2055

MODERNDAY

CENTRAL VACUUM



Modern Day Models MD Part #	M465h M1158NH	M575h M1155NH	M615h M115CAH	M715h M1185LH	M965h M1258NH
Motor	Single 3-stg. 5.7" by-pass	Single 2-stg. 5.7" by-pass	Single 3-stg. 5.7" by-pass	Single 2-stg. 8.4" by-pass	Dual 3-stg. 5.7" by-pass
Max Air Watts	465	574	615	718	963
Max Amps	13.1	15.2	16.5	14.9	26.9
Waterlift	136"	130"	162"	150"	137"
CFM @ 2" Opening	95.3	128.3	108.1	136.1	200
Voltage	120	120	120	120	120
Height	29"	29"	29"	34"	36"
Weight	26 lbs.	26 lbs.	27 lbs.	33 lbs.	49 lbs.
Trash Capacity	8 gal.	8 gal.	8 gal.	8 gal.	8 gal.
Filtration	Tru-Seal® Microfiltration Closed Bag System				
Suggested Footage	6,000*	6,000*	6,000*	10,000*	20,000*
Quietness	70dB _A	74dB _A	70dB _A	76dB _A	75dB _A
Warranty	10 Year Transferable + Lifetime				
Protection	Resettable Minibreaker				
Construction	18 & 20 Gauge Steel				
Finish	Powder Coat				

Power units also available in 240 volts.

ModernDay Warranty

M.D. Manufacturing, Inc. warrants its Modern Day power units against electrical component failure for a period of ten (10) years. This warranty is transferable with the unit and is not solely limited to the original owner. Any parts (excluding filters) required within the first ten years will be furnished free of charge by the Authorized Dealer from whom the power unit was originally purchased. In addition, all Modern Day units are guaranteed for life against defects in materials and workmanship.

If an Authorized Dealer is not nearby, M.D. Manufacturing, Inc. will honor and perform required warranty services. The end user must return the unit to the factory freight pre-paid. This warranty does not apply to applications outside of North America, commercial applications, misuse, abuse, acts of God, operating without the filters, or units tampered with by unauthorized personnel.

Exterior Venting

Venting is optional but is required for confined locations. When venting model M965h, both exhaust ports should be vented separately.

*A central vacuum's square foot coverage should be based on factors including altitude, hours of use, complexity of pipe installation, length of furthest vacuum inlet, noise level desired, type and size of filtration, installation materials, and budget. The square footage recommendation on this page can be higher or lower when taking these factors into consideration.