

20 X UNIT SPECIFICATIONS

20 X UNIT FRONT



TANISAIR.com
by TanisTechnologies.com

- Voltage: 208v, 230v, 480v, 575v
- Motor: 5 HP premium grade
- AMPs-FLA: 208-230v (13.7-12.6), 460v (6.3), 575v (5)
- Drive: Belt and pulley system with auto-tensioner
- CFM: 8500
- Weight: 440 lbs.
- Dimensions: 67" L x 114" W x 31" H
- Construction: Steel, Aluminum, Bolted, Riveted, Sealed
- Finish: White, two-coat power coat
- Applications: Clean and circulate, whole shop filtration
- Db: 68
- Standard Features:
- Easy, no-tool filter changes
- Balanced/Machined Blower and drive assembly parts
- Greaseable bearings with easy-access grease fitting located outside unit
- Comes standard with spark arrestors
- Many filter options to suit your needs
- Easy-hang uni-strut mounting options available

20 X UNIT BACK



ONLY 45 MINUTES OF FILTER MAINTENANCE PER YEAR!!

ONE OF OUR MEDIUM SIZED UNITS, BUT AT 8500 CFM AND 4 LARGE INTAKES

THIS UNIT IS MOUNTED HORIZONTALLY AND CAN HAVE VENTED OR PIPED EXHAUST.

THIS UNIT IS SPECIALLY DESIGNED TO PULL FROM THE 4 CORNERS OF ANY AREA AND WORKS AS GREAT AS IT LOOKS!

These units are used where the the exhaust is piped away from the unit, creating a local low pressure area around the unit. This forces unwanted particles to the unit and away from people.

For all applications from SILICA and SMOKE to CARDBOARD DUST, THIS UNIT TAKES CARE OF IT FOR A SAFER SHOP

CALL ROD TANIS 616-990-8005

